PRODUCT CATALOGUE | 2025 | LG | THERMA VIII



Q BROWSE NOW

For more LG THERMA V information, please visit our website through QR code.





www.lg.com | http://partner.lge.com | Copyright © 2025 LG Electronics. All rights reserved.

• The images in this catalogue are scenes created to help customers' understand and may differ from the actual product.

• The specifications or product appearance may be subject to change without prior notice to improve the appearance and product performance.





INDEX



INTRODUCTION

004 LG Business Partnership & Infrastructure

006 The EU Building Sector

010 Heat Pump Technology

012 Regulations & Certifications

016 THERMA V Introduction

020 What is LG THERMA V

022 THERMA V Solution Overview

026 THERMA V Line-up Overview

028 THERMA V Line-up Introduction

034 Pre-Sales / Engineering Tools

036 ThinQ Seamless Connectivity

038 LG BECON cloud Service for THERMA V



SOLUTIONS

INDIVIDUAL SOLUTIONS

MONOBLOC

044 R290 Monobloc

048 - Control Unit (7/9/12/14/16 kW)

062 - Hydro Unit (7/9/12/14/16 kW)

076 - Combi Unit (7/9/12/14/16 kW)

094 R32 Monobloc S I (5/7/9/12/14/16 kW)

HYDROSPLIT

110 R32 Hydrosplit

114 - Hydro Unit (12/14/16 kW)

124 - Combi Unit (12/14/16 kW)

SPLIT

134 R32 Split

138 - Hydro Unit (4/6, 5/7/9 kW)

152 - Combi Unit (4/6, 5/7/9 kW)

HEAT PUMP WATER HEATER

174 R290 Round Type (100/150/200l)

182 R134a Square Type (200/270*l*)

COLLECTIVE SOLUTIONS

MONOBLOC

190 R32 Monobloc 51 kW

CASCADE SOLUTION

200 Cascade Control Unit

ACCESSORIES

208 Accessories Provided by LG

212 Electric Backup Heater

214 LG Wi-Fi Modem

215 Domestic Hot Water Tank





LG BUSINESS PARTNERSHIP & INFRASTRUCTURE

Infrastructure in Europe

LG Electronics' European Air Solution department is committed to ensuring your business success.

With 16 pan-European sales offices and academies, we seek to deliver on our promise of support, efficiency and proactivity throughout each stage of our business partnership.

Our highly competitive products are delivered through our dedicated European distribution centre to ensure a steady and reliable supply of inventory.

At our European Energy Lab, LG Business Solutions is developing a heat pump technology that is optimized for the varied European climates and weather patterns along with continuous product performance verification.





LG Europe R&D Center

LG Europe R&D Center is located in Eschborn Germany. Purpose of this laboratory where to test and verity LG Air Solution product's liability in advance and also to verify with local HVAC components compatibility.



LG Europe B2B Regional Head Office

LG Business Solutions Europe is based in Eschborn, Germany, with regional offices located throughout Europe. LG Europe B2B Regional Head Office is a control tower for European B2B business dealing with a wide range of products, including heat pumps and air conditioners. LG Electronics has a strong global network.





LG Heat Pump and Air Conditioning Academy

LG has set up 20 official heat pump and air conditioning academies in Europe, teaching much needed skills to thousands of current industry professionals including installers, consultants, designers, sales staff and service technicians. The academy program is designed to share expertise and educate these HVAC experts by providing a cutting-edge technical experience with the newest and most advanced technologies and equipment. Moreover, as LG's entire product range is installed on site, professionals can be trained in a realistic way that offers them the chance to experience the latest products first-hand.



European Distribution Center

LG's European Distribution Center is located in Tilburg, the Netherlands. Supplying products all over Europe, this distribution hub has contributed to smooth and rapid delivery, direct shipping for smaller orders and delivery tailored to air conditioners. Inventory efficiency of the hub is secured by the LG EU's established inventory pool.

THE EU BUILDING SECTOR

Buildings account for 40% of the total carbon emissions in Europe. The building stock that dates back to the 90s is three times less energy efficient than new construction built today.



OF EU ENERGY IS USED BY BUILDING SECTOR, MAKING IT THE SINGLE LARGEST ENERGY CONSUMER IN EUROPE



OF GREENHOUSE GAS EMISSIONS
COME FROM BUILDINGS

LG OUR MISSION

- $\ensuremath{\textcircled{1}}$ Create low-consuming or self-consuming innovations
- ② Build awareness and help people use energy more conservatively
- 3 Reimagine a building's usability, connectivity, convenience & health

^{*} Source: The European Commission website. https://commission.europa.eu/news/focus-energy-efficiency-buildings-2020-02-17_en



Re-Design

Improve Circularity of Raw Materials


Minimize environmental impact with our eco-conscious air conditioning solutions. By reducing reliance on finite resources such as plastic, aluminum, and copper, LG's innovative approach embraces a circular economy supply chain. This not only lessens carbon emissions during pre-manufacturing but also ensures resource efficiency, particularly for energy-hungry materials. Discover the sustainability of LG air conditioners, where recycled materials play a pivotal role. We conduct thorough stability and quality tests to guarantee optimal performance, leading the way toward a more sustainable and efficient future.

About LG Business Solutions: http://www.lg.com/global/business/about-lg-business

Amount of recycled plastic that LG used in previous years 27,000 Tons 2021 achievement 9,282 Tons 11,030 Tons 17,134 Tons 2030 target

Recycling Old Appliances

Many reusable resources are left in discarded products. Founded in 2001 through investment from LG, the Chilseo Recycling Center acts as a virtuous cycle of resources, from product design, use, and recovery, to disposal. Engineers collect old appliances from LG and other brands, then carefully take them apart. More than 40 kinds of renewable raw materials, including separated plastic, iron, and nonferrous metals, are reborn into new LG products.






THE EU BUILDING SECTOR

Re-Program

Achieve 95% in Waste Recycling at Production Sites by 2030

At LGE, we continuously invest in environmental facilities and improve our waste treatment processes with a view to being able to recycle 95% of waste generated at production sites around the world by 2030.





Innovate


Reduce Reliance Upon High GWP Refrigerant Gases

Refrigerant gases contribute to global warming even though their contribution is not the biggest. LG was the first manufacturer to launch an R32 monobloc air-to-water heat pump in 2018 and have also converted our full single split line up to R32 with 3 years lead time on the EU -driven planned ban in 2025. Also, LG is likely to put in place collection and recovery streams of refrigerant gases from end of life equipment at no extra cost for its customers.

Constant Product Efficiency Improvements

Electrically-driven heating and cooling equipment is LG's signature. What's more, we always aim at the highest energy ratings, generation after generation of product launching.

Reduce carbon emissions during use of 7 major products (baseline year 2020)



First Home Appliances Lighthouse Factory

In March 2022, Changwon LG Smart Park was named the first 'lighthouse factory' by the World Economic Forum (WEF). The WEF "Lighthouse" facilities implement Fourth Industrial Revolution technologies, such as the Internet of Things, big data, artificial intelligence and robots, into manufacturing and supply chain operations to deliver a wide range of benefits, from increased production efficiency to enhanced environmental sustainability. LG plans to apply the innovative, smart production technologies pioneered at LG Smart Park to a total of 26 LG production facilities in 13 countries, accelerating the digital transformation of its global manufacturing network by 2025.

Educate

Life Cycle Analysis

The Air Solution Division has assessed 4 product families, as regards their total life cycle impact, according to the French PEP certification scheme: it provides product greenhouse gas emissions from production, transport, use and end of life phases, over a period of 22 years.

Efficiency comparisons between THERMA V & differing technologies

+132%

Standard

improvement

Standard
electric heating & DH

Standard ectric heating & DHW * In Italy improvement
Standard

** In Poland

Certifications

LG Electronics is listed in the:

- DJSI World for 9 consecutive years
- 2020 Global Sustainability Leadership top 100, announced by Privileged United Nationals Sustainability Development Goals (UNSDGs)
- 6th place in the top 100 World Sustainable Management Companies by Wall Street Journal
- ECOVADIS Platinum certified in 2021 & 2023






What is an Air-to-Water Heat Pump System?

Modern Technology to Replace Conventional Boilers


Historically, conventional heating systems have used either oil or gas or have represented direct electric heaters. In such conventional heating systems, environmental aspects such as the pollution produced by fossil fuel use have been overlooked. Over the last years, the interest in these environmentally friendly devices has been increasing and in order to respond to the growing demand for eco-conscious devices, LG has further developed its heat pump technology to produce more efficient, environmentally friendly products.



Modern Technology for Renewable Energy

010

The term "Heat Pump" refers to a technique that pumps heat from renewable energy sources, like the air, ground and water. A heat pump device transforms this energy into a usable heat source via the refrigerant cycle. With THERMA V heat pump technology about 75% of the energy needed to provide heating and hot water comes from a natural air source⁻¹⁾




¹⁾ The efficiency ratio is to help general understanding and is based on the Seasonal Coefficient of Performance (SCOP) of THERMA V R290 Monobloc under Low Temperature & Average Climate conditions, which is higher than 5. The actual efficiency may vary with water and outside temperatures.

LG Electronics Leads the Way in Heat Pump Technology

As a leading HVAC supplier, LG's heating product portfolio comprises a wide range of highly energy efficient renewable energy systems, providing the right heating solution for any type of requirements and/or buildings.

How do Air-to-Water Heat Pumps work?



Temperature & Average Climate conditions, which is higher than 5. The actual efficiency may vary with water and outside temperatures.

INTRODUCTION

INDIVIDUAL SOLUT

REGULATIONS & CERTIFICATIONS


Energy Label

Energy Labels

The EU energy label has been a key driver for helping consumers choose products which are more energy efficient. At the same time, it also encourages manufacturers to drive innovation by using more energy efficient technologies. The energy label was recognized by 93% of consumers and 79% considered it when buying energy efficient products, according to the special eurobarometer 492 carried out in the 28 EU member states during 2019. Starting from 2013, the regulations apply to heat pumps, as well as to water heaters since 2015. As of September 26th, 2019, the energy efficiency scale for seasonal space heating ranges from A+++ to D, with A+++ being the most efficient. The water heating energy efficiency scale for the declared load profile for combination heat pumps ranges from to A+ to F, with A+ being the most efficient.

Information on the Energy Label

The energy labels provide minimum necessary information such as: manufacturer's name, manufacturer's model name, seasonal space heating energy efficiency class under average climate condition from A+++ to D in medium/low temperature applications (55°C/35°C), rated heat output under average, colder and warmer climate conditions in medium/low temperature applications (55°C/35°C), European map displaying the three temperature zones, the sound power level indoors and/or outdoors. In addition, just for combination heat pumps, the energy label also includes Water heating energy efficiency class under average climate condition from A+ to F at declared load profile, while the seasonal space heating energy efficiency class and rated heat output are indicated only for the medium temperature application (55°C).



Heat pump space heaters

- Manufacturer's name or trade mark
 Manufacturer's model name
- Space heating function
 Seasonal space heating energy efficiency class under average climate condition from
- applications (55°C/35°C)

 Rated heat output (kW) under average, colder and warmer climate conditions in medium/low temperature applications

A+++ to D in medium/low temperature

medium/low temperature applications (55°C/35°C)

Operating noise for indoor and outdoor

European map displaying the three

temperature zones

* This energy label may differ depending on local regulations (for example in the UK).

ENERG OF A CONTROL OF A CONTROL

Heat pump combination heaters

- Manufacturer's name or trade mark
- Manufacturer's model name
- Space heating function
 Seasonal space heating energy efficiency class under average climate conditions
- class under average climate conditions from A+++ to D in medium temperature applications (55°C)
- Water heating energy efficiency class under average climate conditions from
 A+ to F
- Rated heat output (kW) under average, colder and warmer climate conditions in medium temperature application (55°C)
- Operating noise for indoor and outdoor
 European map displaying the three temperature zones
- * This energy label may differ depending on local regulations (for example in the UK).


Nearly Zero Energy Building (nZEB)

Nearly Zero Energy Building

Nearly Zero-Energy Building (nZEB) means a building that has a very high energy performance, while the nearly zero or very low amount of energy required should be covered to a very significant extent by energy from renewable sources, including energy from renewable sources produced on-site or nearby. The Energy Performance of Buildings Directive (EPBD) requires that EU countries ensure that all new buildings are nearly zero-energy by the end of 2020, while all new public buildings had to be nearly zero-energy after 31 December 2018. As concrete numeric thresholds or ranges are not defined in the EPBD, each EU member state defines their Nearly Zero-Energy Buildings (nZEB) in a flexible way, taking into account their country-specific climate conditions, primary energy factors, calculation methodologies, building traditions and current ambitions.

How LG THERMA V Supports to Nearly Zero Energy Buildings (nZEB)

In general, consultants use software programs to evaluate nZEB satisfaction of a new building. LG has been registering THERMA V products in their database so that our THERMA V products can be used directly in these software programs such as BENG in Netherlands, SAP in UK and RE2020 in France.



LG THERMA V energy labels | Energy labels for each LG THERMA V model can be found on the websites below.



LG.COM Compliance Information

https://www.lg.com/global/ support/cedoc/cedoc

Browse now Q



European Product Registry for Energy Labelling

https://eprel.ec.europa.eu/screen/product/

snaceheaters

Browse now Q



Netherland -

https://bcrg.nl/nl/databanken/energieprestaties/databank/

Browse now Q



SAI

https://www.ncm-pcdb.org.uk/sap/pcdbsearch.jsp?type=362&pid=31

Browse now Q



France -RE2020

https://www.edibatec.org/base-produits/

Browse now Q

REGULATIONS & CERTIFICATIONS

Keymark



The heat pump Keymark is a voluntary, independent European certification mark (ISO type 5 certification) for all heat pumps, combination heat pumps and hot water heaters (as covered by ecodesign, EU regulation 813/2013 and 814/2013). It is based on independent, third party testing and demonstrates compliance with product requirements as set in the heat pump Keymark scheme rules and with efficiency requirements as set by ecodesign lot 1 and lot 2. The heat pump Keymark scheme is owned by the European committee for standardization (CEN). The certificates are granted by independent certification bodies to products fulfilling all requirements of the scheme. LG THERMA V products are certified with the heat pump Keymark. Please, refer to the web page below for details.



https://keymark.eu/en/products/heatpumps/certified-products



Eurovent

014



Established in 1993, Eurovent certification is recognized as a world leader in third-party product performance certification in the heating, ventilation, air conditioning and refrigeration fields. Its major certification brand 'Eurovent Certified Performance' has become over the years a major European certification. Today over 67% of HVAC-R products sold in Europe hold this certification. LG THERMA V products are certified with Eurovent. Please, refer to the web page below for details.



https://www.eurovent-certification.com/en/



Certifications

All heat pumps and water heaters in the European market are continuously tested by various certification schemes. These are usually the basis for qualifying for subsidy programs in each country.

MCS



MCS certification is a mark of quality and demonstrates compliance to industry standards. It is supported by the department for business, energy & industrial strategy of the UK. In particular, MCS certification demonstrates the quality and reliability of products in the renewable technology sector and it ensures that products are compliant with the UK regulations. LG THERMA V products are certified with MCS. Please, refer to the web page below for details.



https://mcscertified.com/product-directory/



EHPA



The EHPA quality label is a label that shows the end-consumer a quality heat pump unit or model range on the market. The heat pumps that receive the label need to undergo tests according to the international standard EN14511 and EN16147. These tests are executed by EN17025 accredited test centres. LG THERMA V products are certified with the EHPA quality label for Austria, Germany and Switzerland. Please, refer to the web page below for details.



Browse now Q

THERMA V_{TM} INTRODUCTION



THE SUSTAINABLE CHOICE

Today's informed consumer will consider multiple factors when choosing a heating solution, like an Air-to-Water Heat Pump (AWHP) to include user-friendliness, reliability and regulation-compliance. Shifting regulations year after year exceedingly impact the European customers' choice of heating products.

With refrigerant regulations changing around the world, it's time to move to a more eco-conscious solution. THERMA V R290 Monobloc uses natural R290 refrigerant which has a lower tonne of CO₂ equivalent index than other gases such as R32. Possible carbon emission from refrigerants is reduced by 99.7% compared to previous R32 Monobloc. The R290 can be vented directly into the atmosphere without any impact on the climate because it's ecoconscious refrigerant with nearly zero carbon emissions.

LG Electronics' THERMA V line-up fulfills both European regulations as well as customer needs.

THERMAV

 $_{
m 016}$



FORM MEETS FUNCTION: THERMA V IN DARK DAWN GRAY

Outdoor units are now transformed with an elegant monotone design, showcasing a distinctive style through their design alone while elevating the aesthetic appeal of home's exterior.

Its refined new design ensures seamless integration with a wide variety of home and building exteriors.

Designed with European environmental considerations in mind, it not only offers aesthetic excellence but also ensures exceptional installation efficiency.

This design has been applied not only to the R290 model but also to the R32 Monobloc S II, achieving design unity and maximizing display value by featuring a wave-shaped grille that harmonizes simplicity and a unique pattern.

SIMPLER INSTALLATION

BETTER DESIGN

(1) LG


MORE COMFORTABLE LIVING

THERMA V... WHAT IS LG THERMA V?



LG's Advanced Heating Technology

The LG THERMA V Air-to-Water Heat Pump system boasts an advanced heating technology that can minimize energy consumption more than any other solution in the market. In addition, it has been specially designed to provide a valuable living space and domestic hot water supply to both new build and renovated homes.



THERMA V_{IM}

Space heating

The wide span THERMA V systems with high efficiency can cover heating loads of various types of houses.


Domestic hot water

As the hot water efficiency becomes more and more important, THERMA V can provide an optimized solution for this.

Space cooling

THERMA V is a single device that can also provide a cooling solution besides the heating and hot water provided by boilers.

High Efficiency and Low CO₂ Emission



Benefits of LG THERMA V



For Installers and Service Providers

- Time savings with features for quicker installation and commissioning
- Less manpower for handling with the compact size and light weight
- Less service visit with high reliability and durable equipment
- Intuitive controller interface for all LG products, requiring less training
- Remote control, monitoring and diagnosis to avoid unnecessary site visits
- Clip connections for quick maintenance and no need for special tools



For Consultants and Designers

- Variety of software to support selection and designing THERMA $\mbox{\sc V}$
- Multiple solutions with space heating, cooling and DHW supply
- Wide leaving water temperature compatible with various heat emitters
- Valuable space savings with the small footprint
- Excellent heating performance even at low ambient temperature
- Optimal system interoperability open modbus with 3rd party controller
- Adapts operation to ESS battery output, maximizing self-consumption of locally produced PV energy



For Homeowners

- Energy saving by utilizing renewable energy and high efficiency equipment
- Multiple solutions with space heating, cooling and DHW supply
- Economic support through domestic renewable heat incentive programs
- Investment cost savings thanks to the compatibility with existing heating system like radiator, boiler, etc.
- Valuable space savings with the small footprint
- No disturbing caused to neighbors with low noise
- Low repair cost and high reliability with durable equipment
- Convenient control by user-friendly remote controller
- Remote connectivity for control and monitoring via LG ThinQ

Split

THERMA V_{TM} **SOLUTION OVERVIEW**

Individual Solutions

			Monobloc		
Line-up		Though the state of the state o	→	₩	•
		R290 Monobloc Control Unit	R290 Monobloc Hydro Unit	R290 Monobloc Combi Unit	R32 Monobloc S I
		1 Ø: 7/9/12/14/16 kW 3 Ø: 7/9/12/14/16 kW	1 Ø: 7/9/12/14/16 kW 3 Ø: 7/9/12/14/16 kW	1 Ø: 7/9/12/14/16 kW 3 Ø: 7/9/12/14/16 kW	1 Ø: 5/7/9/12/14/16 kW 3 Ø: 12/14/16 kW
Capacity			-		
Application			- \ \ -\	*	
Energy labe	el	Space heating A+++ 35°C A+++ 55°C A+++ Combination with OSHW-200F (Profile L)	Space heating A+++ 35°C A+++ 55°C A+++ Combination with OSHW-200F (Profile L)	Space heating A+++ =35°C A+++ =55°C DHW heating	Space heating A++ 35°C A++ 55°C A++ Combination with OSHW-200F (Profile L)
Certificatio	ns	SG CHITMEN	AUTOVITO AUTOVI	LAND SECTION S	AUTOVERS SG Rect
Operation	Outdoor air	-28 ~ 35°C	-28 ~ 35°C	-28 ~ 35°C	-25 ~ 35°C
range (heating)	Leaving water	15 ~ 75°C	15 ~ 75°C	15 ~ 75°C	15 ~ 65°C
Operation	Outdoor air	5 ~ 48°C	5 ~ 48°C	5~48°C	5~48°C
range (cooling)	Leaving water	5 ~ 27°C	5 ~ 27°C	5 ~ 27°C	5 ~ 27°C
Operation r	ange (hot water)	15 ~ 65°C¹)	15 ~ 65°C¹)	15 ~ 65°C¹)	15 ~ 55°C¹)
Domestic h	ot water tank included	Х	Х	○ (200 ℓ)	X
Backup hea	ter included	Х	0	0	X (accessory)
F-gas licens	se needed	Х	Х	Х	Х
Wi-Fi remot	te control via ThinQ ²⁾	0	0	0	0

	The Control of the Co		The Control of the Co
R32 Hydrosplit Hydro Unit	R32 Hydrosplit Combi Unit	R32 Split Hydro Unit	R32 Split Combi Unit
1 Ø: 12/14/16 kW 3 Ø: 12/14/16 kW	1 Ø: 12/14/16 kW 3 Ø: 12/14/16 kW	1 Ø: 4/6 kW (U24A) 1 Ø: 5/7/9 kW (U36A)	1 Ø: 4/6 kW (U24A) 1 Ø: 5/7/9 kW (U36A)
LG.	LG LG		
	÷		
Space heating A+++ =35°C A++ =55°C	Space heating A+++ = 35°C A++ = 55°C DHW heating	Space heating A+++ = 35°C A++ = 55°C	Space heating A+++ =35°C A++ =55°C A++ DHW Profile L (4/6 kW) Profile L (5/7 kW) Profile X (9 kW)
AUROVENI SG	AMIGNATI SG	AUTOVENT CO SG Recty	eunover en europe en europ
Recdy Recdy Materials Recdy	Redy Man has had been seen as a seen	Su chipis .	muchtpia.
-25 ~ 35°C	-25 ~ 35°C	4/6 kW: -20 ~ 35°C 5/7/9 kW: -25 ~ 35°C	4/6 kW: -20 ~ 35°C 5/7/9 kW: -25 ~ 35°C
15 ~ 65°C	15 ~ 65°C	4/6 kW: 15 ~ 55°C 5/7/9 kW: 15 ~ 65°C	4/6 kW: 15 ~ 55°C 5/7/9 kW: 15 ~ 65°C
5 ~ 48°C	5~48°C	5~48°C	5 ~ 48°C
5 ~ 27°C	5 ~ 27°C	5 ~ 27°C	5 ~ 27°C
15 ~ 55°C ¹⁾	15 ~ 55°C ¹⁾	4/6 kW: 15 ~ 50°C ¹⁾ 5/7/9 kW: 15 ~ 55°C ¹⁾	4/6 kW: 15 ~ 50°C ¹⁾ 5/7/9 kW: 15 ~ 55°C ¹⁾
X	○ (200 ℓ)	X	○(200ℓ)
X (accessory)	0	0	0
X	Х	0	0
0	0	0	0

Hydrosplit

¹⁾ With electric boost heater up to 80°C possible.

²⁾ Wi-Fi modem (PWFMDD200) should be purchased and installed separately.

THERMA V_{IM} **SOLUTION OVERVIEW**

Individual Solutions

		Heat Pump V	Vater Heater
Line-up		ThinQ	ThinQ
		R290 Round Type 1 Ø: 100/150/200 ℓ	R134a Square Type 1 Ø: 200/270 ℓ
Capacity			
Application			
Energy labe	el	DHW 100£ (profile M) heating 150/200ℓ (profile L)	DHW 200/270ℓ (profile L)
Certificatio	ns	SG	SG (Recety
Operation	Air temperature (Heat pump)	-7 ~ 48°C	-5 ~ 48°C
range	Max. water temperature	up to 75°C	up to 60°C
Compresso	r type	Constant speed rotary	Inverter twin rotary
Heating ele	ment included	0	0
F-gas licens	se needed	X	X
Wi-Fi remo	te control via ThinQ	0	0

Collective Solutions

		Monobloc
Line-up		R32 Monobloc 51 kW
Capacity		3 Ø: 51 kW
Application	ı	*
Energy labe	el	Space heating A++ =35°C A++ 55°C
Certificatio	ns ¹⁾	SG Redy Market
Operation	Outdoor	-25 ~ 35°C
range (heating)	Leaving water	25 ~ 60°C (65°C) ²⁾
Operation range	Outdoor air	10 ~ 48°C
(cooling)	Leaving water	5~27°C
Operation r (hot water)		25 ~ 55°C³)
Domestic h tank includ		Х
Backup hea	ter	X
F-gas licens	se needed	X
Wi-Fi remo		0

i) The our	er certifica	1011210112	VOC INIOIII	ו כ שטוענ	KVV ale ul	idei bic	ryress,	
2) The leav	ving water	temperatu	re of 65°	C is pos	sible only	when a	backup	heater is

installed.

- 3) With electric boost heater up to 80°C possible
 4) Wi-Fi modem (PWFMDD200) should be purchased and installed separately.

		Cascade
Line-up		
		Cascade Control Unit 8 Units 1)
Max. numboutdoor un that can be	its	
Application	1	* *
Compatible	line-up	R290 Monobloc ²⁾
Operation range 3)	Outdoor	-28 ~ 35°C
(heating)	Leaving water	15 ~ 70°C
Operation	Outdoor	5~48°C
range 3) (cooling)	Leaving water	5 ~ 27°C
Operation r (hot water)		15 ~ 65°C ^{3) 4)}
Indoor unit separately Cascade co	from	X
Wi-Fi remo		0

¹⁾ All units connected to Cascade Control Unit must be configured with models of the same capacity.

- 3) When combined to R290 Monobloc
- 4) With electric boost heater up to 80°C possible
 5) Wi-Fi modem (PWFMDD200) should be purchased and installed separately.

¹⁾ WH20S.F5 / WH27S.F5 2) WH20STR2.FA / WH27STR2.FA

²⁾ Only R290 Monobloc outdoor units manufactured after June of 2025 are compatible with cascade control unit.

THERMA V_{IM} **LINE-UP OVERVIEW**

Line-up	Unit	Туре	Power supply	Appearance	4 kW	6 kW	Appearance	5 kW
	Outdoor	_	1 Ø / 230 V				Ole	
	Unit	-	3 Ø / 400 V					
R290		Control Unit	Common					
Monobloc	Indoor	Hydro	1 Ø / 230 V				•	
	Unit	Unit	3 Ø / 400 V				Ē	
		Combi	1 Ø / 230 V				=	
		Unit						
R32	Set	_	1 Ø / 230 V				016	HM051MRS UA40
Monobloc S I	261		3 Ø / 400 V					
Outdoor Unit	Outdoor		1 Ø / 230 V					
	Unit		3 Ø / 400 V					
R32 Hydrosplit	Indoor	Hydro Unit	Common					
Unit	Unit	Combi Unit	Common					
	Outdoor Unit	-	1 Ø / 230 V	© LS	HU041MR U20	HU061MR U20	E G	HU051MR U44
R32 Split	Indoor	Hydro Unit	1 Ø / 230 V	=	HN061:	3M NK5		HN091MR NK5
	Unit	Combi Unit	1 Ø / 230 V	E	HN061	3T NKO		HN0913T NK0
R32 Monobloc	Outdoor Unit	-	3 Ø / 400 V					
51 kW	Indoor Unit	Control Unit	1 Ø / 230 V					

¹⁾ This is the power specifications of the backup heater inside indoor unit, and the main power supply of the indoor unit is single phase (10/230V).

Line-	up	Туре	Power supply	Appearance	100 ℓ	Appearance	150 <i>l</i>	Appearance
Heat Pui	np	Round Type	1 Ø / 230 V		WH10ESF0 HA ¹⁾		WH15ESF0 HA ¹⁾	
Water H	eater	Square Type	1 Ø / 230 V					

1) SG Ready certified	ifind	corti	Doody	100	1)

7kW	9 kW	Appearance	12 kW	14 kW	16 kW	Appearance	51 kW
HM071HF UB40	HM091HF UB40		HM121HF UB60	HM141HF UB60	HM161HF UB60		
HM073HF UB40	HM093HF UB40		HM123HF UB60	HM143HF UB60	HM163HF UB60		
PHCS0 E	ENCXLEU		PHCS0 ENCXLEU				
HN1616HC NK0 ²⁾		*		HN1616HC NK0 ²⁾			
HN1639HC NK0 ³⁾		=		HN1639HC NK0 ³⁾			
HN1616HY NK0 ²⁾				HN1616HY NK0 ²⁾			
HN1639HY NK0 ³⁾				HN1639HY NK0 ³⁾			
HM071MRS UA40	HM091MRS UA40	A •••	HM121MRS UB40	HM141MRS UB40	HM161MRS UB40		
		9	HM123MRS UB40	HM143MRS UB40	HM163MRS UB40		
		0:	HU121MRB U30	HU141MRB U30	HU161MRB U30		
		0	HU123MRB U30	HU143MRB U30	HU163MRB U30		
		·	HN1600MC NK1				
		=	HN1616Y NB1				
HU071MR U44	HU091MR U44						
HN091	MR NK5						
HN091	3T NKO						
						0.0	HM513MR UXC0
						-	PHCSL0 ENCXLE

200 l	Appearance	270 l
WH20ESF0 CA ¹⁾		
WH20STR2 FA ¹⁾ WH20S F5		WH27STR2 FA ¹⁾ WH27S F5

4)	00	D	-I		
1)	20	Kea	av	certif	

Line-up	Power supply	Appearance	Model name
Cascade Control Unit	1 Ø / 230 V	•	PHCM0 ENCXLEU

²⁾ Combinations for 1 Ø outdoor units
3) Combinations for 3 Ø outdoor units

THERMA V.

LINE-UP INTRODUCTION

R290 Monobloc




The new R290 Monobloc is a super-quiet, future-conscious heat pump that uses the R290 refrigerant which has lower GWP of only three. From an aesthetic standpoint, refined gray design allows it to seamlessly harmonize with a diverse range of home and building exteriors, and from a technical standpoint, it is designed to be low-noise, so you don't have to worry about causing noise pollution to neighbors. The LG THERMA V R290 Monobloc is available in three different combinations (Control Unit, Hydro Unit or Combi Unit) depending on the customers' needs. By adopting a highefficiency compressor leveraging injection technology, R290 Monobloc can deliver a leaving water temperature of up to 75°C all year round. Thus, this unit is suitable for home renovations due to high water temperature compatibility with existing radiators.

Due to LG's advanced compressor technology, the THERMA V R290 Monobloc keeps indoor spaces comfortably warm-even when outdoor temperatures drop as low as -28°C.







^{*} The power supply is shown based on the outdoor unit.



R32 Monobloc SII



The THERMA V R32 Monobloc S II is the next generation model that continues the legacy of the LG THERMA V R32 Monobloc S. The new generation's sleek look matches that of the rest of the modernized lineup, while maintaining the excellent performance of the existing R32 Monobloc S, and that the single fan design has been applied to not only the 5, 7, and 9 kW but also the 12, 14, and 16 kW models. Along with these design changes, various features and installation conveniences that were developed from the R290 Monobloc have been reflected.






Line-up	Capacity (kW)	4.0	5.5	6.0	7.0	9.0	12.0	14.0	16.0
R32	1 Ø 230 V		•		•	•	•	•	•
Monobloc S I	3 Ø 400 V						•	•	•

R32 Hydrosplit Hydro Unit



The LG THERMA V Hydrosplit series separates the indoor unit (IDU) and outdoor unit (ODU), connecting them via water pipes. The unit's heat exchanger is located within the ODU, reducing the risk of indoor refrigerant leakage. THERMA V R32 Hydrosplit Hydro Unit is a solution providing space heating, cooling and DHW supply with high installation flexibility thanks to the characteristic of being a wall mounted type. Its wall-mounted design frees up floor space and speeds up installation due to its lightweight build. With the unit located indoors-often in a machine room-access for maintenance is quick and hassle-free.





Line-up	Capacity (kW)	4.0	5.5	6.0	7.0	9.0	12.0	14.0	16.0
R32 Hydrosplit	1 Ø 230 V						•	•	•
Hydro Unit	3 Ø 400 V						•	•	•

^{*} The power supply is shown based on the outdoor unit


THERMA V_{IM}

LINE-UP INTRODUCTION

R32 Hydrosplit Combi Unit



The LG THERMA V Hydrosplit series separates the indoor unit (IDU) and outdoor unit (ODU), connecting them via water pipes. The unit's heat exchanger is located within the ODU, reducing the risk of indoor refrigerant leakage. THERMA V R32 Hydrosplit Combi Unit combines an indoor unit, a water tank and complex piping into a single, space-saving solution that is able to provide space heating, cooling and DHW supply. Relatively compact and lightweight, the innovative all-in-one system is easy to install and operate, and boasts outstanding reliability and efficiency. Since there is no need to install a separate domestic hot water tank for hot water supply, space is not wasted, and the concept with all-in-one enables quick installation.






Line-up	Capacity (kW)	4.0	5.5	6.0	7.0	9.0	12.0	14.0	16.0
R32 Hydrosplit	1 Ø 230 V						•	•	•
Combi Unit	3 Ø 400 V						•	•	•

^{*} The power supply is shown based on the outdoor unit.

R32 Split Hydro Unit



The LG THERMA V R32 Split Hydro Unit is a hydro type system consisting of an indoor unit and an outdoor unit. The two units are connected by refrigerant piping only, thus hydronic components such as plate heat exchanger, expansion tank and water pump are located within the indoor unit. Due to the split nature, freezing will not compromise this unit regardless of outdoor ambient temperatures. The outdoor unit is on offer in 4/6 kW and 5/7/9 kW capacity range. R32 Split 4/6 kW model is suitable for new build houses that are well insulated and require a small heating load, while R32 Split 5/7/9 kW model is adapted for both new build and renovation projects.






Line-up	Capacity (kW)	4.0	5.5	6.0	7.0	9.0	12.0	14.0	16.0
R32 Split	1 Ø 230 V	•	•	•	•	•			
Hydro Unit	3 Ø 400 V								

^{*} The power supply is shown based on the outdoor unit.

R32 Split Combi Unit



The LG THERMA V R32 Split Combi Unit is a domestic hot water supply, space heating and cooling solution that conveniently combines an indoor hot water tank with a separate outdoor unit. THERMA V R32 Split Combi Unit is the perfect space-saving solution for residential applications because hydronic components like the Domestic Hot Water (DHW) and buffer tanks, which are typically installed separately, are fully integrated. Its split design eliminates the risk of freezing, delivering reliable operation against harsh outdoor ambient temperatures. The outdoor unit is on offer in 4/6 kW and 5/7/9 kW capacity range. R32 Split 4/6 kW model is suitable for new build houses that are well insulated and require a small heating load, while the R32 Split 5/7/9 kW model is adapted for both new build and renovation projects.





Line-up	Capacity (kW)	4.0	5.5	6.0	7.0	9.0	12.0	14.0	16.0
R32 Split	1 Ø 230 V	•	•	•	•	•			
Combi Unit	3 Ø 400 V								

^{*} The power supply is shown based on the outdoor unit.

033

LINE-UP INTRODUCTION

R290 Heat Pump Water Heater



The new refrigerant technology allows the unit to efficiently reach outlet temperatures of up to 75°C. Available in sizes ranging from 100 to 200 liters, the unit is developed to meet the capacity needs of each household. Designed with modern living in mind, the R290 Heat Pump Water Heater blends seamlessly into any indoor space. Plus, its ultralow noise level-quieter than a typical office-ensures everyday comfort without disruption. The magnesium anode and ICCP (Impressed Current Cathodic Protection) help to always keep the tank clean by preventing interior corrosion.





Line-up	Capacity (1)	80 £	100 l	150 l	200 l	270 ℓ	300 l
R290 Heat Pump	1 Ø 230 V		•	•	•		
Mater Heater							

R134a Heat Pump Water Heater




LG inverter compressor and two heater coils on the top and bottom provide hot water quickly. LG unit's exclusive square shape and luxury silver color make it an excellent fit for any interior design. With the LG ThinQ smartphone app, users can easily control and monitor the heat pump, check for current water temperatures, setting operating schedules and more. Four operating modes help the customer use the water heater more effectively.






Line-up	Capacity (1)	80 l	100 l	150 ℓ	200 ℓ	270 l	300 l
R134a Heat Pump Water Heater	1 Ø 230 V				•	•	

R32 Monobloc 51 kW



The LG R32 Monobloc 51 kW is a large capacity heat pump that provides a collective central heating solution for multi-family houses or light commercial buildings. Ideal for locations that require reliable heating and cooling year-round, this air to water heat pump offers a versatile solution.

Operating efficiently as a single system, it is well-suited for various commercial spaces including multi family house, office buildings, schools and universities.






Line-up	Capacity (kW)	18.0	24.0	32.0	36.0	48.0	51.0	64.0	80.0	96.0	112.0	128.0
R32 Monobloc 51 kW	3 Ø 400 V	F	Recommend	to use Caso	cade Solutio	n	•		Recommend	l to use Casc	ade Solution	n

Cascade Control Unit



The LG Cascade Control Unit is an advanced heating solution designed to manage up to 8 units of the THERMA V system with a single controller. This centralized control enhances system efficiency and simplifies operation, making it an ideal choice for optimizing heat pump performance in multiunit applications.

Cascade system offers efficient performance across all heating capacity ranges, adapting to fluctuating demand while maintaining reliability and reducing unnecessary energy consumption.





Line-up	Capacity (kW)	18.0	24.0	32.0	36.0	48.0	64.0	80.0	96.0	112.0	128.0
Cascade	Combination	9 kW x 2 Units	12 kW x 2 Units	16 kW x 2 Units	12 kW x 3 Units	16 kW x 3 Units	16 kW x 4 Units	16 kW x 5 Units	16 kW x 6 Units	16 kW x 7 Units	16 kW x 8 Units
Control Unit	No of Units		2 Units		3 U	nits	4 Units	5 Units	6 Units	7 Units	8 Units

^{*}LG recommends above combinations as much as possible even though up to eight (8) R290 Monobloc outdoor units of the same capacity can be connected.

PRE-SALES / **ENGINEERING TOOLS**

Pre-sales / Engineering Tools

LG provides a variety of software to support THERMA V for all customers including designers, installers, and end users.

1, LATS THERMA V

LATS THERMA V is a web based simulation tool that enables to choose the optimal THERMA V model from various capacity range and simulates its energy cost comparing to other heating solutions. Furthermore, customer is easily able to simulate payback compared to a conventional system such as a gas boiler, electric boiler by using LATS THERMA V.





There are 3 types project in LATS THERMA V WEB.

1. Model Selection: Select suitable model based on the design conditions you input.



2. Diagram: Generate piping / wiring diagrams in DWG format based on the design conditions and other selected applications.




3. Sound Simulation: Provide noise simulation results according to distance from house.



2. LG Energy Lab

LG Energy Lab online is a web version tool that can print energy labels. It is easy to use because it is composed of a user-friendly UI, and provides additional functions such as contact function and project management function.






3. LGMV

LGMV is a useful engineering tool that monitors THERMA V's real-time refrigerant and water cycle. It assists installers with effective and efficient start-up and commissioning after the THERMA V installation. LGMV enables service/field engineers to detect the errors and troubleshooting for fast and reliable problem solving.


* LGMV is available on the LG partner portal.



4. LG THERMA V Selector

The LG THERMA V Selector is a mobile application for designers, installers and end users, which provides various real-life simulations. An energy simulation can quickly indicate energy consumption and cost as well as CO₂ emission values that can be vastly reduced from conventional heating systems using minimal input

With both model selection and energy simulation tools, quick and accurate selection is made possible with detailed input values such as desired system configuration, required heating and Domestic Hot Water (DHW) load, which will calculate payback, result in a faster energy simulation and generate cost comparisons. Sound level can also be calculated through simulations based on the installation environment.



ThinQ SEAMLESS CONNECTIVITY

Smart Control, Smarter Life

LG ThinQ, a smart phone app, allows users to monitor and manage compatible LG products remotely, which means they can set the temperature and regulate the use of their THERMA V anytime and anywhere.

In most EU countries, LG ThinQ technology also works with Google Assistant, letting users control their THERMA V with voice commands.



PWFMDD200 (LG Wi-Fi Modem) / PWYREW000 (10 m extension connect cable in between THERMA V indoor and LG Wi-Fi Modem) could be required depending on

- * Search "LG ThinQ" on Google market or App store, then download the app.
- * Google assistant voice control may be restricted in use and language in some countries.
- * Google and Google Home are trademarks of Google LLC.
- * Voice-enabled smart speaker device is not included

How to install the LG ThinQ app

Search and install for the LG ThinQ application from the Google Play or Apple App Store on a smart phone.

For iOS users







Download now 🕹)

How to connect THERMA V to the LG ThinQ app




A ThinQ guide for **LG THERMA V**



In the video below, see how to install Wi-Fi modem and connect THERMA V and ThinQ.



In the video below, learn how to smartly monitor and control your THERMA V with ThinQ





Connect and Control from anywhere, anytime

LG ThinQ allows end users to easily control their heating system in away they have never done before. Let them experience smart control of THERMA V with just the tap of a button. Even when outside, they can operate the THERMA V remotely.




Simple control with voice assistant

Tell THERMA V exactly what is needed. Say, "Turn on/off the THERMA V" and the AI speaker will listen and turn on/off the THERMA V.



Efficient energy monitoring


The LG ThinQ app continuously monitors THERMA V. Whether it's everyday maintenance or something else, the app allows you to easily monitor energy usage.








ThinQ mobile app



Space heating / Cooling control

Hot water control

Useful features



Energy monitoring

Widget on home screen

(Android)

This image is intended to help you understand, and there may be some differences in actual use.

^{*} Control via widgets is only possible with the Android app.


LG BECON CLOUD SERVICE






What is LG BECON cloud Service?

LG BECON cloud service is a cloud-based service that remotely monitors a customer's heating system via PC, tablet or mobile anytime, anywhere. The operation status of the heat pump can be monitored at a glance as well as the past operation history. In the event of an issue, the cause can be identified in advance and the repair can be completed during a one-time visit. For more details and service contract, please contact your LG regional service contact.



Target Customer and Benefits

Service partners / Installers



☑ Save time and cost

- One time visit with right parts
- No need pre-visit for diagnosis


☑ Quality of service

- Better service to end users with accurate diagnosis and fast repair

✓ Increased business opportunity

- Combine product + service offer
- Make more installation / repairs

End-users



☑ Enjoy peace of mind

- Be serviced at once or faster
- Be confident that immediate and quality of service will be provided in case of an error

✓ Less constraints

- No need to be at home for first diagnosis
- Monitor the operation status and control the system remotely

Key Features



Management at a glance

Monitoring status of customers

• Interactive map view or list view



Energy monitoring

Providing warning if energy usage is excessively

• Display estimated power consumption by selfcalculation



Operation and error history

Providing operation data and error history to quickly identify the issue

• Operation history, error history, setting history,



Error notification by e-mail

Providing an e-mail notification automatically when an error occurs

• Possible to identify immediately and take a fast



Remote control via cloud

• Schematic view or table view

• Current status and historical data

Preventing unnecessary site visit caused by simple operation mistake

Monitoring with visualized schematic

• Cycle monitoring, sensor and actuator monitoring

• Operation mode (heating / cooling / DHW), target temperature

DHW operation

• Emergency operation, low noise operation, quick


LG BECON CLOUD SERVICE

for THERMA VI

Why LG BECON cloud Service?


Quick service response time

Saving time and cost thanks to remote diagnosis of operation cycle without access to product.




Accurate diagnosis

Accurate diagnosis for cause of failure can be done by utilizing the error code and cycle data when an actual failure occurs.




Remote device control

With single account, maintenance service provider (or installer) can control their customer's sites remotely. As a result, site visit is not needed for minor issues, such as adjusting temperature or mode.



Error notification by e-mail

Providing an e-mail notification automatically when an error occurs, making it possible for maintenance service provider (or installer) to immediately identify and quickly react.




Energy monitoring

Power consumption based on self-calculation is recorded and displayed. Maintenance service provider (or installer) can provide warning if energy usage is excessively high.



ThinQ for end-users

Without purchasing additional Wi-Fi Modem, end-users can control LG THERMA V via using smart internet devices.



Requirements



Cloud gateway



PI485 gateway

- Compatible THERMA V 1) Required accessory Network router R290 Monobloc R32 Monobloc S I Cloud gateway (PWFMDB200) Wireless or wired LAN R32 Split Hydro Unit R32 Split Combi Unit R32 Hydrosplit Hydro Unit LG BECON cloud service contract Supported device / software Supported language Authority (ID and PW) PC, Tablet, Mobile PC or English, Spanish, Italian, to use LG platform Mobile web browser, German, Polish, Greek (LG BECON cloud service) Mobile app. (Android / iOS)
- 1) In the case of R290 Monobloc, PI485 G/W is built-in, so there is no need to purchase it separately.
- 2) More languages will be supported sequentially. The schedule for service availability may vary by country.

Interface Screen

Dashboard



[Operation status summary]

[Operation status]

Site




[Site overview]

Control







[Cycle monitoring – schematic view]



[Cycle monitoring – table view]

History



ГО		1
I()n	ieration	history



[Error history]



[Outdoor unit cycle history]

SOLUTIONS

INDIVIDUAL SOLUTIONS

MONOBLOC

044 R290 Monobloc

048 - Control Unit (7/9/12/14/16 kW)

062 - Hydro Unit (7/9/12/14/16 kW)

076 - Combi Unit (7/9/12/14/16 kW)

094 R32 Monobloc S I (5/7/9/12/14/16 kW)

HYDROSPLIT

110 R32 Hydrosplit

114 - Hydro Unit (12/14/16 kW)

124 - Combi Unit (12/14/16 kW)

SPLIT

134 R32 Split


138 - Hydro Unit (4/6, 5/7/9 kW)

152 - Combi Unit (4/6, 5/7/9 kW)

HEAT PUMP WATER HEATER

174 R290 Round Type (100/150/200l)

182 R134a Square Type (200/270l)





What is R290 Monobloc

The new R290 Monobloc is a super-quiet, future-conscious heat pump that uses the R290 refrigerant which has lower GWP of only three.

From an aesthetic standpoint, refined gray design allows it to seamlessly harmonize with a diverse range of home and building exteriors, and from a technical standpoint, it is designed to be lownoise, so you don't have to worry about causing noise pollution to neighbors.

The LG THERMA V R290 Monobloc is available in three different combinations (Control Unit, Hydro Unit or Combi Unit) depending on the customers' needs.

Key Features

- Capacity range from 7 to 16 kW for new build and renovation
- Natural refrigerant R290 with low GWP (3)
- Refined gray design that adapts to various surroundings
- ErP Energy Labeling A+++ / A+++ for space heating (Average Climate 35°C / 55°C LWT)
- One of the quietest models on the market (49 dB(A) for 7 kW, 12 kW models)
- Maximum flow temperature up to 75°C
- Operation range down to -28°C
- Customized options through different three indoor units combinations
- Provides 75°C leaving water even at -15°C outdoor temperatures (7/9 kW only)
- 2024 IDEA Design Awards Bronze Winner













Product Range

Phase	Capacity		Indoor Unit		Outside and Disable
nase	(kW)	Control Unit	Hydro Unit	Combi Unit	Outdoor Unit
	7				HM071HF UB40
	9			25	HM091HF UB40
1Ø	12		HN1616HC NK0	HN1616HY NK0	HM121HF UB60
	14	N. S.			HM141HF UB60
	16	PHCS0			HM161HF UB60
	7	ENCXLEU			HM073HF UB40
	9				HM093HF UB40
3 Ø	12		HN1639HC NK0	HN1639HY NK0	HM123HF UB60
	14				HM143HF UB60
	16				HM163HF UB60

HIGHLIGHT OF R290 MONOBLOC

New Design

European Design



High Reliability







Anti-icing and Deicing technologies for R290 Monobloc.

- Defrost operation by dual EEVs & Cycle
- 2 Corrugated fin
- 3 Base pan heating (heater)
- 4 Elimination of side panel and rear grille
- **6** Frost-free for bottom pass of heat exchanger
- 6 Increased quantity for drain hole

Improved Operational Stability

Freezing Outside, but Toasty Inside

The R290 Monobloc can function in external temperatures as low as -28°C. Plus, customers can retain their existing radiators as the system can generate an outlet water of up to 75°C, offering a cost-saving advantage. Even at -15°C, it is possible to provide an outlet water temperature of 75°C. $(7/9\,\mathrm{kW}\,\mathrm{only})$



Extremely Quiet Operation


Heats Home in Hushed Tones



R290 Monobloc	7 kW	9 kW	12 kW	14 kW	16 kW
Sound power level 1) (heating / rated)	49	50	49	51	52
Sound power level 1) (heating / low noise mode)	47	48	48	50	51

¹⁾ Sound power level is measured in accordance with EN 12102-1 and ISO 9614.


Ensuring regulatory compliance across all EU markets



Customers can have peace of mind with no risk of complaints and no additional costs for acoustic enclosures.

High Efficiency Operation

Exceptional Efficiency




Achieving the highest ErP energy grade A+++ / A+++ for space heating

LG THERMA V R290 Monobloc (7 / 9 / 12 / 14 / 16 kW)



Reduced annual energy costs

Estimated Average Annual Energy Costs* in the EU (EU 27)



* This is simulation result based on conditions under average climate & Medium temperature (55°C) and it may differ from actual value since there are many assumptions used.


Convenience

Easy Installation

The two-way piping connection method not only grants greater installation flexibility but also offers distinct advantages when it comes to concealing underground piping for both aesthetic and frost protection purposes.

- * The downward piping kit should be purchased and installed separately.
- PHDW36B0 for 7, 9 kW models
- PHDW60B0 for 12, 14, 16 kW models





Backward Connection

Downward Connection

Freedom of Integration

Customized Combinations to Meet Diverse Needs

Since THERMA V R290 Monobloc has hydro components integrated into the outdoor unit, it can be combined with various indoor units to implement applications tailored to customer needs.

Outdoor Unit		Indoor Unit Type
200		Control Unit Stand-alone concept Easy integration with 3 rd party equipment
		Hydro Unit Back-up heater & expansion tank integrated inside
	8	Combi Unit DHW tank, back-up heater, expansion tank integrated inside 200 & stainless steel tank

046



THERMA V. R290 Monobloc **CONTROL UNIT**




Easy to Install, **Minimal Space** Required

Since the water pipe is not connected to the indoor unit and requires less installation space, it offers an easy installation process similar to the full Monobloc concept.

This setup is especially recommended for cases where the customer does not wish to install a backup heater, prefers to add it as a third-party accessory, or opts to install a larger expansion tank.

Key Features

- Stand-alone concept
- Light weight and compact size fits in small spaces
- Simple installation by minimizing piping and wiring work
- Easy integration with 3rd party equipment because of less cabling
- No pipe connections for the indoor unit allow for a neat installation



Application







Certifications











Energy Label







THERMA V R290 MONOBLOC CONTROL UNIT (7/9 kW)

Outdoor unit

HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40

Indoor unit

PHCS0 ENCXLEU























Key Components

Outdoor Unit



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 Biomimetic fan
- 3 New R1 compressor
- 4 Hydronic components assembly
- Deaerator
- 6 Water pump
- 7 Flow sensor
- 8 Plate heat exchanger
- 9 Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Indoor Unit (Control Unit)



Components

1 Standard III remote controller 1) (air temp. sensor integrated)

1) Temperature control class (ERP class): V

Product Specification

Efficiency Data		Unit	7 kW (1 Ø) 7 kW (3 Ø)	9 kW (1 Ø) 9 kW (3 Ø)		
Seasonal space heating eff. class (35°C / 55°	°C)	-	A+++ / A+++	A+++ / A+++		
Seasonal space heating efficiency (η_s) (35°C	/ 55°C)	%	207 / 151	205 / 151		
SCOP (35°C / 55°C)		-	5.24 / 3.86	5.20 / 3.86		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	50 / 48		
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	28 / 26		
Nominal Capacity and COP/EER						
Air +7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 5.00	9.00 / 4.70		
Air +2°C / water +35°C	+2°C / water +35°C Heating capacity / COP		7.00 / 3.80	8.00 / 3.70		
Air -7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 2.80	9.00 / 2.70		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	4.50 / 3.35	5.50 / 3.30		
Air -7°C / water +55°C	Heating capacity / COP	kW / -	7.00 / 2.40	8.00 / 2.20		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.00 / 4.40	5.50 / 4.20		
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.00 / 2.80	5.50 / 2.60		
Outdoor Units		Unit	HM071HF UB40 HM073HF UB40	HM091HF UB40 HM093HF UB40		
Operation range	Heating & DHW (Min. ~ Max.)	°C	-28	~ 35		
outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~	48		
	Туре	-	R2	90		
efrigerant	GWP	-	3			
	Precharged amount	g	90	00		
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" according to ISC	7-1 (tapered pipe threads)		
Dimension	HxWxD	mm	1,019 x 1,3	320 x 520		
Weight	Net	kg	130	0.0		
F. A. J.	Color of chassis / RAL code	-	Dawn gray ,	/ RAL 7037		
Exterior	Color of front grille / RAL code	-	Dark dawn gra	ay / RAL 7012		
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50 /	⁷ 380 ~ 415, 3, 50		
Power supply	Standby power consumption	W	1	0		
	Recommended circuit breaker	А	1 Ø: 20 /	′ 3 Ø: 16		
Indoor Units		Unit	PHCS0 E	NCXLEU		
	Heating (Min. ~ Max.)	°C	15 -	· 75		
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~	27		
DHW (Min. ~ Max.)		°C	15 ~	· 80		
Dimension	HxWxD	mm	490 x 420 x 141			
Weight	Net	kg	6.8			
Exterior	Color / RAL code	-	Essence white / RAL 9003			
Deview events	Voltage, phase, frequency	V, Ø, Hz	220 ~ 24	40, 1, 50		
Power supply	Recommended circuit breaker	А	10			

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- $6. \ All \ installation \ sites \ must \ be \ equipped \ with \ an \ earth \ leakage \ circuit \ breaker \ (ELCB).$
- 7. DHW 65 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

053

THERMA V R290 MONOBLOC CONTROL UNIT (7/9 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM071HF UB40 + PHCS0 ENCXLEU / HM073HF UB40 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]		Capacity (kW)										
-25	5.90	5.85	5.85	5.85	5.80	5.80	5.80	-	-	-		
-20	6.50	6.50	6.50	6.50	6.20	6.10	6.10	6.00	-	-		
-15	7.00	7.00	7.00	7.00	6.80	6.70	6.30	6.30	6.20	6.20		
-7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.60	6.40		
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.50		
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80	6.50		
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70		
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80		
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
35	-	-	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00		

HM091HF UB40 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]		Capacity (kW)										
-25	7.40	7.20	7.10	6.90	6.80	6.70	6.60	-	-	-		
-20	8.20	7.90	7.70	7.50	7.30	7.10	6.90	6.60	-	-		
-15	9.00	9.00	8.20	7.90	7.70	7.60	7.30	7.00	6.80	6.50		
-7	9.00	9.00	9.00	8.50	8.40	8.00	7.90	7.70	7.40	6.60		
-4	9.00	9.00	9.00	9.00	9.00	8.40	8.20	7.90	7.70	6.70		
-2	9.00	9.00	9.00	9.00	9.00	9.00	8.40	8.10	7.60	6.80		
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	7.80	6.90		
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.10		
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.20		
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.30	7.30		
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.40		
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.50		
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00		

HM093HF UB40 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]		Capacity (kW)										
-25	7.90	7.77	7.92	8.08	8.20	8.40	8.40	-	-	-		
-20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-	-		
-15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
-7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	8.00	7.00		
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00		

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM: Liters Per Minute (\$\ell/min), TC: Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- $\, \bullet \,$ Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \ \, \text{Above table values may not be matched according to installation condition.} \ \, \text{Except for rated value, the performance is not guaranteed.}$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM071HF UB40 + PHCS0 ENCXLEU / HM073HF UB40 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	5.30	6.00	6.70	7.00	7.00	7.00	7.00
30	5.10	5.40	5.80	6.20	7.00	7.00	7.00
35	5.00	5.40	5.80	6.20	6.80	6.80	7.00
40	4.60	4.90	5.30	5.60	6.20	6.70	7.00
45	4.20	4.70	5.30	5.60	6.20	6.50	7.00

HM091HF UB40 + PHCS0 ENCXLEU / HM093HF UB40 + PHCS0 ENCXLEU

LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
			Capacity (kW)			
5.80	6.70	7.50	9.00	9.00	9.00	9.00
5.60	6.40	7.20	7.70	9.00	9.00	9.00
5.50	6.30	7.20	7.80	9.00	9.00	9.00
5.00	5.70	6.40	6.80	7.40	7.70	9.00
4.40	5.10	5.70	6.10	6.80	7.20	7.60
	5.80 5.60 5.50 5.00	5.80 6.70 5.60 6.40 5.50 6.30 5.00 5.70	5.80 6.70 7.50 5.60 6.40 7.20 5.50 6.30 7.20 5.00 5.70 6.40	Capacity (kW) 5.80 6.70 7.50 9.00 5.60 6.40 7.20 7.70 5.50 6.30 7.20 7.80 5.00 5.70 6.40 6.80	Capacity (kW) 5.80 6.70 7.50 9.00 9.00 5.60 6.40 7.20 7.70 9.00 5.50 6.30 7.20 7.80 9.00 5.00 5.70 6.40 6.80 7.40	Capacity (kW) 5.80 6.70 7.50 9.00 9.00 9.00 5.60 6.40 7.20 7.70 9.00 9.00 5.50 6.30 7.20 7.80 9.00 9.00 5.00 5.70 6.40 6.80 7.40 7.70

Note

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
 Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

 4. The shaded areas are not guaranteed continuous operation.
- 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer




Technical Specification		Unit	Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1


- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.

THERMA V R290 MONOBLOC CONTROL UNIT (7/9 kW)

Drawings [Unit: mm] [Unit: mm]


HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40










3D view





Front view





Before piping, remove the cover brackets.

Drain holes for drain cap (7EA)


If you need more drains, remove them.

Bottom view


054


No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Air Discharge Grille	-
4	Access to Electrical Terminals	Power, Communication


PHCS0 ENCXLEU




3D view









No.	Part Name	Description
1	Remote Controller Assembly	Built-in Remote Controller
2	Panel Assembly.Front	SGMCD1 M08 ESSENCE WHITE PCM
3	Panel Assembly.Indoor	PCB and Terminal Blocks
4	Cover	MOLD ABS

THERMA V R290 MONOBLOC **CONTROL UNIT (12/14/16 kW)**

Outdoor unit

HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60

Indoor unit

PHCS0 ENCXLEU


























Key Components

Outdoor Unit



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 New biomimetic fan
- 3 Dual sound shield
- 4 R290 scroll compressor
- **5** Hydronic components assembly
- 6 Water pump
- Deaerator
- 8 Plate heat exchanger (ref / water)
- Flow sensor
- 10 Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Indoor Unit (Control Unit)



Components

1 Standard III remote controller 1) (air temp. sensor integrated)

1) Temperature control class (ERP class): V

Product Specification

Efficiency Data		Unit	12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)		
Seasonal space heating eff. class (35°C / 55	°C)	-	A+++ / A+++	A+++ / A+++	A+++ / A+++		
Seasonal space heating efficiency (η _s) (35°C	/ 55°C)	%	215 / 156	212 / 155	201 / 154		
SCOP (35°C / 55°C)		-	5.45 / 3.97	5.38 / 3.96	5.11 / 3.92		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	51 / 50	52 / 51		
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	29 / 28	30 / 29		
Nominal Capacity and COP/EER							
Air +7°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 4.70	14.00 / 4.50	16.00 / 4.30		
Air +2°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 3.72	14.00 / 3.61	14.50 / 3.49		
Air -7°C / water +35°C	Heating capacity / COP	kW / -	11.80 / 3.27	13.00 / 3.21	13.80 / 3.17		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	10.00 / 3.10	11.00 / 3.25	12.00 / 3.30		
Air -7°C / water +55°C	Heating capacity / COP	kW / -	9.30 / 2.32	10.30 / 2.28	10.90 / 2.26		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	11.50 / 3.78	12.00 / 3.70	12.50 / 3.70		
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	10.50 / 3.12	12.00 / 2.99	12.50 / 2.95		
Outdoor Units		Unit	HM121HF UB60 HM123HF UB60	HM141HF UB60 HM143HF UB60	HM161HF UB60 HM163HF UB60		
Operation range	Heating & DHW (Min. ~ Max.)	°C	-28 ~ 35				
outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48				
	Туре	-	R290				
defrigerant	GWP	-	3				
	Precharged amount	g	1,200				
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" acc	cording to ISO 7-1 (tapered	f pipe threads)		
Dimension	HxWxD	mm		1,019 x 1,560 x 520			
Weight	Net	kg		181.0			
Exterior	Color of chassis / RAL code	-		Dawn gray / RAL 7037			
Exterior	Color of front grille / RAL code	-	I	Dark dawn gray / RAL 701	2		
	Voltage, phase, frequency	V, Ø, Hz	220	~ 240, 1, 50 / 380 ~ 415, 3	3, 50		
Power supply	Standby power consumption	W		10			
	Recommended circuit breaker	А		1 Ø: 25 / 3 Ø: 16			
Indoor Units		Unit		PHCS0 ENCXLEU			
	Heating (Min. ~ Max.)	°C		15 ~ 75			
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 27			
	DHW (Min. ~ Max.)	°C	15 ~ 80				
Dimension	HxWxD	mm	490 x 420 x 141				
Weight	Net	kg		6.8			
Exterior	Color / RAL code	-		Essence white / RAL 9003	1		
Power supply	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50				
Power supply	Recommended circuit breaker	А	10				

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

059

THERMA V R290 MONOBLOC CONTROL UNIT (12/14/16 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM121HF UB60 + PHCS0 ENCXLEU / HM123HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	8.36	8.07	7.79	7.54	7.32	6.37	-	-	-	-
-20	9.60	9.39	9.20	9.09	9.08	8.27	6.77	-	-	-
-15	10.84	10.69	10.55	10.55	10.84	10.76	8.71	7.17	-	-
-7	12.00	12.00	12.00	12.00	12.00	12.00	11.27	10.00	8.99	-
-4	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.88	9.65	8.91
-2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.45	10.29	9.32
2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	8.08	6.84	6.36
7	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.28	8.34	7.67
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.20	9.90	8.95
15	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.09
18	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.69
20	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
35	-	-	12,00	12,00	12.00	12.00	12,00	12,00	12,00	12.00

HM141HF UB60 + PHCS0 ENCXLEU / HM143HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]		Capacity (kW)										
-25	8.88	8.57	8.28	8.01	7.78	6.37	-	-	-	-		
-20	10.20	9.97	9.78	9.66	9.48	8.27	6.77	-	-	-		
-15	12.06	11.99	11.79	11.59	11,29	10.76	8.71	7.17	-	-		
-7	14.00	14.00	13.82	13.63	13.45	12.58	11,27	10.00	8.99	-		
-4	14.00	14.00	13.90	13.83	13.83	13.23	12.06	10.88	9.65	8.91		
-2	14.00	14.00	13.96	13.95	14.00	13.71	12,59	11.45	10.29	9.32		
2	14.00	14.00	14.00	14.00	14.00	14.00	13.16	8.08	6.84	6.36		
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	10.28	8.34	7.67		
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	11.20	9.90	8.95		
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.72	12.02	11.09		
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.82	12.89	11.69		
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.47	12.09		
35	-	-	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.80		

HM161HF UB60 + PHCS0 ENCXLEU / HM163HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]	Capacity (kW)											
-25	9.41	9.08	8.76	8.48	7.81	6.37	-	-	-	-		
-20	10.80	10.56	10.35	10.23	9.48	8.27	6.77	-	-	-		
-15	13.36	13.28	12.74	12.15	11.29	10.76	8.71	7.17	-	-		
-7	16.00	16.00	15.17	14.35	13.52	12,58	11.27	10.00	8.99	-		
-4	16.00	16.00	15.43	14.85	14.29	13.23	12.06	10.88	9.65	8.91		
-2	16.00	16.00	15.69	15.34	14.81	13.71	12,59	11.45	10.29	9.32		
2	16.00	16.00	16.00	16.00	16.00	14.84	13.16	8.08	6.84	6.36		
7	16.00	16.00	16.00	16.00	16.00	16.00	14.25	10.28	8.34	7.67		
10	16.00	16.00	16.00	16.00	16.00	16.00	14.92	11.20	9.90	8.95		
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	12.72	12.02	11.09		
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	13.82	12.89	11.69		
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	14.56	13.47	12.09		
35	-	-	16.00	16.00	16.00	16.00	16.00	16.00	14.40	12.80		

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ /min), TC : Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- $\, \bullet \,$ Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \textbf{Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed. } \\$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM121HF UB60 + PHCS0 ENCXLEU / HM123HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	11.50	11.50	11.50	11.50	11.50	11.50	11.50
30	10.97	11.50	11.50	11.50	11.50	11.50	11.50
35	10.50	11.28	11.50	11.50	11.50	11.50	11.50
40	9.35	10.08	10.80	11.27	11.50	11.50	11.50
45	8.19	8.90	9.61	10.07	10.77	11.23	11.50

HM141HF UB60 + PHCS0 ENCXLEU / HM143HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]							
20	12.00	12.00	12,00	12.00	12.00	12.00	12.00
30	12.00	12.00	12.00	12.00	12.00	12.00	12.00
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00
40	10.68	11.52	12.00	12.00	12.00	12.00	12.00
45	9.36	10.17	10.98	11.51	12.00	12.00	12.00

HM161HF UB60 + PHCS0 ENCXLEU / HM163HF UB60 + PHCS0 ENCXLEU

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]							
20	12.50	12.50	12,50	12.50	12,50	12.50	12,50
30	12.50	12.50	12,50	12.50	12.50	12.50	12,50
35	12.50	12.50	12,50	12.50	12,50	12.50	12.50
40	12.02	12.50	12.50	12.50	12.50	12,50	12.50
45	10.03	10.78	11.54	12.05	12.50	12.50	12.50

Note

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- $2.\, {\hbox{Direct interpolation is permissible.}}\, \hbox{Do not extrapolate},$
- 3. Measuring procedure follows EN-14511.
- $\bullet\,\mathsf{Rated}\,\mathsf{values}\,\mathsf{are}\,\mathsf{based}\,\mathsf{on}\,\mathsf{standard}\,\mathsf{conditions}\,\mathsf{and}\,\mathsf{it}\,\mathsf{can}\,\mathsf{be}\,\mathsf{found}\,\mathsf{on}\,\mathsf{specifications}.$
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

 4. The shaded areas are not guaranteed continuous operation.
- ____

Supplied Parts

Strainer




Technical Specification	Technical Specification		Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1


- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.


THERMA V R290 MONOBLOC CONTROL UNIT (12/14/16 kW)

Drawings [Unit: mm] [Unit: mm]

HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60










Bottom view


No.	Part Name	Description			
1	Leaving Water Pipe	Male PT 1 inch			
2	Entering Water Pipe	Male PT 1 inch			
3	Air Discharge Grille	-			
4	Access to Electrical Terminals	Power, Communication			











Front view

No.	Part Name	Description
1	Remote Controller Assembly	Built-in Remote Controller
2	Panel Assembly.Front	SGMCD1 M08 ESSENCE WHITE PCM
3	Panel Assembly.Indoor	PCB and Terminal Blocks
4	Cover	MOLD ABS



THERMA V_m R290% Monobloc **HYDRO UNIT**




Optimized Solution, Time and Space Saving Design

Hydronic components such as backup heater and expansion tank are included in the indoor unit, minimizing installation space and reducing installation time.

Key Features

- Integrated hydronic components Backup heater, Expansion tank
- Space-saving solution with compact and light indoor unit
- Simple installation due to no refrigerant piping work



Application







Certifications









Energy Label







THERMA V R290 MONOBLOC HYDRO UNIT (7/9 kW)

Outdoor unit

HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40

Indoor unit

HN1616HC NK0 HN1639HC NK0

























Key Components

Outdoor Unit



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 Biomimetic fan
- 3 New R1 compressor
- 4 Hydronic components assembly
- 5 Deaerator
- 6 Water pump
- 7 Flow sensor8 Plate heat exchanger
- Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Indoor Unit (Hydro Unit)



Components

- 1 Backup heater (1 Ø: 6 kW / 3 Ø: 9 kW)
- 2 Expansion tank (8 l)
- 3 Air vent valve
- 4 Standard III remote controller 1)
 (air temp. sensor integrated)

1) Temperature control class (ERP class): V

Connections

- A Heating circuit outlet pipe (male PT 1")
- B Heating circuit inlet pipe (male PT 1")
- Outlet pipe to outdoor unit (male PT 1")
- D Inlet pipe from outdoor unit (male PT 1")

Product Specification

Efficiency Data		Unit	7 kW (1 Ø) 9 kW (1 Ø) 7 kW (3 Ø) 9 kW (3 Ø)			
Seasonal space heating eff. class (35°C / 55	°C)	-	A+++ / A+++	A+++ / A+++		
Seasonal space heating efficiency (η_s) (35°C	/ 55°C)	%	207 / 151	205 / 151		
SCOP (35°C / 55°C)		-	5,24 / 3,86	5.20 / 3.86		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	50 / 48		
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	28 / 26		
Sound power level (indoor unit)	Rated	dB(A)	39			
Sound pressure level at 1m (indoor unit)	Rated	dB(A)	31			
Nominal Capacity and COP/EER						
Air +7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 5.00 9.00 / 4.70			
Air +2°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 3.80	8.00 / 3.70		
Air -7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 2.80	9.00 / 2.70		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	4.50 / 3.35	5.50 / 3.30		
Air -7°C / water +55°C	Heating capacity / COP	kW / -	7.00 / 2.40	8.00 / 2.20		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.00 / 4.40	5.50 / 4.20		
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.00 / 2.80	5.50 / 2.60		
	J. J		HM071HF UB40	HM091HF UB40		
Outdoor Units		Unit	HM073HF UB40	HM093HF UB40		
Operation range	Heating & DHW (Min. ~ Max.)	°C	-28 ~ 3	35		
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48	В		
	Туре	-	R290)		
Refrigerant	GWP	-	3			
	Precharged amount	g	900			
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" according to ISO 7	-1 (tapered pipe threads)		
Dimension	HxWxD	mm	1,019 x 1,32	0 x 520		
Weight	Net	kg	130.0			
Exterior	Color of chassis / RAL code	-	Dawn gray / RAL 7037			
Exterior	Color of front grille / RAL code	-	Dark dawn gray	/ RAL 7012		
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50 / 3	80 ~ 415, 3, 50		
Power supply	Standby power consumption	W	10			
	Recommended circuit breaker	А	1 Ø: 20 / 3	Ø: 16		
Indoor Units		Unit	HN1616HC NK0 / H	IN1639HC NK0		
	Heating (Min. ~ Max.)	°C	15 ~ 7	5		
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 2	7		
(coving water temperature)	DHW (Min. ~ Max.)	°C	15 ~ 8	0		
Expansion vessel (heating circuit)	Volume	l	8			
	Capacity combination	kW	3.0 + 3.0 / 3.0	+ 3.0 + 3.0		
Dealers beater	Heating steps	Steps	2			
Backup heater	Power supply	V, Ø, Hz	220 - 240, 1, 50 / 3	80 - 415, 3, 50		
	Rated running current	А	26 / 1	3		
	Heating circuit outlet pipe	inch				
Distance of the second	Heating circuit inlet pipe	inch	Mala DT d"	4/		
Piping connections (water)	Outlet pipe to outdoor unit	inch	Male PT T" according to ISO 7	1" according to ISO 7-1 (tapered pipe threads)		
	Inlet pipe from outdoor unit	inch				
Dimension	HxWxD	mm	850 x 490	x 315		
Weight	Net	kg	1 Ø: 30.0 / 3	Ø: 31.0		
Exterior	Color / RAL code	-	Noble white /	RAL 9016		
	Voltage, phase, frequency	V, Ø, Hz	220 - 240	, 1, 50		
Power supply	Recommended circuit breaker	А	10			

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes, Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

067

THERMA V R290 MONOBLOC HYDRO UNIT (7/9kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM071HF UB40 + HN1616HC NK0 / HM073HF UB40 + HN1639HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C	
[°C DB]	Capacity (kW)										
-25	5.90	5.85	5.85	5.85	5.80	5.80	5.80	-	-	-	
-20	6.50	6.50	6.50	6.50	6.20	6.10	6.10	6.00	-	-	
-15	7.00	7.00	7.00	7.00	6.80	6.70	6.30	6.30	6.20	6.20	
-7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.60	6.40	
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.50	
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80	6.50	
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80	
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	
35	-	-	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	

HM091HF UB40 + HN1616HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	7.40	7.20	7.10	6.90	6.80	6.70	6.60	-	-	-
-20	8.20	7.90	7.70	7.50	7.30	7.10	6.90	6.60	-	-
-15	9.00	9.00	8.20	7.90	7.70	7.60	7.30	7.00	6.80	6.50
-7	9.00	9.00	9.00	8.50	8.40	8.00	7.90	7.70	7.40	6.60
-4	9.00	9.00	9.00	9.00	9.00	8.40	8.20	7.90	7.70	6.70
-2	9.00	9.00	9.00	9.00	9.00	9.00	8.40	8.10	7.60	6.80
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	7.80	6.90
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.10
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.20
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.30	7.30
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.40
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.50
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00

HM093HF UB40 + HN1639HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]	Capacity (kW)									
-25	7.90	7.77	7.92	8.08	8.20	8.40	8.40	-	-	-
-20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-	-
-15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	8.00	7.00
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- $2.\, {\sf Direct\ interpolation\ is\ permissible}.\, {\sf Do\ not\ extrapolate}.$
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM071HF UB40 + HN1616HC NK0 / HM073HF UB40 + HN1639HC NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	5.30	6.00	6.70	7.00	7.00	7.00	7.00
30	5.10	5.40	5.80	6.20	7.00	7.00	7.00
35	5.00	5.40	5.80	6.20	6.80	6.80	7.00
40	4.60	4.90	5.30	5.60	6.20	6.70	7.00
45	4.20	4.70	5.30	5.60	6.20	6.50	7.00

HM091HF UB40 + HN1616HC NK0 / HM093HF UB40 + HN1639HC NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	5.80	6.70	7.50	9.00	9.00	9.00	9.00
30	5.60	6.40	7.20	7.70	9.00	9.00	9.00
35	5.50	6.30	7.20	7.80	9.00	9.00	9.00
40	5.00	5.70	6.40	6.80	7.40	7.70	9.00
45	4.40	5.10	5.70	6.10	6.80	7.20	7.60

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \ Above \ table \ values \ may \ not \ be \ matched \ according \ to \ installation \ condition. \ Except \ for \ rated \ value, \ the \ performance \ is \ not \ guaranteed.$
- In accordance with the test standard (or nations), the rating will vary slightly. 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer



Technical Specification		Unit	Details
Material	Body	-	Brass
	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1


- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.


[Unit: mm]

THERMA V R290 MONOBLOC HYDRO UNIT (7/9kW)

Drawings [Unit: mm]

HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40










Top view


3D view **Back view**







Front view



If you need more drains, remove them.

Bottom view


No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Air Discharge Grille	-
4	Access to Electrical Terminals	Power, Communication

External HN1616HC NK0 / HN1639HC NK0 3D view Front view Side view **Bottom view**

No.	Part Name	Description			
1	Control Panel	Built-in Remote Controller			

Internal

HN1616HC NK0 / HN1639HC NK0



No.	Part Name	Description
1	Leaving Water Pipe (Heat load)	Male PT 1 inch
2	Entering Water Pipe (Heat load)	Male PT 1 inch
3	Leaving Water Pipe (ODU)	Male PT 1 inch
4	Entering Water Pipe (ODU)	Male PT 1 inch
5	Control Box	PCB and Terminal Blocks
6	Expansion Tank	Absorbing Volume Change of Heated Water
7	Air Vent	Air Purging when Charging Water
8	Backup Heater	Capacity : 1 Ø 6 kW, 3 Ø 9 kW
9	Thermal Switch	Cut-off Power Input to Backup Heater at 90°C (Manual return at 55°C)

THERMA V R290 MONOBLOC HYDRO UNIT (12/14/16 kW)

Outdoor unit

HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60

Indoor unit

HN1616HC NK0 HN1639HC NK0
























Key Components

Outdoor Unit



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 New biomimetic fan
- 3 Dual sound shield
- 4 R290 scroll compressor
- 5 Hydronic components assembly
- Water pump
- 7 Deaerator
- 8 Plate heat exchanger (ref / water)
- 9 Flow sensor
- Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Indoor Unit (Hydro Unit)



Components

- 1 Backup heater (1 Ø: 6 kW / 3 Ø: 9 kW)
- 2 Expansion tank (8 l)
- 3 Air vent valve
- 4 Standard III remote controller 1)
 (air temp. sensor integrated)

1) Temperature control class (ERP class) : V

Connections

- A Heating circuit outlet pipe (male PT 1")
- B Heating circuit inlet pipe (male PT 1")
- Outlet pipe to outdoor unit (male PT 1")
- D Inlet pipe from outdoor unit (male PT 1")

Product Specification

Efficiency Data			12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)		
Seasonal space heating eff. class (35°C / 55	°C)	-	A+++ / A+++	A+++ / A+++	A+++ / A+++		
Seasonal space heating efficiency (η_s) (35°C / 55°C)			215 / 156	212 / 155	201 / 154		
SCOP (35°C / 55°C)		-	5.45 / 3.97	5.38 / 3.96	5.11 / 3.92		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	51 / 50	52 / 51		
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	29 / 28	30 / 29		
Sound power level (indoor unit)	Rated	dB(A)		39			
Sound pressure level at 1m (indoor unit)	Rated	dB(A)		31			
Nominal Capacity and COP/EER							
Air +7°C / water +35°C	Heating capacity / COP	kW/-	12.00 / 4.70	14.00 / 4.50	16.00 / 4.30		
Air +2°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 3.72	14.00 / 3.61	14.50 / 3.49		
Air -7°C / water +35°C	Heating capacity / COP	kW/-	11.80 / 3.27	13.00 / 3.21	13.80 / 3.17		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	10.00 / 3.10	11.00 / 3.25	12.00 / 3.30		
Air -7°C / water +55°C	Heating capacity / COP	kW / -	9.30 / 2.32	10.30 / 2.28	10.90 / 2.26		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	11.50 / 3.78	12.00 / 3.70	12.50 / 3.70		
Air +35°C / water +7°C	Cooling capacity / EER	kW/-	10.50 / 3.12	12.00 / 2.99	12.50 / 2.95		
Outdoor Units		Unit	HM121HF UB60 HM123HF UB60	HM141HF UB60 HM143HF UB60	HM161HF UB60 HM163HF UB60		
Operation range	Heating & DHW (Min. ~ Max.)	°C	-28 ~ 35				
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48				
	Туре	-	R290				
Refrigerant	GWP	-	3				
	Precharged amount	g	1,200				
Piping connections (water) Inlet / outlet diameter		inch	Male PT 1" acc	ording to ISO 7-1 (tapered	pipe threads)		
Dimension	HxWxD	mm	1,019 x 1,560 x 520				
Weight	Net	kg	181.0				
Exterior	Color of chassis / RAL code	-	Dawn gray / RAL 7037				
Exterior	Color of front grille / RAL code	-	Dark dawn gray / RAL 7012				
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50 / 380 ~ 415, 3, 50				
Power supply	Standby power consumption	W	10				
	Recommended circuit breaker	А	1 Ø: 25 / 3 Ø: 16				
Indoor Units		Unit	HN1	616HC NK0 / HN1639HC	NK0		
	Heating (Min. ~ Max.)	°C		15 ~ 75			
Operation range	Cooling (Min. ~ Max.)	°C		5 ~ 27			
(leaving water temperature)	DHW (Min. ~ Max.)	°C		15 ~ 80			
Expansion vessel (heating circuit)	Volume	l	8				
	Capacity combination	kW		3.0 + 3.0 / 3.0 + 3.0 + 3.0			
	Heating steps	Steps		2			
Backup heater	Power supply	V, Ø, Hz	220	- 240, 1, 50 / 380 - 415, 3	3, 50		
	Rated running current	А		26 / 13			
	Heating circuit outlet pipe	inch					
Distance and the second	Heating circuit inlet pipe	inch	14 1 57 4"		Laine About 1.		
Piping connections (water)	Outlet pipe to outdoor unit	inch	Male PI 1" acc	cording to ISO 7-1 (tapered	pipe threads)		
	Inlet pipe from outdoor unit	inch					
Dimension H x W x D		mm	850 x 490 x 315				
Weight	Net	kg		1 Ø: 30.0 / 3 Ø: 31.0			
Exterior	Color / RAL code	-	Noble white / RAL 9016				
Davis and the	Voltage, phase, frequency	V, Ø, Hz	220 - 240, 1, 50				
Power supply	Recommended circuit breaker	А	10				

Note

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- $2. \ Wiring \ cable \ size \ must \ comply \ with \ the \ applicable \ local \ and \ national \ codes. \ Especially \ the \ power \ cable \ and \ circuit \ breaker \ should \ be \ selected \ in \ accordance \ with \ that.$
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80°C Operating is available only when the booster heater is operating.

073

THERMA V R290 MONOBLOC HYDRO UNIT (12/14/16 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM121HF UB60 + HN1616HC NK0 / HM123HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C	
[°C DB]		Capacity (kW)									
-25	8.36	8.07	7.79	7.54	7.32	6.37	-	-	-	-	
-20	9.60	9.39	9.20	9.09	9.08	8.27	6.77	-	-	-	
-15	10.84	10.69	10.55	10.55	10.84	10.76	8.71	7.17	-	-	
-7	12.00	12.00	12.00	12.00	12.00	12.00	11.27	10.00	8.99	-	
-4	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.88	9.65	8.91	
-2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.45	10.29	9.32	
2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	8.08	6.84	6.36	
7	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.28	8.34	7.67	
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.20	9.90	8.95	
15	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.09	
18	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.69	
20	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	
35	-	-	12,00	12,00	12.00	12.00	12,00	12,00	12,00	12.00	

HM141HF UB60 + HN1616HC NK0 / HM143HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	8.88	8.57	8.28	8.01	7.78	6.37	-	-	-	-
-20	10.20	9.97	9.78	9.66	9.48	8.27	6.77	-	-	-
-15	12.06	11.99	11.79	11.59	11.29	10.76	8.71	7.17	-	-
-7	14.00	14.00	13.82	13.63	13.45	12.58	11.27	10.00	8.99	-
-4	14.00	14.00	13.90	13.83	13.83	13.23	12.06	10.88	9.65	8.91
-2	14.00	14.00	13.96	13.95	14.00	13.71	12.59	11.45	10.29	9.32
2	14.00	14.00	14.00	14.00	14.00	14.00	13.16	8.08	6.84	6.36
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	10.28	8.34	7.67
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	11.20	9.90	8.95
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.72	12.02	11.09
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.82	12.89	11.69
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.47	12.09
35	-	-	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.80

HM161HF UB60 + HN1616HC NK0 / HM163HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C			
[°C DB]		Capacity (kW)											
-25	9.41	9.08	8.76	8.48	7.81	6.37	-	-	-	-			
-20	10.80	10.56	10.35	10.23	9.48	8.27	6.77	-	-	-			
-15	13.36	13.28	12.74	12.15	11,29	10.76	8.71	7.17	-	-			
-7	16.00	16.00	15.17	14.35	13.52	12,58	11.27	10.00	8.99	-			
-4	16.00	16.00	15.43	14.85	14.29	13.23	12.06	10.88	9.65	8.91			
-2	16.00	16.00	15.69	15.34	14.81	13.71	12,59	11.45	10.29	9.32			
2	16.00	16.00	16.00	16.00	16.00	14.84	13.16	8.08	6.84	6.36			
7	16.00	16.00	16.00	16.00	16.00	16.00	14.25	10.28	8.34	7.67			
10	16.00	16.00	16.00	16.00	16.00	16.00	14.92	11.20	9.90	8.95			
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	12.72	12.02	11.09			
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	13.82	12.89	11.69			
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	14.56	13.47	12.09			
35	-	-	16.00	16.00	16.00	16.00	16.00	16.00	14.40	12.80			

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ /min), TC : Total Capacity (kW)
- $2.\, {\hbox{Direct interpolation is permissible.}}\, \hbox{Do not extrapolate}.$
- 3. Measuring procedure follows EN-14511.

 Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM121HF UB60 + HN1616HC NK0 / HM123HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	11.50	11.50	11.50	11.50	11.50	11.50	11.50
30	10.97	11.50	11.50	11.50	11.50	11.50	11.50
35	10.50	11,28	11.50	11.50	11.50	11.50	11.50
40	9.35	10.08	10.80	11.27	11.50	11.50	11.50
45	8.19	8.90	9.61	10.07	10.77	11.23	11.50

HM141HF UB60 + HN1616HC NK0 / HM143HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C				
[°C DB]	Capacity (kW)										
20	12.00	12.00	12.00	12.00	12.00	12.00	12,00				
30	12.00	12.00	12.00	12.00	12.00	12.00	12,00				
35	12.00	12.00	12.00	12.00	12.00	12.00	12,00				
40	10.68	11,52	12.00	12.00	12.00	12.00	12,00				
45	9.36	10.17	10.98	11,51	12,00	12,00	12.00				

HM161HF UB60 + HN1616HC NK0 / HM163HF UB60 + HN1639HC NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C	
[°C DB]				Capacity (kW)				
20	12.50	12.50	12.50	12,50	12.50	12.50	12.50	
30	12.50	12.50	12,50	12,50	12.50	12.50	12,50	
35	12.50	12.50	12.50	12,50	12.50	12.50	12.50	
40	12.02	12.50	12.50	12.50	12.50	12.50	12,50	
45	10.03	10.78	11.54	12,05	12.50	12,50	12.50	

Note

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- $2.\, {\hbox{Direct interpolation is permissible.}}\, \hbox{Do not extrapolate},$
- 3. Measuring procedure follows EN-14511.
- \bullet Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer



Technical Specification	Technical Specification		Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1

- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.


Built-in Remote Controller


[Unit: mm]


THERMA V R290 MONOBLOC HYDRO UNIT (12/14/16 kW)


Drawings [Unit: mm]

HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60










Bottom view

Front view


No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Air Discharge Grille	-
4	Access to Electrical Terminals	Power, Communication



Internal

HN1616HC NK0 / HN1639HC NK0

Control Panel



No.	Part Name	Description				
1	Leaving Water Pipe (Heat load)	Male PT 1 inch				
2	Entering Water Pipe (Heat load)	Male PT 1 inch				
3	Leaving Water Pipe (ODU)	Male PT 1 inch				
4	Entering Water Pipe (ODU)	Male PT 1 inch				
5	Control Box	PCB and Terminal Blocks				
6	Expansion Tank	Absorbing Volume Change of Heated Water				
7	Air Vent	Air Purging when Charging Water				
8	Backup Heater	Capacity : 1 Ø 6 kW, 3 Ø 9 kW				
9	Thermal Switch	Switch Cut-off Power Input to Backup Heater at 90°C (Manual return at 55°C)				



THERMA V_m R290% Monobloc **COMBIUNIT**



All-in-One

integration.


Designed to streamline your home's heating, cooling, and hot water systems, this all-in-

one solution provides seamless

It efficiently saves space in your

Key Features

- All-in-one Combi Unit with integrated hot water cylinder
- Saves space in the technical room with a small footprint
- Reduced installation time with pre-installed components
- Harmonized with other household appliances for a cohesive exterior









Certifications











Energy Label











THERMA V R290 MONOBLOC COMBI UNIT (7/9kW)

Outdoor unit

HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40

Indoor unit

HN1616HY NKO HN1639HY NKO


























Key Components

Outdoor Unit



Indoor Unit (Combi Unit)



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 Biomimetic fan
- 3 New R1 compressor
- 4 Hydronic components assembly
- 6 Deaerator
- 6 Water pump
- 7 Flow sensor
- 8 Plate heat exchanger
- 9 Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Components

- 1 3 Way diverting valve (DC)
- 2 Electric heater (1 ph: 6 kW / 3 ph: 9 kW)
- 3 Drain pan
- 4 DHW storage tank (200 L / Duplex stainless Steel)
- 6 Drain valve
- 6 Expansion tank (81)
- 7 Standard III remote controller 1) (air temp. sensor integrated)
- 1) Temperature control class (ERP class) : V

Connections

- A Inlet pipe from outdoor unit (female G1")
- B Outlet pipe to outdoor unit (female G1")
- Heating circuit outlet pipe (female G1")
- D Heating circuit inlet pipe (female G1")
- **(E)** Domestic hot water inlet pipe (female G1") Domestic hot water outlet pipe (female G1")
- © Domestic hot water re-circulation pipe (female G1")

THERMA V_{III} R290% Monobloc

Product Specification

Efficiency Data		Unit	7 kW (1 Ø) 7 kW (3 Ø)	9 kW (1 Ø) 9 kW (3 Ø)
Seasonal space heating eff. class (35°C / 55°	C)	-	A+++ / A+++	A+++ / A+++
Seasonal space heating efficiency (η_s) (35°C	/ 55°C)	%	207 / 151	205 / 151
SCOP (35°C / 55°C)		-	5.24 / 3.86	5.20 / 3.86
Declared load profile, average climate		-	L	L
Water heating efficiency (η_{WH}), average clima	te	%	130	130
COP _{DHW} , average climate		-	3.10	3.10
Water heating eff. class, average climate		-	A+	A+
Annual energy consumption, DHW (average of	limate)	kWh	780	780
Heating up time acc. to EN 16147 (average cl	imate)	h/mm	1h 25	1h 25
Max. usable water volume acc. to EN 16147 (average climate)	l	240	240
Declared load profile, warmer climate		-	L	L
Water heating efficiency (η_{WH}), warmer climate	te	%	160	160
COP _{DHW} , warmer climate		-	3.78	3.78
Water heating eff. class, warmer climate		-	A++	A++
Declared load profile, colder climate		-	L	L
Water heating efficiency (η_{WH}), colder climate	1	%	110	110
COP _{DHW} , colder climate		-	2.64	2.64
Water heating eff. class, colder climate		-	A	A
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	50 / 48
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	28 / 26
Sound power level (indoor unit)	Rated	dB(A)	3	9
Sound pressure level at 1m (indoor unit)	Rated	dB(A)	3	1
Nominal Capacity and COP/EER				
Air +7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 5.00	9.00 / 4.70
Air +2°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 3.80	8.00 / 3.70
Air -7°C / water +35°C	Heating capacity / COP	kW / -	7.00 / 2.80	9.00 / 2.70
Air +7°C / water +55°C	Heating capacity / COP	kW / -	4.50 / 3.35	5.50 / 3.30
Air -7°C / water +55°C	Heating capacity / COP	kW / -	7.00 / 2.40	8.00 / 2.20
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.00 / 4.40	5.50 / 4.20
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.00 / 2.80	5.50 / 2.60

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

Product Specification

COMBI UNIT (7/9 kW)

Outdoor Units		Unit	HM071HF UB40 HM073HF UB40	HM091HF UB40 HM093HF UB40
Operation range	Heating & DHW (Min. ~ Max.)	°C	-28	~ 35
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~	48
	Туре	-	R2	90
Refrigerant	GWP	-	3	3
	Precharged amount	g	90	00
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" according to ISC	7-1 (tapered pipe threads)
Dimension	HxWxD	mm	1,019 x 1,3	320 x 520
Weight	Net	kg	130	0.0
Futanian	Color of chassis / RAL code	-	Dawn gray ,	/ RAL 7037
Exterior	Color of front grille / RAL code	-	Dark dawn gra	ay / RAL 7012
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50 /	⁷ 380 ~ 415, 3, 50
Power supply	Standby power consumption	W	1	0
	Recommended circuit breaker	А	1 Ø: 20 /	′ 3 Ø: 16
Indoor Units		Unit	HN1616HY NK0 /	/ HN1639HY NK0
	Heating (Min. ~ Max.)	°C	15 -	· 75
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~	27
	DHW (Min. ~ Max.)	°C	15 ~	· 80
	Volume	l	20	00
Domestic hot water tank	Tank material	-	Duplex sta	inless steel
	Standby losses	W	6	0
Expansion vessel (heating circuit)	Volume	l	3	3
Electric heater	Capacity combination	kW	1 Ø: 6.0 /	′ 3 Ø: 9.0
Electric neater	Power supply	V, Ø, Hz	220 ~ 24	40, 1, 50
	Inlet / outlet diameter for connection to outdoor unit	inch		
Piping connections (water)	Inlet / outlet diameter for space heating	inch	Female G1" according to ISO	228-1 (parallel pipe threads)
	Inlet / outlet diameter for DHW	inch		
	Recirculation	inch		
Dimension	HxWxD	mm	1,750 x 6	00 × 660
Weight	Net	kg	1 Ø: 106.5 /	′ 3 Ø: 107.0
Exterior	Color / RAL code	-	Noble white	/ RAL 9016

THERMA V R290 MONOBLOC

Note

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- $4. \ Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.\\$
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80°C Operating is available only when the booster heater is operating.



THERMA V R290 MONOBLOC COMBI UNIT (7/9 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM071HF UB40 + HN1616HY NK0 / HM073HF UB40 + HN1639HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]	Capacity (kW)									
-25	5.90	5.85	5.85	5.85	5.80	5.80	5.80	-	-	-
-20	6.50	6.50	6.50	6.50	6.20	6.10	6.10	6.00	-	-
-15	7.00	7.00	7.00	7.00	6.80	6.70	6.30	6.30	6.20	6.20
-7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.60	6.40
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70	6.50
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80	6.50
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.70
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	6.80
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35	-	-	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00

HM091HF UB40 + HN1616HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	7.40	7.20	7.10	6.90	6.80	6.70	6.60	-	-	-
-20	8.20	7.90	7.70	7.50	7.30	7.10	6.90	6.60	-	-
-15	9.00	9.00	8.20	7.90	7.70	7.60	7.30	7.00	6.80	6.50
-7	9.00	9.00	9.00	8.50	8.40	8.00	7.90	7.70	7.40	6.60
-4	9.00	9.00	9.00	9.00	9.00	8.40	8.20	7.90	7.70	6.70
-2	9.00	9.00	9.00	9.00	9.00	9.00	8.40	8.10	7.60	6.80
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	7.80	6.90
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.10
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.20	7.20
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.30	7.30
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.40
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.40	7.50
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00

HM093HF UB40 + HN1639HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capacit	ty (kW)				
-25	7.90	7.77	7.92	8.08	8.20	8.40	8.40	-	-	-
-20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-	-
-15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
2	8.00	8.00	8.10	8.20	8.30	8.40	8.20	8.10	8.00	7.00
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	-	-	9.00	9.00	9.00	9.00	9.00	9.00	9.00	8.00

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM: Liters Per Minute (l/min), TC: Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \, \text{Above table values may not be matched according to installation condition.} \, \text{Except for rated value, the performance is not guaranteed}.$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM071HF UB40 + HN1616HY NK0 / HM073HF UB40 + HN1639HY NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C			
[°C DB]	Capacity (kW)									
20	5.30	6.00	6.70	7.00	7.00	7.00	7.00			
30	5.10	5.40	5.80	6.20	7.00	7.00	7.00			
35	5.00	5.40	5.80	6.20	6.80	6.80	7.00			
40	4.60	4.90	5.30	5.60	6.20	6.70	7.00			
45	4.20	4.70	5.30	5.60	6.20	6.50	7.00			

HM091HF UB40 + HN1616HY NK0 / HM093HF UB40 + HN1639HY NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	5.80	6.70	7.50	9.00	9.00	9.00	9.00
30	5.60	6.40	7.20	7.70	9.00	9.00	9.00
35	5.50	6.30	7.20	7.80	9.00	9.00	9.00
40	5.00	5.70	6.40	6.80	7.40	7.70	9.00
45	4.40	5.10	5.70	6.10	6.80	7.20	7.60

Note

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- $2.\, {\hbox{Direct interpolation is permissible.}}\, \hbox{Do not extrapolate}.$
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer




Technical Specification		Unit	Details			
Material	Body	-	Brass			
Material	Mesh	-	Stainless steel (STS304)			
Mesh	Mesh no.	-	30			
Mesn	Max. particle size	mm	0.6			
Piping connection		-	Female G1" according to ISO 228-1			


- * The strainer and valves are supplied with the product, but it need to be installed separately.
- *This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.

THERMA V R290 MONOBLOC COMBI UNIT (7/9kW)

Drawings [Unit: mm] [Unit: mm]

HM071HF UB40 / HM073HF UB40 HM091HF UB40 / HM093HF UB40









3D view

Top view








Side view

Front view

Side view



Before piping, remove the cover brackets.


If you need more drains, remove them.

Bottom view

No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Air Discharge Grille	-
4	Access to Electrical Terminals	Power, Communication

External

HN1616HY NK0 / HN1639HY NK0




No.	Part Name	Description	No.	Part Name		
1	Inlet Pipe from Outdoor Unit		5	Domestic Hot Water Inlet Pipe		
2	Outlet Pipe from Outdoor Unit	Female G1" According to ISO228-1	6	Domestic Hot Water Outlet Pipe	Female G1" According to ISO228- (Parallel pipe threads)	
3	Heating Circuit Outlet Pipe	(Parallel pipe threads)	7	DHW Re-circulation Pipe	, , , , , , , , , , , , , , , , , , , ,	
4	Heating Circuit Inlet Pipe		8	Control Panel	Built-in Remote Controller	

Internal

HN1616HY NK0 / HN1639HY NK0

Top view



No.	Part Name	Description	No.	Part Name	
1	DHW Tank	Domestic Hot Water Tank (200 L)	6	Heat Exchanger	Coil Heat Exchanger (Water / DHW)
2	Heater	Electric Heater (1Ø 6 kW, 3Ø 9 kW)	7	Control Box	PCB'A and Terminal Blocks
3	3 Way Valve	For DHW / Heating	8	Air Vent	For Air Purging
4	Expansion Vessel	8L for Heating Circuit	9	Drain Cock 1	Valve for DHW Tank Drain
5	DHW Tank Sensor	Temperature Sensor	10	Safety Valve	For DHW (10 bar)

THERMA V R290 MONOBLOC **COMBI UNIT (12/14/16 kW)**



Outdoor unit

HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60

Indoor unit

HN1616HY NKO HN1639HY NKO





























Key Components

Outdoor Unit



Indoor Unit (Combi Unit)



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 New biomimetic fan
- 3 Dual sound shield
- 4 R290 scroll compressor
- **5** Hydronic components assembly
- 6 Water pump
- Deaerator
- 8 Plate heat exchanger (ref / water)
- 9 Flow sensor
- Pressure sensor

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

Components

- 1 3 Way diverting valve (DC)
- 2 Electric heater (1 ph: 6 kW / 3 ph: 9 kW)
- 3 Drain pan
- 4 DHW storage tank (200 L / Duplex stainless Steel)
- 6 Drain valve
- 6 Expansion tank (81)
- 7 Standard III remote controller 1) (air temp. sensor integrated)
- 1) Temperature control class (ERP class) : V

Connections

- A Inlet pipe from outdoor unit (female G1")
- B Outlet pipe to outdoor unit (female G1")
- Heating circuit outlet pipe (female G1")
- D Heating circuit inlet pipe (female G1")
- **(E)** Domestic hot water inlet pipe (female G1") Domestic hot water outlet pipe (female G1")
- © Domestic hot water re-circulation pipe (female G1")

THERMA V_{III} R290% Monobloc

Product Specification

Efficiency Data		Unit	12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)
Seasonal space heating eff. class (35°C / 55	°C)	-	A+++ / A+++	A+++ / A+++	A+++ / A+++
Seasonal space heating efficiency (η_s) (35°C	/ 55°C)	%	215 / 156	212 / 155	201 / 154
SCOP (35°C / 55°C)		-	5.45 / 3.97	5.38 / 3.96	5.11 / 3.92
Declared load profile, average climate		-	L	L	L
Water heating efficiency (η _{WH}), average clima	ate	%	130	130	130
COP _{DHW} , average climate		-	3.00	3.00	3.00
Water heating eff. class, average climate		-	A+	A+	A+
Annual energy consumption, DHW (average	climate)	kWh	771	771	771
Heating up time acc. to EN 16147 (average of	climate)	h/mm	1h 25	1h 25	1h 25
Max, usable water volume acc, to EN 16147	(average climate)	l	240	240	240
Declared load profile, warmer climate		-	L	L	L
Water heating efficiency (η _{WH}), warmer clima	ite	%	151	151	151
COP _{DHW} , warmer climate		-	3.43	3.43	3.43
Water heating eff. class, warmer climate		-	A++	A++	A++
Declared load profile, colder climate		-	L	L	L
Water heating efficiency (η _{WH}), colder climat	е	%	101	101	101
COP _{DHW} , colder climate		-	2.34	2.34	2.34
Water heating eff. class, colder climate		-	А	A	А
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	49 / 48	51 / 50	52 / 51
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	27 / 26	29 / 28	30 / 29
Sound power level (indoor unit)	Rated	dB(A)		39	
Sound pressure level at 1m (indoor unit)	Rated	dB(A)		31	
Nominal Capacity and COP/EER					
Air +7°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 4.70	14.00 / 4.50	16.00 / 4.30
Air +2°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 3.72	14.00 / 3.61	14.50 / 3.49
Air -7°C / water +35°C	Heating capacity / COP	kW / -	11.80 / 3.27	13.00 / 3.21	13.80 / 3.17
Air +7°C / water +55°C	Heating capacity / COP	kW / -	10.00 / 3.10	11.00 / 3.25	12.00 / 3.30
Air -7°C / water +55°C	Heating capacity / COP	kW / -	9.30 / 2.32	10.30 / 2.28	10.90 / 2.26
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	11.50 / 3.78	12.00 / 3.70	12.50 / 3.70
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	10.50 / 3.12	12.00 / 2.99	12.50 / 2.95

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80°C Operating is available only when the booster heater is operating.

Product Specification


Outdoor Units		Unit	HM121HF UB60 HM123HF UB60	HM141HF UB60 HM143HF UB60	HM161HF UB60 HM163HF UB60			
Operation range	Heating & DHW (Min. ~ Max.)	°C		-28 ~ 35				
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 48				
	Туре	-		R290				
Refrigerant	GWP	-		3				
	Precharged amount	g		1,200				
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" ac	cording to ISO 7-1 (tapered	d pipe threads)			
Dimension	HxWxD	mm		1,019 x 1,560 x 520				
Weight	Net	kg		181.0				
Fotovico	Color of chassis / RAL code	-						
Exterior	Color of front grille / RAL code	-		Dark dawn gray / RAL 701	2			
	Voltage, phase, frequency	V, Ø, Hz	220	~ 240, 1, 50 / 380 ~ 415,	3, 50			
Power supply	Standby power consumption	W		10				
	Recommended circuit breaker	А		1 Ø: 25 / 3 Ø: 16				
Indoor Units	·	Unit	HN1	1616HY NKO / HN1639HY	NK0			
	Heating (Min. ~ Max.)	°C		15 ~ 75				
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 27				
	DHW (Min. ~ Max.)	°C		15 ~ 80				
	Volume	l		200				
Domestic hot water tank	Tank material	-		Duplex stainless steel				
	Standby losses	W		60				
Expansion vessel (heating circuit)	Volume	L		8				
Florida hantan	Capacity combination	kW		1 Ø: 6.0 / 3 Ø: 9.0				
Electric heater	Power supply	V, Ø, Hz		220 ~ 240, 1, 50				
	Inlet / outlet diameter for connection to outdoor unit	inch						
Piping connections (water)	Inlet / outlet diameter for space heating	inch	Female G1" acc	220 ~ 240, 1, 50 emale G1" according to ISO228-1 (parallel pipe threads)				
	Inlet / outlet diameter for DHW	inch						
	Recirculation	inch						
Dimension	HxWxD	mm		1,750 x 600 × 660				
Weight	Net	kg		1 Ø: 106.5 / 3 Ø: 107.0				
Exterior	Color / RAL code	-		Noble white / RAL 9016				

THERMA V R290 MONOBLOC

COMBI UNIT (12/14/16 kW)

Note

- $1. \ \mathsf{Due} \ \mathsf{to} \ \mathsf{our} \ \mathsf{policy} \ \mathsf{of} \ \mathsf{innovation}, \ \mathsf{some} \ \mathsf{specifications} \ \mathsf{may} \ \mathsf{be} \ \mathsf{changed} \ \mathsf{without} \ \mathsf{notification}.$
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- $4. \ Performances \ are in accordance with EN14511 \ and \ reflect ErP \ testing \ conditions. Above gives the declared values at rated conditions according to ErP \ regulation.$
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 65 ~ 80°C Operating is available only when the booster heater is operating



091

THERMA V R290 MONOBLOC COMBI UNIT (12/14/16 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM121HF UB60 + HN1616HY NK0 / HM123HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	8.36	8.07	7.79	7.54	7.32	6.37	-	-	-	-
-20	9.60	9.39	9.20	9.09	9.08	8.27	6.77	-	-	-
-15	10.84	10.69	10.55	10.55	10.84	10.76	8.71	7.17	-	-
-7	12.00	12.00	12.00	12.00	12.00	12.00	11.27	10.00	8.99	-
-4	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.88	9.65	8.91
-2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.45	10.29	9.32
2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	8.08	6.84	6.36
7	12.00	12.00	12.00	12.00	12.00	12.00	12.00	10.28	8.34	7.67
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.20	9.90	8.95
15	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.09
18	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	11.69
20	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00
35	-	-	12,00	12,00	12.00	12.00	12,00	12,00	12,00	12.00

HM141HF UB60 + HN1616HY NK0 / HM143HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C		
[°C DB]		Capacity (kW)										
-25	8.88	8.57	8.28	8.01	7.78	6.37	-	-	-	-		
-20	10.20	9.97	9.78	9.66	9.48	8.27	6.77	-	-	-		
-15	12.06	11.99	11.79	11.59	11.29	10.76	8.71	7.17	-	-		
-7	14.00	14.00	13.82	13.63	13.45	12,58	11.27	10.00	8.99	-		
-4	14.00	14.00	13.90	13.83	13.83	13.23	12.06	10.88	9.65	8.91		
-2	14.00	14.00	13.96	13.95	14.00	13.71	12.59	11.45	10.29	9.32		
2	14.00	14.00	14.00	14.00	14.00	14.00	13.16	8.08	6.84	6.36		
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	10.28	8.34	7.67		
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	11,20	9.90	8.95		
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.72	12.02	11.09		
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.82	12.89	11.69		
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00	13.47	12.09		
35	-	-	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.80		

HM161HF UB60 + HN1616HY NK0 / HM163HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C	LWT 70 °C	LWT 75 °C
[°C DB]					Capaci	ty (kW)				
-25	9.41	9.08	8.76	8.48	7.81	6.37	-	-	-	-
-20	10.80	10.56	10.35	10.23	9.48	8.27	6.77	-	-	-
-15	13.36	13.28	12.74	12.15	11.29	10.76	8.71	7.17	-	-
-7	16.00	16.00	15.17	14.35	13.52	12,58	11.27	10.00	8.99	-
-4	16.00	16.00	15.43	14.85	14.29	13.23	12.06	10.88	9.65	8.91
-2	16.00	16.00	15.69	15.34	14.81	13.71	12.59	11.45	10.29	9.32
2	16.00	16.00	16.00	16.00	16.00	14.84	13.16	8.08	6.84	6.36
7	16.00	16.00	16.00	16.00	16.00	16.00	14.25	10.28	8.34	7.67
10	16.00	16.00	16.00	16.00	16.00	16.00	14.92	11.20	9.90	8.95
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	12.72	12.02	11.09
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	13.82	12.89	11.69
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	14.56	13.47	12.09
35	-	-	16.00	16.00	16.00	16.00	16.00	16.00	14.40	12.80

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ /min), TC : Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \textbf{Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed. } \\$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM121HF UB60 + HN1616HY NK0 / HM123HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C		
[°C DB]			Capacity (kW)						
20	11.50	11.50	11.50	11.50	11.50	11.50	11.50		
30	10.97	11.50	11.50	11.50	11.50	11.50	11.50		
35	10.50	11,28	11.50	11.50	11.50	11.50	11.50		
40	9.35	10.08	10.80	11.27	11.50	11.50	11.50		
45	8.19	8.90	9.61	10.07	10.77	11.23	11.50		

HM141HF UB60 + HN1616HY NK0 / HM143HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
20	12.00	12.00	12.00	12.00	12.00	12.00	12.00
30	12.00	12.00	12.00	12.00	12.00	12.00	12.00
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00
40	10.68	11,52	12.00	12.00	12.00	12.00	12.00
45	9.36	10.17	10.98	11,51	12.00	12.00	12.00

HM161HF UB60 + HN1616HY NK0 / HM163HF UB60 + HN1639HY NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]							
20	12.50	12.50	12.50	12,50	12.50	12.50	12.50
30	12.50	12.50	12,50	12,50	12.50	12.50	12,50
35	12.50	12.50	12.50	12,50	12.50	12.50	12.50
40	12.02	12.50	12.50	12.50	12.50	12.50	12,50
45	10.03	10.78	11.54	12,05	12.50	12,50	12.50

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
 Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition, Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

 4. The shaded areas are not guaranteed continuous operation.
- _____

Supplied Parts

Strainer




Technical Specification		Unit	Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1


- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.

THERMA V R290 MONOBLOC COMBI UNIT (12/14/16 kW)


Drawings [Unit: mm]


HM121HF UB60 / HM123HF UB60 HM141HF UB60 / HM143HF UB60 HM161HF UB60 / HM163HF UB60





Front view






Bottom view

No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1 inch
2	Entering Water Pipe	Male PT 1 inch
3	Air Discharge Grille	-
4	Access to Electrical Terminals	Power, Communication






No.	Part Name	Description	No.	Part Name	
1	Inlet Pipe from Outdoor Unit		5	Domestic Hot Water Inlet Pipe	
2	Outlet Pipe from Outdoor Unit	Female G1" According to ISO228-1	6	Domestic Hot Water Outlet Pipe	Female G1" According to ISO228-1 (Parallel pipe threads)
3	Heating Circuit Outlet Pipe	(Parallel pipe threads)	7	DHW Re-circulation Pipe	, , , , , , , , , , , , , , , , , , , ,
4	Heating Circuit Inlet Pipe		8	Control Panel	Built-in Remote Controller

Internal

HN1616HY NK0 / HN1639HY NK0



No.	Part Name	Description	No.	Part Name	Description	
1	DHW Tank	Domestic Hot Water Tank (200 L)	omestic Hot Water Tank (200 L) 6 Heat Exchanger Coil Heat Excha		Coil Heat Exchanger (Water / DHW)	
2	Heater	Electric Heater (1Ø 6 kW, 3Ø 9 kW)	7	Control Box	PCB'A and Terminal Blocks	
3	3 Way Valve	For DHW / Heating	8	Air Vent	For Air Purging	
4	Expansion Vessel	8L for Heating Circuit	9	Drain Cock 1	Valve for DHW Tank Drain	
5	DHW Tank Sensor	Temperature Sensor	10	Safety Valve	For DHW (10 bar)	






The Final Evolution of the R32 Monobloc

The R32 Monobloc S I is the ultimate evolution of the R32 Monobloc series, with all the benefits of the R32 Monobloc S in a sleek gray European design.

What is R32 Monobloc SII

The THERMA V R32 Monobloc S I is the next generation model that continues the legacy of the LG THERMA V R32 Monobloc S. The new generation's sleek look matches that of the rest of the modernized line-up, while maintaining the excellent performance of the existing R32 Monobloc S, and that the single fan design has been applied to not only the 5, 7, and 9 kW but also the 12, 14, and 16 kW models. Along with these design changes, various features and installation conveniences that were developed from the R290 Monobloc have been reflected.



Key Features


- Capacity range from 5 to 16 kW for new build and renovation
- Refined gray design that adapt to various surroundings
- Standalone heat pump allowing easy installation (Plug and play solution)
- ErP Energy Labeling A+++ / A++ for space heating (Average Climate 35°C / 55°C LWT)
- Low noise level for high installation flexibility
- 100% Heating capacity at -15°C outdoor temperature (16 kW 90%)
- Maximum flow temperature up to 65°C
- Operation range down to -25°C











Product Range

Phase	Capacity (kW)	Outdoor Unit			
	5	HM051MRS UA40			
7	7	HM071MRS UA40			
10	9	HM091MRS UA40			
שו	12	HM121MRS UB40			
	14	HM141MRS UB40			
	16	HM161MRS UB40			
	12	HM123MRS UB40			
30	14	HM143MRS UB40			
	16	HM163MRS UB40			


HIGHLIGHT OF R32 MONOBLOC S II



Browse now Q

New Design

European-style Gray



Enhanced Convenience



- Outdoor units design meets European standards
- Refined gray design that will look great anywhere
- 2 feet instead of 3 feet which was uncomfortable

Improved Structure


Prevent Cumulative Icing

Elimination of side panel and rear grille to prevent ice build-up

Monobloc S











Free from ice build up

Monobloc S I

Space Efficiency

Simpler Exterior

- Integrated hydronic components in the package
- Easier and guicker installation without refrigerant piping work
- The best solution, when interior space is limited



Comfortable Ease

Low Noise Level Allowing Installation Flexibility

- Designed to reach lower noise levels in order to meet homeowner expectations in urban areas
- Noise reduction technology such as encapsulated compressor and vibration-decoupling to ensure a quieter and more comfortable experience



Reliable Performance

Remarkable Heating Performance even in Cold Weather

- 100 % heating capacity at -15 °C ambient temp. (@LWT 35 °C, except for 16 kW model)
- Longer continuous heating periods with reduced defrost operation time and extended intervals



Convenience

Easy Maintenance

Easy access to PCB for installing and maintenance







Separate Supply of Strainer

Easy strainer cleaning by not opening the panel







Integrated strainer

Loose supplied item (Supplied with outdoor unit)

THERMA V R32 MONOBLOC S II (5/7/9kW)

Outdoor unit

HM051MRS UA40 HM071MRS UA40 HM091MRS UA40






















Key Components

Outdoor Unit



Components

- 1 Standard III remote controller 1) 2)
- 2 Black Fin heat exchanger (air / ref.)
- 3 Biomimetic fan
- 4 R1 compressor
- 5 Hydronic components assembly
- 6 Air vent valve
- Safety valve
- 8 Water pump Pressure sensor
- Tlow sensor
- ① Expansion tank (81)
- Plate heat exchanger Strainer (loose supplied)
- 1) The remote controller is supplied with the product, but it needs to be installed separately.
- 2) Temperature control class (ERP class): V

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

THERMA V... (B) Monobloc S I

Product Specification

Efficiency Data		Unit	5 kW (1 Ø)	7 kW (1 Ø)	9 kW (1 Ø)	
Seasonal space heating eff. class (35°C	/ 55°C)	-	A+++ / A++	A+++ / A++	A+++ / A++	
Seasonal space heating efficiency (η_s) (3	85°C / 55°C)	%	175 / 125	176 / 125	179 / 125	
SCOP (35°C / 55°C)		-	4.46 / 3.20	4.48 / 3.20	4.55 / 3.20	
Sound power level	Rated / low noise mode	dB(A)	57 / 54	57 / 55	57 / 55	
Sound pressure level at 5m	Rated / low noise mode	dB(A)	35 /32	35 / 33	35 / 33	
Nominal Capacity and COP/EER						
Air +7°C / water +35°C	Heating capacity / COP	kW / -	5.50 / 4.70	7.00 / 4.70	9.00 / 4.60	
Air +2°C / water +35°C	Heating capacity / COP	kW / -	5.50 / 3.60	6.00 / 3.55	7.00 / 3.50	
Air +7°C / water +55°C	Heating capacity / COP	kW / -	5.50 / 2.70	5.75 / 2.70	6.00 / 2.70	
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.50 / 4.70	7.00 / 4.65	9.00 / 4.60	
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.50 / 3.30	7.00 / 3.20	9.00 / 3.00	
Outdoor Units		Unit	HM051MRS UA40	HM071MRS UA40	HM091MRS UA40	
Operation range	Heating & DHW (Min. ~ Max.)	°C	-25 ~ 35			
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48			
	Heating (Min. ~ Max.)	°C	15 ~ 65			
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27			
	DHW (Min. ~ Max.)	°C		15 ~ 80		
	Туре	-		R32		
Refrigerant	GWP	-		675		
	Precharged amount	g		1,400		
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" ac	cording to ISO 7-1 (tapered	l pipe threads)	
Expansion vessel (heating circuit)	Volume	l		8		
Dimension	HxWxD	mm		853 x 1,242 x 391		
Weight	Net	kg		94		
Eutorion	Color of chassis / RAL code	-		Dawn gray / RAL 7037		
Exterior	Color of front grille / RAL code	-	I	Dark dawn gray / RAL 7012	2	
	Voltage, phase, frequency	V, Ø, Hz		220 ~ 240, 1, 50		
Power supply	Standby power consumption	W		10		
	Recommended circuit breaker	А	16 20		25	

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

THERMA V R32 MONOBLOC S II (5/7/9kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM051MRS UA40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	5.50	5.50	5.50	5.50	-	-	-	-
-20	5.50	5.50	5.50	5.50	5.23	-	-	-
-15	5.50	5.50	5.50	5.50	5,23	5.23	-	-
-7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-4	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
-2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
10	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
15	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
18	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
20	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
35	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50

HM071MRS UA40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	5.85	5.85	5.85	5.85	-	-	-	-
-20	6.43	6.43	6.43	6.43	6.10	-	-	-
-15	7.00	7.00	7.00	7.00	6.65	6.65	-	-
-7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00

HM091MRS UA40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	6.20	6.20	6.20	6.20	-	-	-	-
-20	7.60	7.60	7.60	7.60	7.22	-	-	-
-15	9.00	9.00	9.00	9.00	8.55	8.55	-	-
-7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00

100

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3, Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM051MRS UA40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	5.50	5.50	5.50	5.50	5.50	5.50	5.50
20	5.50	5.50	5.50	5.50	5.50	5.50	5.50
30	5.50	5.50	5.50	5.50	5.50	5.50	5.50
35	5.50	5.50	5.50	5.50	5.50	5.50	5.50
40	5,29	5.32	5.36	5.38	5.41	5.43	5.45
45	5.09	5.15	5.21	5.25	5.31	5.36	5.40

THERMA V. (B32) Monobloc S I

HM071MRS UA40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C		
[°C DB]	Capacity (kW)								
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
30	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00		
40	6.36	6.45	6.55	6.61	6.71	6.77	6.84		
45	5.71	5.82	5.92	5.99	6.10	6.17	6.24		

HM091MRS UA40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C		
[°C DB]		Capacity (kW)							
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
30	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00		
40	7.66	7.66	7.65	7.65	7.65	7.65	7.65		
45	6.31	6.35	6.39	6.42	6.45	6.48	6.51		

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \ Above \ table \ values \ may \ not \ be \ matched \ according \ to \ installation \ condition. \ Except \ for \ rated \ value, \ the \ performance \ is \ not \ guaranteed.$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer



Technical Specification		Details			
Body	-	Brass			
Mesh	-	Stainless steel (STS304)			
Mesh no.	-	30			
Max. particle size	mm	0.6			
	-	Female G1" according to ISO 228-1			
	Mesh no.	Mesh - Mesh no Max. particle size mm			

- * The strainer and valves are supplied with the product, but it need to be installed separately.
- * This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.


[Unit: mm]


THERMA V R32 MONOBLOC S II (5/7/9kW)


THERMA V... (B32) Monobloc S I


Drawings [Unit: mm]


HM051MRS UA40 HM071MRS UA40 HM091MRS UA40












Bottom view



No.	Part Name	Description		
1	Entering Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)		
2	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)		
3	Air Discharge Grille	-		
4	Top Cover	-		
5	Front Panel	-		
6	Side Panel	-		
7	Low Voltage	Communication Cable Hole		
8	UNIT Power Power Cable Hole			
9	Water Pump	OH SUNG, ODM-061P / GRUNDFOS, UPM3K 20-75 CHBL		
10	Plate Heat Exchanger	Heat Exchanger Between Refrigerant and Water		
11	Compressor Shield Panel	-		
12	Safety Relief Valve	Open at Water Pressure 3 Bar		
13	Indoor Control Box	Hydro, Cycle PCB and Terminal Blocks		
14	Outdoor Control Box	Inverter PCB and Terminal Blocks		
15	Flow Sensor	SIKA VVX20 / SEBA LGF-080-C20-E-0.5V, 5-80 LPM		
16	Water Pressure Sensor	SENSATA 2HMP3-05W 02-MPa		
17	Automatic Air Vents	-		

THERMA V R32 MONOBLOC S II (12/14/16 kW)

Outdoor unit

HM121MRS UB40 / HM123MRS UB40 HM141MRS UB40 / HM143MRS UB40 HM161MRS UB40 / HM163MRS UB40
























Key Components

Outdoor Unit



Components

- 1 Standard III remote controller 1) 2)
- 2 Black Fin heat exchanger (air / ref.)
- 3 Biomimetic fan
- 4 R1 compressor
- 5 Hydronic components assembly
- 6 Air vent valve
- Safety valve
- 8 Water pump
- Pressure sensor
- Tlow sensor
- ① Expansion tank (81) Plate heat exchanger
- Strainer (loose supplied)
- 1) The remote controller is supplied with the product, but it needs to be installed separately.
- 2) Temperature control class (ERP class): V

Connections

- A Leaving water pipe (male PT 1")
- B Entering water pipe (male PT 1")

THERMA V... (B) Monobloc S I

Product Specification

Efficiency Data		Unit	12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)	
Seasonal space heating eff. class (35°C /	′ 55°C)	-	A+++ / A++	A+++ / A++	A+++ / A++	
Seasonal space heating efficiency (η_s) (3	5°C / 55°C)	%	184 / 136	182 / 135	178 / 135	
SCOP (35°C / 55°C)		-	4.67 / 3.47	4.62 / 3.46	4.53 / 3.45	
Sound power level	Rated / low noise mode	dB(A)	60 / 56 61 / 57		61 / 57	
Sound pressure level at 5m	Rated / low noise mode	dB(A)	38 / 34	39 / 35	39 / 35	
Nominal Capacity and COP/EER						
Air +7°C / water +35°C	Heating capacity / COP	kW/-	12.00 / 4.90	14.00 / 4.80	16.00 / 4.70	
Air +2°C / water +35°C	Heating capacity / COP	kW / -	11.00 / 3.60	12.00 / 3.55	13.80 / 3.50	
Air +7°C / water +55°C	Heating capacity / COP	kW / -	11.00 / 2.90	11.50 / 2.85	12.00 / 2.80	
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	12.00 / 4.80	14.00 / 4.70	16.00 / 4.60	
Air +35°C / water +7°C	Cooling capacity / EER	kW/-	12.00 / 3.20	14.00 / 3.10	15.00 / 3.00	
Outdoor Units		Unit	HM121MRS UB40 HM123MRS UB40	HM141MRS UB40 HM143MRS UB40	HM161MRS UB40 HM163MRS UB40	
Operation range	Heating & DHW (Min. ~ Max.)	°C		-25 ~ 35		
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48			
	Heating (Min. ~ Max.)	°C				
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27			
	DHW (Min. ~ Max.)	°C		15 ~ 80		
	Туре	-		R32		
Refrigerant	GWP	-		675		
	Precharged amount	g		1,600		
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" ac	cording to ISO 7-1 (tapered	d pipe threads)	
Expansion vessel (heating circuit)	Volume	l		8		
Dimension	HxWxD	mm		1,019 x 1,320 x 520		
Weight	Net	kg		117		
Exterior	Color of chassis / RAL code	-		Dawn gray / RAL 7037		
LACE IUI	Color of front grille / RAL code	-		Dark dawn gray / RAL 701:	2	
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50 / 380 ~ 415, 3, 50			
Power supply	Standby power consumption	W	10			
	Recommended circuit breaker	А		40 / 16		

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

THERMA V... (B32) Monobloc S I

THERMA V R32 MONOBLOC S II (12/14/16 kW)

Performance Table for Heating Operation

Maximum heating capacity (Include defrost effect)

HM121MRS UB40 / HM123MRS UB40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	9.50	9.50	9.50	9.50	-	-	-	-
-20	10.75	10.75	10.75	10.75	10.21	-	-	-
-15	12.00	12.00	12.00	12,00	11.50	11.50	-	-
-7	12.00	12.00	12,00	12,00	12.00	12,00	12.00	-
-4	12.00	12.00	12.00	12,00	12.00	12.00	12.00	12.00
-2	12.00	12.00	12,00	12,00	12.00	12.00	12,00	12.00
2	12.00	12.00	12.00	12,00	12.00	12.00	12.00	12.00
7	12.00	12.00	12,00	12,00	12.00	12.00	12,00	12,00
10	12.00	12.00	12.00	12,00	12.00	12.00	12.00	12.00
15	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12,00
18	12,00	12.00	12,00	12,00	12.00	12,00	12,00	12,00
20	12,00	12.00	12,00	12,00	12,00	12,00	12,00	12,00
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00

HM141MRS UB40 / HM143MRS UB40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	10.00	10.00	10.00	10.00	-	-	-	-
-20	12.00	12.00	12.00	12.00	11.40	-	-	-
-15	14.00	14.00	14.00	14.00	13.30	13.30	-	-
-7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	-
-4	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
-2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00	12.50

HM161MRS UB40 / HM163MRS UB40

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]				Capaci	ty (kW)			
-25	10.50	10.50	10.50	10.50	-	-	-	-
-20	13.25	13.25	13.25	13.25	12.59	-	-	-
-15	16.00	14.40	14.40	14.40	13.68	13.68	-	-
-7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	-
-4	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
-2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
10	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00	13.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM121MRS UB40 / HM123MRS UB40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	12.00	12,00	12.00	12,00	12.00	12.00	12.00
20	12,00	12,00	12.00	12,00	12.00	12.00	12.00
30	12,00	12,00	12.00	12,00	12.00	12.00	12.00
35	12.00	12,00	12.00	12,00	12.00	12.00	12.00
40	11.05	11.19	11.33	11.43	11.57	11.67	11.76
45	10.10	10.37	10.64	10.83	11.10	11.28	11.46

HM141MRS UB40 / HM143MRS UB40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C		
[°C DB]	Capacity (kW)								
10	12.50	12,80	13.10	13.30	13.60	13.80	14.00		
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00		
30	14.00	14.00	14.00	14.00	14.00	14.00	14.00		
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00		
40	12,35	12,60	12,84	13.01	13,26	13,42	13.59		
45	10.69	11.19	11.69	12.02	12.51	12.84	13.17		

HM161MRS UB40 / HM163MRS UB40

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]							
10	13.00	13.60	14.20	14.60	15,20	15.60	16.00
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00
30	16.00	16.00	16.00	16.00	16.00	16.00	16.00
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00
40	13.60	13.96	14.32	14.56	14.92	15.16	15.40
45	11.20	11.76	12.32	12,69	13,25	13.62	14.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- $\bullet \ Above \ table \ values \ may \ not \ be \ matched \ according \ to \ installation \ condition. \ Except \ for \ rated \ value, \ the \ performance \ is \ not \ guaranteed.$
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Supplied Parts

Strainer



Technical Specification		Unit	Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mesh	Mesh no.	-	30
Mesn	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1

^{*} The strainer and valves are supplied with the product, but it need to be installed separately.


^{*} This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.


THERMA V R32 MONOBLOC S II (12/14/16 kW)

THERMA V... (B2) Monobloc S I


Drawings [Unit: mm]


HM121MRS UB40 / HM123MRS UB40 HM141MRS UB40 / HM143MRS UB40 HM161MRS UB40 / HM163MRS UB40







3D view









No.	Part Name	Description
1	Entering Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
2	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
3	Air Discharge Grille	-
4	Top Cover	-
5	Front Panel	-
6	Side Panel	-
7	Low Voltage	Communication Cable Hole
8	UNIT Power	Power Cable Hole
9	Water Pump	OH SUNG, ODM-061P / GRUNDFOS, UPM3K 20-75 CHBL
10	Plate Heat Exchanger	Heat Exchanger Between Refrigerant and Water
11	Compressor Shield Panel	-
12	Safety Relief Valve	Open at Water Pressure 3 Bar
13	Indoor Control Box	Hydro, Cycle PCB and Terminal Blocks
14	Outdoor Control Box	Inverter PCB and Terminal Blocks
15	Flow Sensor	SIKA VVX20 / SEBA LGF-080-C20-E-0.5V, 5-80 LPM
16	Water Pressure Sensor	SENSATA 2HMP3-05W 02-MPa
17	Automatic Air Vents	-



What is R32 Hydrosplit

The LG THERMA V Hydrosplit series is a simple, safe heat pump that eliminating the risk of indoor refrigerant leakage by connecting outdoor unit and indoor unit using water piping. It separates the indoor unit and outdoor unit, connecting them just via water pipes instead of refrigerant pipe.

Key Features

- Capacity range from 12 to 16 kW for renovation and large new build
- ErP Energy Labeling A+++ / A++ for space heating (Average Climate 35°C / 55°C LWT)
- ErP Energy Labeling A+ for hot water heating (L profile)
- No need for F-gas license and simple installation due to no refrigerant piping work
- Operation range down to -25°C
- Maximum flow temperature up to 65°C













Product Range

Phase	Capacity	Indoor	Outdoor Unit	
Pnase	(kW)	Hydro Unit	Combi Unit	Outdoor Unit
	12	- 7		HU121MRB U30
1Ø	14			HU141MRB U30
	16	111111111111111111111111111111111111111	LINGSONIDS	HU161MRB U30
	12	HN1600MC NK1	HN1616Y NB1	HU123MRB U30
30 14	14			HU143MRB U30
			HÚ163MRB U30	

HIGHLIGHT OF R32 HYDROSPLIT

THERMA V_m (R32) Hydrosplit

Simple Installation without **Refrigerant Piping**

- No need for F-gas license, because outdoor and indoor unit are connected by water pipes
- As hydronic parts are packaged inside indoor units, the installation can be realized with minimum usage of space
- Refrigerant is hermetically sealed inside outdoor unit




Remarkable Heating Performance even in Cold Weather

- Wide operation range down to -25℃
- 100 % heating capacity at -7℃ ambient temp. (@ LWT 35℃)
- Reduces energy bills with the highest energy efficiency of A+++ (@ 35°C)



No Risk of Indoor Refrigerant Leakage

The Hydrosplit architecture, with no refrigerant circulating indoors, makes it possible to expand the living space, as the minimum floor area requirements do not apply.



All-in-one Integration (Combi Unit)

- Integrated indoor unit with a hot water storage tank
- Saves space in the technical room with a small footprint
- Installation time reduced with pre-installed components
- Harmonized with other household appliances for a cohesive exterior



Sophisticated and **Harmonious Exterior**

The indoor unit's sleek design fits into diverse indoor spaces, such as a utility or laundry room, a garage or a kitchen.



Save Space and Time

Unlike in the case of a conventional system, this all-in-one solution requires reduced installation time and saves valuable living space.





THERMA V_{TM} (R32) Hydrosplit **HYDRO UNIT**




Only Water Enters Home

The LG THERMA V Hydrosplit series is a simple, safe heat pump that eliminating the risk of indoor refrigerant leakage by connecting outdoor unit and indoor unit using water piping. Since the indoor unit of R32 Hydrosplit Hydro Unit is installed on the wall rather than on the floor, space is not wasted, and the light weight enables quick installation. This makes it perfect for renovation projects. Also, it has good maintainability because the indoor unit is located indoors, for example in a machine room.

Key Features

- Capacity range from 12 to 16 kW for renovation and large new build
- No need for F-gas license and simple installation due to no refrigerant piping work
- Operation range down to -25°C
- Maximum flow temperature up to 65°C
- High level hydronic components integration for fast and clean



Application







Certifications









Energy Label







THERMA V_m (R22) Hydrosplit

THERMA V R32 HYDROSPLIT HYDRO UNIT


Outdoor unit

HU121MRB U30 / HU123MRB U30 HU141MRB U30 / HU143MRB U30 HU161MRB U30 / HU163MRB U30

Indoor unit

HN1600MC NK1






















Key Components

Hydro Unit



Components

- 1 Standard III remote controller 1) (air temp. sensor integrated)
- 2 Flow sensor
- Water pressure sensor
- 4 Air vent valve
- 6 Backup electric heater (6 kW, accessory)
- 6 Water pump
- 7 Expansion vessel (8 l)
- 8 Strainer

1) Temperature control class (ERP class) : V

Connections

- A Heating circuit outlet pipe (male PT 1")
- B Heating circuit inlet pipe (male PT 1")
- Outlet pipe to outdoor unit (male PT 1")
- D Inlet pipe from outdoor unit (male PT 1")

Product Specification


Efficiency Data			12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)		
Seasonal space heating eff. class (35°C / 55	5°C)	-	A+++ / A++	A+++ / A++	A+++ / A++		
Seasonal space heating efficiency (η_s) (35°C	: / 55°C)	%	181 / 137	180 / 136	179 / 135		
SCOP (35°C / 55°C)		-	4.60 / 3.50	4.57 / 3.47	4.55 / 3.45		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	61 / 60	62 / 60	63 / 60		
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	39 / 38	40 / 38	41 / 38		
Sound power level (indoor unit)	Rated	dB(A)		44			
Sound pressure level at 1m (indoor unit)	dB(A)		36				
Nominal Capacity and COP/EER							
Air +7°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 5.04	14.00 / 4.89	16.00 / 4.80		
Air +2°C / water +35°C	Heating capacity / COP	kW / -	11.00 / 3.65	12.00 / 3.63	13.80 / 3.60		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	11.00 / 2.90	11.50 / 2.85	12.00 / 2.80		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	12.00 / 4.75	14.00 / 4.30	16.00 / 4.00		
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	12.00 / 2.70	14.00 / 2.60	16.00 / 2.50		
Outdoor Units		Unit	HU121MRB U30 HU123MRB U30	HU141MRB U30 HU143MRB U30	HU161MRB U30 HU163MRB U30		
Operation range	Heating & DHW (Min. ~ Max.)	°C		-25 ~ 35			
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48				
	Туре	-	R32				
Refrigerant	GWP	-	675				
	Precharged amount	g		2,100			
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" acc	cording to ISO 7-1 (tapered	d pipe threads)		
Dimension	HxWxD	mm		1,380 x 950 x 330			
Weight	Net	kg		91.7			
Exterior	Color of chassis / RAL code	-		Warm gray / RAL 7044			
	Voltage, phase, frequency (10, 30)	V, Ø, Hz	220	- 240, 1, 50 / 380 - 415, 3	3, 50		
Power supply	Standby power consumption	W		60			
	Recommended circuit breaker (10, 30)	А		40 / 16			
Indoor Units		Unit		HN1600MC NK1			
2	Heating (Min. ~ Max.)	°C		15 ~ 65			
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 27			
	DHW (Min. ~ Max.)	°C		15 ~ 80			
Expansion vessel (heating circuit)	Volume	l		8			
	Outlet to outdoor unit	inch					
Piping connections (water)	Inlet from outdoor unit	inch	Male PT 1" acc	cording to ISO 7-1 (tapered	d pipe threads)		
Outlet to heat load		inch	mater in according to 150 / I (tapered pipe tilleaus)				
	Inlet from heat load	inch					
Dimension	HxWxD	mm		850 x 490 x 315			
Weight	Net	kg		30.5			
Exterior	Color / RAL code	-	Noble white / RAL 9016				

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

THERMA V R32 HYDROSPLIT HYDRO UNIT

Accessory Parts (Optional Accessory)

Accessory Backup Heater for Hydrosplit Hydro Unit



Electrical Specification			HA061C E1	HA063C E1	
	Capacity combination	kW	3.0 + 3.0	2,0 +2,0 + 2,0	
Backup heater	Heating steps	Steps	1	1	
Backup Heater	Power supply		220 ~ 240, 1, 50	380 ~ 415, 30, 50	
	Rated running current	А	24.0	8.7	

^{*} The backup heater should be purchased and installed separately.

Supplied Parts

Strainer



Technical Specification		Details			
Material	Body	Brass			
Material	Mesh	Stainless steel (ST304)			
Mach	Mesh no.	30			
Mesh	Max. particle size	0.6 mm			
Piping connection		Female G 1" according to ISO 228-1			

^{*} The strainer is supplied with the product, but it needs to be installed separately.





^{*} This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.

121

THERMA V R32 HYDROSPLIT HYDRO UNIT

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU121MRB U30 / HU123MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C			
[°C DB]		Capacity (kW)									
-25	9.66	8.85	8.42	8.29	-	-	-	-			
-20	10.13	10.00	9.88	9.75	9.63	-	-	-			
-15	11.50	11.50	11.50	11.50	11.50	11.50	-	-			
-7	12,00	12.00	12,00	12,00	12.00	12.00	12.00	-			
-4	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
-2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
7	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
15	12.00	12.00	12,00	12,00	12.00	12.00	12.00	12.00			
18	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			
20	12.00	12.00	12,00	12,00	12.00	12.00	12.00	12.00			
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00			

HU141MRB U30 / HU143MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C			
[°C DB]		Capacity (kW)									
-25	10.04	9.21	8.76	8.62	-	-	-	-			
-20	11.82	11,25	10.95	10.67	10.59	-	-	-			
-15	12.52	12.90	13.26	12,88	12,81	12.63	-	-			
-7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	-			
-4	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
-2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			

HU161MRB U30 / HU163MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C		
[°C DB]	Capacity (kW)									
-25	10.98	10.00	9.50	9.33	-	-	-	-		
-20	13.43	12.54	12.03	11.78	11.47	-	-	-		
-15	14.23	14.39	14.50	13.95	13.86	13.12	-	-		
-7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	-		
-4	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
-2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
10	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

THERMA V_m (R22) Hydrosplit

Performance Table for Cooling Operation

Maximum cooling capacity

HU121MRB U30 / HU123MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00
20	12.00	12.00	12.00	12.00	12,00	12.00	12.00
30	12.00	12.00	12.00	12.00	12,00	12.00	12.00
35	12.00	12.00	12.00	12.00	12,00	12.00	12.00
40	11.75	12.00	12.00	12.00	12,00	12.00	12.00
45	11.50	12.00	12.00	12.00	12.00	12.00	12.00

HU141MRB U30 / HU143MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C			
[°C DB]		Capacity (kW)								
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
30	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
40	13.75	14.00	14.00	14.00	14.00	14.00	14.00			
45	13.50	14.00	14.00	14.00	14.00	14.00	14.00			

HU161MRB U30 / HU163MRB U30 + HN1600MC NK1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C				
[°C DB]		Capacity (kW)									
10	16.00	16.00	16.00	16.00	16.00	16.00	16.00				
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00				
30	16.00	16.00	16.00	16.00	16.00	16.00	16.00				
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00				
40	15.75	16.00	16.00	16.00	16.00	16.00	16.00				
45	15.50	16.00	16.00	16.00	16.00	16.00	16.00				

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ /min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- * Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- ${\it 4.} \ {\it The shaded areas are not guaranteed continuous operation}.$


[Unit: mm]

THERMA V R32 HYDROSPLIT HYDRO UNIT

THERMA V_m (R32) Hydrosplit

Drawings

HU121MRB U30 / HU123MRB U30 HU141MRB U30 / HU143MRB U30 HU161MRB U30 / HU163MRB U30





Top view



[Unit: mm]

3D view






Bottom view

No.	Part Name	Description				
1	Entering Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
2	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
3	Unit Power	Power Cable Hole				
4	Low Voltage	Communication Cable Hole				
5	Handle	-				
6	Air Outlet	-				
7	Side Panel	-				

External


HN1600MC NK1



No.	Part Name	Description					
1	Control Panel	Built-in Remote Controller					

Internal

HN1600MC NK1



No.	Part Name	Description				
1	Heating Circuit Outlet Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
2	Heating Circuit Inlet Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
3	Outlet Pipe to Outdoor Unit	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
4	Inlet Pipe to Outdoor Unit	Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
5	Water Pump	To Circulate Water Inside the System				
6	Control Box	PCB and Terminal Blocks				
7	Pressure Sensor	To Measure the Water Pressure (0-2MPa)				
8	Expansion Tank	8 Liter, 3/4" Connection				
9	Flow Sensor	To Measure the Water Flow Rate (5-80 LPM)				
10	Safety Valve Open at Water Pressure 3 Bar					




THERMA V_{TM} (R32) Hydrosplit **COMBIUNIT**



Key Features

- Capacity range from 12 to 16 kW for renovation and large
- No need for F-gas license and simple installation due to no refrigerant piping work
- Operation range down to -25°C
- Maximum flow temperature up to 65°C
- All-in-one Combi Unit with integrated hot water cylinder



Perfect Space-Saving Solution

THERMA V R32 Hydrosplit Combi Unit combines an indoor unit, a water tank and complex piping into a single, space-saving solution that is able to provide space heating, cooling and DHW supply.

Since there is no need to install a separate domestic hot water tank for hot water supply, space is not wasted, and the concept with all-in-one enables quick installation.

Also, it has good installability and maintainability because the indoor unit is located indoors, for example in a machine room.

Application







Certifications









Energy Label











THERMA V R32 HYDROSPLIT **COMBIUNIT**

Outdoor unit

HU121MRB U30 / HU123MRB U30 HU141MRB U30 / HU143MRB U30 HU161MRB U30 / HU163MRB U30

Indoor unit

HN1616Y NB1

















Key Components

Combi Unit



Components

- 1 DHW storage tank (200 l)
- 2 Main water pump
- 3 Water pump for DHW charging
- 4 Plate heat exchanger for DHW (water / DHW)
- 5 Electric heater (max. 6 kW)
- 6 3-way diverting valve
- Texpansion vessel for heating (12 l)
- 8 Flow sensor
- Water pressure sensor
- (D) Expansion vessel for DHW (8 l, option)
- 1 Buffer tank (40 l, option)
- 2 Standard III remote controller 1) (attached on the front panel)

Connections

- A Inlet pipe from outdoor unit (female G1")
- B Outlet pipe to outdoor unit (female G1")
- O Domestic hot water outlet pipe (female G3/4")
- Domestic cold water outlet pipe (female G3/4")
- **■** DHW recirculation pipe (female G3/4")
- (Female G1")
- G Heating circuit outlet pipe (female G1")



Product Specification

Efficiency Data		Unit	12 kW (1 Ø) 12 kW (3 Ø)	14 kW (1 Ø) 14 kW (3 Ø)	16 kW (1 Ø) 16 kW (3 Ø)	
Seasonal space heating eff. class (35°C / 55	o°C)	-	A+++ / A++	A+++ / A++	A+++ / A++	
Seasonal space heating efficiency (η_s) (35°C	: / 55°C)	%	181 / 137	180 / 136	179 / 135	
SCOP (35°C / 55°C)		-	4.60 / 3.50	4.57 / 3.47	4.55 / 3.45	
Declared load profile, average climate		-	L	L	L	
Water heating efficiency (η_{WH}), average clim	ate	%	120	120	120	
COP _{DHW} , average climate		-	2.74	2.74	2.74	
Water heating eff. class, average climate		-	A+	A+	A+	
Annual energy consumption, DHW (average	climate)	kWh	850	850	850	
Heating up time acc. to EN 16147 (average of	climate)	h/mm	1h 25	1h 25	1h 25	
Max. usable water volume acc. to EN 16147	(average climate)	l	222	222	222	
Declared load profile, warmer climate			L	L	L	
Water heating efficiency (η _{WH}), warmer climate			151	151	151	
COP _{DHW} , warmer climate			3.43	3.43	3.43	
Water heating eff. class, warmer climate			A++	A++	A++	
Declared load profile, colder climate		-	L	L	L	
Water heating efficiency (η_{WH}), colder climat	te .	%	101	101	101	
COP _{DHW} , colder climate		-	2.34	2.34	2.34	
Water heating eff. class, colder climate		-	А	А	А	
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	61 / 60	62 / 60	63 / 60	
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	39 / 38	40 / 38	41 / 38	
Sound power level (indoor unit)	Rated	dB(A)	43			
Sound pressure level at 1m (indoor unit)	Rated	dB(A)		35		
Nominal Capacity and COP/EER						
Air +7°C / water +35°C	Heating capacity / COP	kW / -	12.00 / 5.04	14.00 / 4.89	16.00 / 4.80	
Air +2°C / water +35°C	Heating capacity / COP	kW / -	11.00 / 3.65	12.00 / 3.63	13.80 / 3.60	
Air +7°C / water +55°C	Heating capacity / COP	kW / -	11.00 / 2.90	11.50 / 2.85	12.00 / 2.80	
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	12.00 / 4.75	14.00 / 4.30	16.00 / 4.00	
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	12.00 / 2.70	14.00 / 2.60	16.00 / 2.50	

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

¹⁾ Temperature control class (ERP class): V

THERMA V R32 HYDROSPLIT COMBI UNIT

Product Specification

Outdoor Units		Unit	HU121MRB U30 HU123MRB U30	HU141MRB U30 HU143MRB U30	HU161MRB U30 HU163MRB U30		
Operation range	Heating & DHW (Min. ~ Max.)	°C		-25 ~ 35			
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 48			
	Туре	-		R32			
Refrigerant	GWP	-		675			
	Precharged amount	g		2,100			
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" acc	cording to ISO 7-1 (tapered	d pipe threads)		
Dimension	HxWxD	mm		1,380 x 950 x 330			
Weight	Net	kg		91.7			
Exterior	Color of chassis / RAL code	-		Warm gray / RAL 7044			
	Voltage, phase, frequency	V, Ø, Hz	220	- 240, 1, 50 / 380 - 415, 3	3, 50		
Power supply	Standby power consumption	W		60			
	Recommended circuit breaker	А	40 / 16				
Indoor Units		Unit		HN1616Y NB1			
	Heating (Min. ~ Max.)	°C	15 ~ 65				
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27				
(leaving water temperature)	DHW (Min. ~ Max.)	°C	15 ~ 80				
	Volume	Q.	200				
Domestic hot water tank	Tank material	-	Enameled steel				
	Standby losses	-	61				
Expansion vessel (heating circuit)	Volume	l	12				
	Capacity combination	kW	2.0	0 / 2.0 + 2.0 / 2.0 + 2.0 +	2.0		
Electric heater	Heating steps	Steps		1			
(Case 1 / Case 2 / Case 3)	Power supply	V, Ø, Hz	220 - 240, 1,	50 / 220 - 240, 1, 50 / 38	0 - 415, 3, 50		
	Rated running current	А		8.7 / 17.4 / 8.7			
	Outlet to outdoor unit	inch					
	Inlet from outdoor unit	inch	Female G1" acc	ording to ISO228-1 (parall	el nine threads)		
Piping connections (water)	Outlet to heat load	inch	. Smale G1 dec	g to 100220 1 (parati	F-he endas)		
	Inlet from heat load	inch					
	Inlet / outlet diameter for DHW	inch	Female G3/4" according to ISO228-1 (parallel pip		llel pipe threads)		
Recirculation		inch					
Dimension	HxWxD	mm	1,812 x 601 x 685				
Weight	Net	kg	130.0				
Exterior	Color / RAL code	-		White / RAL 9002			

lote

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes, Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- $4. \ Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.\\$
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80°C Operating is available only when the booster heater is operating.

Accessory Parts (Optional Accessory)

Buffer Tank for Space Heating



A standard 40 ℓ buffer tank for can be installed as an optional accessory for space heating. Fitting seamlessly into the main casing, it can be attached to the backside of the indoor unit.

THERMA V_m (R22) Hydrosplit

Electrical Specification		Unit	OSHB-40KT AEU
Water volume		l	40
Dimensions (H x W x D)		mm	518 x 560 x 175
Weight (w/o water) Product		kg	24

^{*} The buffer tank for space heating should be purchased and installed separately.

Expansion Vessel for DHW



A standard 8 ℓ DHW expansion vessel, that conveniently fits inside the indoor unit, can be installed as an optional accessory. It is provided with an accessory kit that includes a flexible connection tube.

Electrical Specification		Unit	OSHE-12KT AEU		
Water volume		l	8		
Connection		inch	3/4		
Max. pressure		bar	10		
Pre-charge	Pre-charge		3		
Dimensions (H x W x D)		mm	416 x 238 x 502		
Weight (w/o water) Product		kg	2.5		

 $[\]ensuremath{^{\star}}$ The expansion vessel for DHW should be purchased and installed separately.

Supplied Parts

Shut-off Valve



Shut-off Valve with Strainer



Strainer



Technical Specification		Unit	Details
Material	Body	-	Brass
Material	Mesh	-	Stainless steel (STS304)
Mach	Mesh no.	-	30
Mesh	Max. particle size	mm	0.6
Piping connection		-	Female G1" according to ISO 228-1

^{*} The strainer and valves are supplied with the product, but it need to be installed separately.

^{*} This strainer should be installed at the inlet connection of the outdoor unit to protect the clogging of a plate heat exchanger.

THERMA V R32 HYDROSPLIT **COMBIUNIT**

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU121MRB U30 / HU123MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C		
[°C DB]	Capacity (kW)									
-25	9.66	8.85	8.42	8.29	-	-	-	-		
-20	10.13	10.00	9.88	9.75	9.63	-	-	-		
-15	11.50	11.50	11.50	11.50	11.50	11.50	-	-		
-7	12.00	12.00	12,00	12,00	12.00	12.00	12.00	-		
-4	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00		
-2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00		
2	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00		
7	12.00	12.00	12,00	12,00	12.00	12.00	12.00	12.00		
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00		
15	12.00	12.00	12,00	12,00	12.00	12.00	12.00	12.00		
18	12.00	12.00	12,00	12,00	12,00	12.00	12.00	12.00		
20	12.00	12.00	12,00	12,00	12.00	12.00	12.00	12.00		
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00	12.00		

HU141MRB U30 / HU143MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C			
[°C DB]		Capacity (kW)									
-25	10.04	9.21	8.76	8.62	-	-	-	-			
-20	11.82	11,25	10.95	10.67	10.59	-	-	-			
-15	12.52	12.90	13.26	12,88	12,81	12.63	-	-			
-7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	-			
-4	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
-2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
2	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
7	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
15	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
18	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00	14.00			

HU161MRB U30 / HU163MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C		
[°C DB]		Capacity (kW)								
-25	10.98	10.00	9.50	9.33	-	-	-	-		
-20	13.43	12.54	12.03	11.78	11.47	-	-	-		
-15	14.23	14.39	14.50	13.95	13.86	13.12	-	-		
-7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	-		
-4	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
-2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
2	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
7	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
10	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
15	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
18	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00	16.00		

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

THERMA V_m (R22) Hydrosplit

Performance Table for Cooling Operation

Maximum cooling capacity

HU121MRB U30 / HU123MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]							
10	12.00	12.00	12.00	12.00	12.00	12.00	12.00
20	12.00	12.00	12.00	12.00	12,00	12.00	12.00
30	12.00	12.00	12.00	12.00	12,00	12.00	12.00
35	12.00	12.00	12.00	12.00	12.00	12.00	12.00
40	11.75	12.00	12,00	12.00	12.00	12.00	12.00
45	11.50	12.00	12.00	12.00	12.00	12.00	12.00

HU141MRB U30 / HU143MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C	
[°C DB]			Capacity (kW)					
10	14.00	14.00	14.00	14.00	14.00	14.00	14.00	
20	14.00	14.00	14.00	14.00	14.00	14.00	14.00	
30	14.00	14.00	14.00	14.00	14.00	14.00	14.00	
35	14.00	14.00	14.00	14.00	14.00	14.00	14.00	
40	13.75	14.00	14.00	14.00	14.00	14.00	14.00	
45	13.50	14.00	14.00	14.00	14.00	14.00	14.00	

HU161MRB U30 / HU163MRB U30 + HN1616Y NB1

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	16.00	16.00	16.00	16.00	16.00	16.00	16.00
20	16.00	16.00	16.00	16.00	16.00	16.00	16.00
30	16.00	16.00	16.00	16.00	16.00	16.00	16.00
35	16.00	16.00	16.00	16.00	16.00	16.00	16.00
40	15.75	16.00	16.00	16.00	16.00	16.00	16.00
45	15.50	16.00	16.00	16.00	16.00	16.00	16.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ /min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- * Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- ${\it 4.} \ {\it The shaded areas are not guaranteed continuous operation}.$


[Unit: mm]

THERMA V R32 HYDROSPLIT COMBI UNIT

THERMA V_m (32) Hydrosplit

Drawings

HU121MRB U30 / HU123MRB U30 HU141MRB U30 / HU143MRB U30 HU161MRB U30 / HU163MRB U30





Top view



[Unit: mm]

3D view






Bottom view

No.	Part Name	Description			
1	Entering Water Pipe Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
2	Leaving Water Pipe Male PT 1" according to ISO 7-1 (Tapered pipe threads)				
3	Unit Power	Power Cable Hole			
4	Low Voltage	Communication Cable Hole			
5	Handle	-			
6	Air Outlet	-			
7	Side Panel	-			






Top view


BDG

551 Front view

9 3 3



17 10 10 10



3D view

Back view Right side view

140.	I di c ivalile	Description	140.	I di L'Ivaille	Description
1	Domestic Hot Water Tank	Domestic Hot Water Tank (200L)	А	Inlet Pipe from Outdoor Unit	Female G1"
2	Electric Heater	200 ℓ	В	Outlet Pipe to Outdoor Unit	Female G1"
3	Flow Sensor	Max. 6 kW	С	Domestic Hot Water Outlet Pipe	Female G3/4"
4	3 Way Valve	To Measure the Water Flow Rate (5-80 LPM)	D	Domestic Cold Water Inlet Pipe	Female G3/4"
5	Water Pressure Sensor	Heating / DHW Circuit	Е	Domestic Re-circulation Pipe	Female G3/4"
6	Expansion Vessel	To Measure the Water Pressure (0-2 MPa)	F	Heating Circuit Outlet Pipe	Female G1"
7	Magnesium Anode	12 ℓ for Heating Circuit	G	Heating Circuit Inlet Pipe	Female G1"
8	DHW Tank Sensor	To Prevent Corrosion	Н	Electrical Conduits	For electric wiring
9	Plate Heat Exchanger	Temperature Sensor	I	Control Panel	Built-in remote controller
10	DHW Charging Pump	Heat Exchange (Water / DHW tank)			
11	Strainer for DHW Tank	To Circulate Water for DHW Heating			
12	Main Water Pump	Filtering and Stacking Particles			
13	Expansion Vessel	To Circulate Water Inside the System			
14	Control Box	8 l For DHW Circuit (Accessory)			
15	Air Vent	Air Purging when Charging Water			
16	Drain Cock	Valve for Water Draining			
17	Electrical Conduits	For Electric Wiring			



What is R32 Split

The LG THERMA V Split series is a heat pump that is easy, flexible to install. As the expression "split" suggests, the outdoor and indoor units are connected by refrigerant piping, thus freezing will not compromise this unit regardless of outdoor ambient temperatures.

Key Features

- Capacity range from 4 and 6 kW for new build and 5 to 9 kW for new build or small renovation
- ErP Energy Labeling A+++ / A++ for space heating (Average Climate 35°C / 55°C LWT)
- Maximum flow temperature up to 55°C (4/6 kW) and 65°C (5/7/9 kW)
- Operation range down to -20°C (4/6 kW) and -25°C (5/7/9 kW)

4/6 kW











5/7/9 kW











Product Range

DI	Capacity	Indoo	Outdoor Unit		
Phase	(kW)	Hydro Unit	Combi Unit	Outdoor Unit	
	4 HN0613M NK5 HN0613T NK0 -	HU041MR U20			
	6	HINU613MLINK5	HNU6131 NKU -	HU061MR U20	
1Ø	5			HU051MR U44	
	7	HN091MR NK5		HU071MR U44	
	9			HU091MR U44	

HIGHLIGHT OF R32 SPLIT

THERMA V. (32) Split

Browse now Q

No Potential Risk of Piping Freezing

- Robust to cold ambient thanks to refrigerant piping
- \bullet No exposed piping freezing even during prolonged blackouts



High Installation Flexibility Not Restricted by the Site Condition

- Light weight and compact size
- Allows a maximum refrigerant pipe length of 50 m and offers 3-way piping connection availability (R32 Split 5/7/9 kW Split)
- Eliminates minimum floor area requirements due to R32 refrigerant (R32 Split 4/6 kW)



Small Refrigerant Amount


ONLY 4 / 6 kW

Free from Minimum Floor Area Requirements Due to R32 Refrigerant

Minimum floor space requirements do not apply to R32 Split 4/6 kW, as the maximum refrigerant amount (including 30 m pipes) used in the product is smaller than the minimum set by regulation. As a result, there are more opportunities for flexible design and installation.









All-in-one Integration (Combi Unit)

THERMA V R32 Split Combi Unit is the perfect space-saving solution for residential application thanks to its fully integrated hot water tank. Unlike in the case of typical separate installation, in this all-in-one solution hydronic components and Domestic Hot Water (DHW) are pre-wired, which requires reduced installation time and saves valuable living space. THERMA V R32 Split Combi Unit is easy to set up and operate while it demonstrates outstanding reliability and efficiency.







LG THERMA V R32 Split Combi Unit (less installation space required)

Easy Draining System

It is convenient for maintenance or moving as the water inside can be easily drained through the built-in drain valve.







DHW Recirculation Pump Control

THERMA V can be connected to the DHW recirculation pump, which can then be managed via the scheduling function. When a user opens the faucet, hot water is immediately accessible thanks to the DHW recirculating function. This feature also has the added advantage of preventing Legionella growth in the hot water pipe.





THERMA V_{TM} (R32) Split **HYDRO UNIT**




Effortless Installation, **Cold-Weather** Resistance

THERMA V Split Hydro Unit is a combination of an outdoor unit and an indoor Hydro Unit with built-in hydronic components such as a plate heat exchanger, backup heater, expansion tank and water pump.

Key Features

- Capacity range from 4 and 6 kW for new build and 5 to 9 kW for new build or small renovation
- Maximum flow temperature up to 55°C (4/6 kW) and 65°C (5/7/9 kW)
- Operation range down to -20°C (4/6 kW) and -25°C (5/7/9 kW)
- High level hydronic components integration for fast and clean installation



Application







Certifications







Energy Label







THERMA V_{TM} (R32) Split

THERMA V R32 SPLIT HYDRO UNIT (4/6 kW)

Outdoor unit

HU041MR U20 HU061MR U20

Indoor unit

HN0613M NK5




















Key Components

Hydro Unit



Components

- 1 Standard III remote controller 1) (air temp. sensor integrated)
- Water pump
- 3 Water pressure sensor
- 4 Flow sensor
- **6** Plate type heat exchanger (ref/water)
- 6 Air vent valve
- 7 Expansion vessel (8 l)
- 8 Back up electric heater (3 kW)
- Safety valve
- Strainer

1) Temperature control class (ERP class): V

Connections

- A Heating circuit outlet pipe (male PT 1" *)
- B Heating circuit inlet pipe (male PT 1" *)
- © Refrigerant liquid pipe (SAE 1/4" with connector **)
- D Refrigerant gas pipe (SAE 1/2" with connector **)
- * According to ISO 7-1 (tapered pipe threads)
- ** In case of Split 4/6 kW model, the adaptors provided with the outdoor unit must be separately installed on the gas/liquid connection of the indoor unit when connecting the refrigerant pipe. After installing the adaptors, the liquid and gas connection size becomes Ø 6.35 (1/4 inch) and Ø 12.7 (1/2 inch) respectively.

Product Specification

Efficiency Data		Unit	4 kW (1 Ø)	6 kW (1 Ø)
Seasonal space heating eff. class (35°C / 55	5°C)	-	A+++ / A++	A+++ / A++
Seasonal space heating efficiency (η_s) (35°C	C / 55°C)	%	183 / 126	183 / 126
SCOP (35°C / 55°C)		-	4.65 / 3.23	4.65 / 3.23
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	57 / 56	58 / 57
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	35 / 34	36 / 35
Sound power level (indoor unit)	Rated	dB(A)	4	4
Sound pressure level at 1m (indoor unit)	n (indoor unit) Rated		3	6
Nominal Capacity and COP/EER				
Air +7°C / water +35°C	Heating capacity / COP	kW / -	4.00 / 5.10	6.00 / 4.95
Air +2°C / water +35°C	Heating capacity / COP	kW / -	3.60 / 3.75	4.80 / 3.65
Air -7°C / water +35°C	Heating capacity / COP	kW / -	4.00 / 3.08	6.00 / 2.98
Air +7°C / water +55°C	Heating capacity / COP	kW / -	3.70 / 2.85	4.60 / 2.90
Air -7°C / water +55°C	Heating capacity / COP	kW / -	3.70 / 1.80	4.60 / 1.80
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	4.00 / 4.80	6.00 / 4.80
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	4.00 / 3.40	6.00 / 3.20
Outdoor Units		Unit	HU041MR U20	HU061MR U20
Operation range	Heating & DHW (Min. ~ Max.)	°C	-20	~ 35
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~	
	Туре	-		32
Refrigerant	GWP	-		75
	Precharged amount	g	1,1	00
	Gas / Liquid	mm(inch)	Ø 12.7 (1/2) /	/ Ø 6.35 (1/4)
Piping connections (water)	Length standard / Max.	m	5 /	
	Level difference Max.	m	30	
Piping connections (water)	Max. length	m	1	0
	without additional charge	111		
	Mass of additional ref. charge	g/m		0
Dimension	HxWxD	mm	650 x 87	
Weight	Net	kg	44	
Exterior	Color of chassis / RAL code	-	Warm gray	
	Voltage, phase, frequency	V, Ø, Hz	220 - 24	
Power supply	Standby power consumption	W		0
	Recommended circuit breaker	А	16	20
Indoor Units		Unit	HN0613	3M NK5
0	Heating (Min. ~ Max.)	°C	15 ~	- 55
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~	27
	DHW (Min. ~ Max.)	°C	15 ~	- 80
Expansion vessel (heating circuit)	Volume	l	3	3
	Capacity combination	kW	1.5 +	+ 1.5
Backup heater	Heating steps	Steps	2	2
action fielder	Power supply	V, Ø, Hz	220 - 24	40, 1, 50
	Rated running current	А	13	
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" according to ISO	7-1 (tapered pipe threads)
Piping connections (ref.)	Gas / Liquid	mm(inch)	Ø 12.7 (1/2) /	′ Ø 6.35 (1/4)
Dimension	H x W x D	mm	850 x 49	90 x 315
Weight	Net	kg	37	7.8
Exterior	Color / RAL code	-	Noble white	/ RAL 9016

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825,
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- $6. \ All \ installation \ sites \ must \ be \ equipped \ with \ an \ earth \ leakage \ circuit \ breaker \ (ELCB).$
- 7. DHW 50 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

THERMA V R32 SPLIT HYDRO UNIT (4/6kW)

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU041MR U20 + HN0613M NK5

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C			
[°C DB]	Capacity (kW)								
-20	4.00	4.00	4.00	4.00	-	-			
-15	4.00	4.00	4.00	4.00	4.00	-			
-7	4.00	4.00	4.00	4.00	4.00	4.00			
-4	4.00	4.00	4.00	4.00	4.00	4.00			
-2	4.00	4.00	4.00	4.00	4.00	4.00			
2	4.00	4.00	4.00	4.00	4.00	4.00			
7	4.00	4.00	4.00	4.00	4.00	4.00			
10	4.00	4.00	4.00	4.00	4.00	4.00			
15	4.00	4.00	4.00	4.00	4.00	4.00			
18	4.00	4.00	4.00	4.00	4.00	4.00			
20	4.00	4.00	4.00	4.00	4.00	4.00			
35	4.00	4.00	4.00	4.00	4.00	4.00			

HU061MR U20 + HN0613M NK5

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C				
[°C DB]		Capacity (kW)								
-20	4.92	4.78	4.64	4.50	-	-				
-15	5.56	5.52	5.48	5.44	5.40	-				
-7	6.00	6.00	6.00	6.00	6.00	6.00				
-4	6.00	6.00	6.00	6.00	6.00	6.00				
-2	6.00	6.00	6.00	6.00	6.00	6.00				
2	6.00	6.00	6.00	6.00	6.00	6.00				
7	6.00	6.00	6.00	6.00	6.00	6.00				
10	6.00	6.00	6.00	6.00	6.00	6.00				
15	6.00	6.00	6.00	6.00	6.00	6.00				
18	6.00	6.00	6.00	6.00	6.00	6.00				
20	6.00	6.00	6.00	6.00	6.00	6.00				
35	6.00	6.00	6.00	6.00	6.00	6.00				

142

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ/\min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

THERMA V. (822) Split

Performance Table for Cooling Operation

Maximum cooling capacity

HU041MR U20 + HN0613M NK5

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	4.00	4.00	4.00	4.00	4.00	4.00	4.00
20	4.00	4.00	4.00	4.00	4.00	4.00	4.00
30	4.00	4.00	4.00	4.00	4.00	4.00	4.00
35	4.00	4.00	4.00	4.00	4.00	4.00	4.00
40	4.00	4.00	4.00	4.00	4.00	4.00	4.00
45	4.00	4.00	4.00	4.00	4.00	4.00	4.00

HU061MR U20 + HN0613M NK5


Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	6.00	6.00	6.00	6.00	6.00	6.00	6.00
20	6.00	6.00	6.00	6.00	6.00	6.00	6.00
30	6.00	6.00	6.00	6.00	6.00	6.00	6.00
35	6.00	6.00	6.00	6.00	6.00	6.00	6.00
40	5.74	5.81	5.87	5.91	6.00	6.00	6.00
45	5.48	5.61	5.73	5.81	5.94	6.00	6.00


- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ/min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- * Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.

THERMA V R32 SPLIT HYDRO UNIT (4/6 kW)

Drawings [Unit: mm]


HU041MR U20 / HU061MR U20






Top view

3D view






Bottom view

No.	Part Name	Description
1	Air Outlet	-
2	Control Cover & SVC Valve Cover	-
3	Power and Communication Cable Connection	-
4	Gas Pipe Connection	Flare Joint
5	Liquid Pipe Connection	Flare Joint
6	Handle	-
7	Intake Air Temperature Sensor Cover	-

External HN0613M NK5




THERMA V... (22) Split

No.	Part Name	Description
1	Control Panel	Built-in Remote Controller

Internal

HN0613M NK5



No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
2	Entering Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
3	Refrigerant Piping Connection	Ø 6.35 ¹⁾ (mm)
4	Refrigerant Piping Connection	Ø 12.7 ¹⁾ (mm)
5	Water Pump	To Circulate Water Inside the System
6	Safety Valve	Open at Water Pressure 3 Bar
7	Control Box	PCB and Terminal Blocks
8	Thermostat	Cut-off Power Input to Electric Heater at 90°C
9	Flow Sensor	To Measure the Water Flow Rate (5-80 LPM)
10	Plate Heat Exchanger	Heat Exchange between Refrigerant and Water
11	Pressure Sensor	To Measure the Water Pressure (0-2 MPa)
12	Expansion Tank	Absorbing Volume Change of Heated Water
13	Air Vent	Air Purging when Charging Water
14	Backup Heater	3 kW
15	Strainer	Filtering and Stacking Particles Inside Circulating Water

¹⁾ When connecting the refrigerant pipe, the adaptors provided with the outdoor unit must be installed on the connection of the indoor unit.

THERMA V_m Split

THERMA V R32 SPLIT HYDRO UNIT (5/7/9kW)

Outdoor unit

HU051MR U44 HU071MR U44

HU091MR U44

Indoor unit

HN091MR NK5






















Hydro Unit



Components

- 1 Standard III remote controller 1) (air temp. sensor integrated)
- Water pump
- 3 Water pressure sensor
- 4 Flow sensor
- **5** Plate type heat exchanger (ref/water)
- 6 Air vent valve
- 7 Expansion vessel (8 l)
- 8 Back up electric heater (3 kW)
- Safety valve
- Strainer

1) Temperature control class (ERP class): V

Connections

- A Heating circuit outlet pipe (male PT 1" *)
- B Heating circuit inlet pipe (male PT 1" *)
- © Refrigerant liquid pipe (SAE 3/8")
- Refrigerant gas pipe (SAE 5/8")

Product Specification

Efficiency Data		Unit	5 kW (1 Ø)	7 kW (1 Ø)	9 kW (1 Ø)		
Seasonal space heating eff. class (35°C / 55	5°C)	-	A+++ / A++	A+++ / A++	A+++ / A++		
Seasonal space heating efficiency (η _s) (35°C	C / 55°C)	%	183 / 126	183 / 126	183 / 126		
SCOP (35°C / 55°C)		-	4.65 / 3.23	4.65 / 3.23	4.65 / 3.23		
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)		60 / 58			
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)		38 / 36			
Sound power level (indoor unit)	Rated	dB(A)		44			
Sound pressure level at 1m (indoor unit)	Rated	dB(A)		36			
Nominal Capacity and COP/EER							
Air +7°C / water +35°C	Heating capacity / COP	kW / -	5.50 / 4.90	7.00 / 4.90	9.00 / 4.65		
Air +2°C / water +35°C	Heating capacity / COP	kW / -	3.30 / 3.52	4.20 / 3.51	5.40 / 3.50		
Air +7°C / water +55°C	Heating capacity / COP	kW / -	5.50 / 2.70	5.50 / 2.70	5.50 / 2.70		
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.50 / 4.60	7.00 / 4.50	9.00 / 4.20		
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.50 / 2.80	7.00 / 2.70	9.00 / 2.60		
Outdoor Units		Unit	HU051MR U44	HU071MR U44	HU091MR U44		
Operation range	Heating & DHW (Min. ~ Max.)	°C		-25 ~ 35			
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 48			
	Туре	-		R32			
Refrigerant	GWP	-	675				
	Precharged amount	g	1,500				
	Gas / Liquid	mm(inch)	Ø 12.7 (5/8) / Ø 9.52 (3/8)				
	Length standard / Max.	m		5 / 50			
Dining connections (water)	Level difference Max.	m		30			
Piping connections (water)	Max. length without additional charge	m	10				
	Mass of additional ref. charge	g/m	40				
Dimension	HxWxD	mm		834 x 950 x 330			
Weight	Net	kg		60.0			
Exterior	Color of chassis / RAL code	-		Warm gray / RAL 7044			
	Voltage, phase, frequency	V, Ø, Hz		220 - 240, 1, 50			
Power supply	Standby power consumption	W		20			
	Recommended circuit breaker	А	20	25	30		
Indoor Units		Unit		HN091MR NK5			
	Heating (Min. ~ Max.)	°C		15 ~ 65			
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 27			
(leaving water temperature)	DHW (Min. ~ Max.)	°C		15 ~ 80			
Expansion vessel (heating circuit)	Volume	l		8			
	Capacity combination	kW		3.0 + 3.0			
Darleys harden	Heating steps	Steps		2			
Backup heater	Power supply	V, Ø, Hz		220 - 240, 1, 50			
	Rated running current	А	25.0				
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1" acc	ording to ISO 7-1 (tapered	pipe threads)		
Piping connections (ref.)	Gas / Liquid	mm(inch)	Ø	15.88 (5/8) / Ø 9.52 (3/8	3)		
Dimension	HxWxD	mm		850 x 490 x 315			
Weight	Net	kg		38.1			
Exterior	Color / RAL code	-		Noble white / RAL 9016			

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825,
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

^{*} According to ISO 7-1 (tapered pipe threads)

THERMA V_m (R22) Split

THERMA V R32 SPLIT HYDRO UNIT (5/7/9kW)

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU051MR U44 + HN091MR NK5

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]	[°C DB] Capacity (kW)							
-25	4.02	3.90	3.78	3.66	-	-	-	-
-20	4.64	4.51	4.38	4.26	4.13	-	-	-
-15	5.26	5.12	4.99	4.85	4.72	4.58	-	-
-7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-4	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
10	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
15	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
18	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
20	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
35	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50

HU071MR U44 + HN091MR NK5

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]	Capacity (kW)							
-25	5.00	4.85	4.71	4.56	-	-	-	-
-20	5.58	5.43	5.27	5.11	4.95	-	-	-
-15	6.17	6.00	5.83	5.66	5.49	5.32	-	-
-7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00

HU091MR U44 + HN091MR NK5

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]	C DB] Capacity (kW)							
-25	6.40	6.20	6.00	5.80	-	-	-	-
-20	7.23	7.00	6.77	6.54	6.31	-	-	-
-15	8.06	7.80	7.54	7.28	7.02	6.76	-	-
-7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00

Note

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ/\min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.

 Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HU051MR U44 + HN091MR NK5

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]	Capacity (kW)						
10	6.42	6.95	7.49	7.85	8.39	8.75	9.11
20	6.05	6.37	6.70	6.91	7.23	7.45	7.66
30	5.68	5.79	5.90	5.97	6.08	6.15	6.22
35	5.50	5.50	5.50	5.50	5.50	5.50	5.50
40	5.32	5.34	5.35	5.37	5.38	5.40	5.41
45	5.13	5.17	5.21	5.23	5.27	5.29	5.32

HU071MR U44 + HN091MR NK5

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C	
[°C DB]		Capacity (kW)						
10	8.17	8.85	9.54	9.99	10.68	11.13	11.59	
20	7.70	8.11	8.52	8.80	9.21	9.48	9.75	
30	7.23	7.37	7.51	7.60	7.74	7.83	7.92	
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00	
40	6.77	6.79	6.81	6.83	6.85	6.87	6.88	
45	6.53	6.58	6.63	6.66	6.70	6.74	6.77	

HU091MR U44 + HN091MR NK5

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	10.50	11.38	12.26	12.85	13.73	14.31	14.90
20	9.90	10.43	10.96	11.31	11.84	12.19	12.54
30	9.30	9.48	9.65	9.77	9.95	10.06	10.18
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00
40	8.70	8.73	8.76	8.78	8.81	8.83	8.85
45	8.40	8.46	8.52	8.56	8.62	8.66	8.70

lote


- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

THERMA V R32 SPLIT HYDRO UNIT (5/7/9kW)


THERMA V_m (R22) Split


Drawings [Unit: mm] [Unit: mm]


HU051MR U44 / HU071MR U44 / HU091MR U44













Internal front view

Bottom view	Internal top view

No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare Joint
4	Liquid Pipe Connection	Flare Joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-



No.	Part Name	Description
1	Control Panel	Built-in Remote Controller



No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
2	Entering Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
3	Refrigerant Pipe (Liquid)	Ø 9.52 (mm)
4	Refrigerant Pipe (Gas)	Ø 15.88 (mm)
5	Water Pump	To Circulate Water Inside the System
6	Safety Valve	Open at Water Pressure 3 Bar
7	Control Box	PCB and Terminal Blocks
8	Thermal Switch	Cut-off Power Input to Electric Heater at 90°C
9	Flow Sensor	To Measure the Water Flow Rate (5-80 LPM)
10	Plate Heat Exchanger	Heat Exchange between Refrigerant and Water
11	Pressure Sensor	To Measure the Water Pressure (0-2 MPa)
12	Expansion Tank	Absorbing Volume Change of Heated Water
13	Air Vent	Air Purging when Charging Water
14	Backup Heater	6 kW
15	Strainer	Filtering and Stacking Particles Inside Circulating Water



THERMA V_{TM} (R32) Split **COMBIUNIT**




All-in-one Integration

The LG THERMA V R32 Split Combi Unit is a domestic hot water supply, space heating and cooling solution that conveniently combines an indoor hot water tank with a separate outdoor unit.

Since there is no need to install a separate domestic hot water tank for hot water supply, space is not wasted, and the concept with all-in-one enables quick installation.

Key Features

- Capacity range from 4 and 6 kW for new build and 5 to 9 kW for new build or small renovation
- Maximum flow temperature up to 55°C (4/6 kW) and 65°C (5/7/9 kW)
- Operation range down to -20°C (4/6 kW) and -25°C (5/7/9 kW)
- All-in-one Combi Unit with integrated hot water cylinder



Application





Certifications









Energy Label











THERMA V R32 SPLIT COMBI UNIT (4/6 kW)

Outdoor unit

HU041MR U20 HU061MR U20

Indoor unit

HN0613T NK0






















Key Components

Combi Unit



Components

- 1 Plate heat exchanger (ref. / water)
- 3 Expansion tank for heating (8 l)
- 4 Reserved space for DHW expansion tank
- 5 DHW storage tank (stainless steel, 200 l) with internal coil type heat exchanger
- 6 Standard III remote controller 1) (air temp. sensor integrated)
- 7 Air vent valve
- 8 3 Way diverting valve (DC)
- Electric back-up heater (3 kW)
- Water flow sensor
- 1 Main water pump with air vent and safety valve (water circuit, 3 bar)
- Water pressure sensor
- 13 Drain valve for water circuit
- 14 Safety valve (DHW tank, 10 bar)
- 15 Drain valve for DHW tank

1) Temperature control class (ERP class): V

Connections

- A DHW recirculation pipe (female G1" *)
- B Domestic hot water outlet pipe (female G1" *)
- O Domestic cold water inlet pipe (female G1" *)
- D Heating circuit inlet pipe (female G1" *)
- Heating circuit outlet pipe (female G1" *)
- Refrigerant liquid pipe (SAE 1/4" with connector **)
- **G** Refrigerant gas pipe (SAE 1/2" with connector **)
- * According to ISO 228-1 (parallel pipe threads)
- ** In case of Split 4/6 kW model, the adaptors provided with the outdoor unit must be separately installed on the gas/liquid connection of the indoor unit when connecting the refrigerant pipe. After installing the adaptors, the liquid and gas connection size becomes Ø 6.35 (1/4 inch) and Ø 12.7 (1/2 inch) respectively.



Product Specification

Efficiency Data		Unit	4 kW (1 Ø)	6 kW (1 Ø)
Seasonal space heating eff. class (35°C / 55	S°C)	-	A+++ / A++	A+++ / A++
Seasonal space heating efficiency (η_s) (35°C	: / 55°C)	%	183 / 126	183 / 126
SCOP (35°C / 55°C)		-	4.65 / 3.23	4.65 / 3.23
Declared load profile, average climate		-	L	L
Water heating efficiency (η _{WH}), average clim	ate	%	133	133
COP _{DHW} , average climate		-	3.15	3.15
Water heating eff. class, average climate		-	A+	A+
Annual energy consumption, DHW (average	climate)	kWh	770	770
Heating up time acc. to EN 16147 (average	climate)	h/mm	1h 45	1h 45
Max. usable water volume acc. to EN 16147	(average climate)	l	220	220
Declared load profile, warmer climate		-	L	L
Water heating efficiency (η _{WH}), warmer clima	ate	%	160	160
COP _{DHW} , warmer climate		-	3.69	3.69
Water heating eff. class, warmer climate		-	A++	A++
Declared load profile, colder climate		-	L	L
Water heating efficiency (η _{WH}), colder climat	ce	%	110	110
COP _{DHW} , colder climate		-	2.54	2.54
Water heating eff. class, colder climate		-	A	А
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)	57 / 56	58 / 57
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)	35 / 34	36 / 35
Sound power level (indoor unit)	Rated	dB(A)	4	2
Sound pressure level at 1m (indoor unit)	Rated	dB(A)	3	4
Nominal Capacity and COP/EER				
Air +7°C / water +35°C	Heating capacity / COP	kW / -	4.00 / 5.10	6.00 / 4.95
Air +2°C / water +35°C	Heating capacity / COP	kW / -	3.60 / 3.75	4.80 / 3.65
Air -7°C / water +35°C	Heating capacity / COP	kW / -	4.00 / 3.08	6.00 / 2.98
Air +7°C / water +55°C	Heating capacity / COP	kW / -	3.70 / 2.85	4.60 / 2.90
Air -7°C / water +55°C	Heating capacity / COP	kW / -	3.70 / 1.80	4.60 / 1.80
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	4.00 / 4.80	6.00 / 4.80
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	4.00 / 3.40	6.00 / 3.20

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard, Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
- 7. DHW 50 ~ 80°C Operating is available only when the booster heater is operating.

THERMA V_m (R22) Split

THERMA V R32 SPLIT COMBI UNIT (4/6 kW)

Product Specification

Outdoor Units		Unit	HU041MR U20	HU061MR U20
Operation range	Heating & DHW (Min. ~ Max.)	°C	-20 ~ 3	35
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 48	3
	Туре	-	R32	
Refrigerant	GWP	-	675	
	Precharged amount	g	1,100	
	Gas / Liquid	mm(inch)	Ø 12.7 (1/2) / Ø	6.35 (1/4)
	Length standard / Max.		5 / 30)
Piping connections (water)	Level difference Max.		30	
	Max. length without additional charge		10	
	Mass of additional ref. charge		20	
Dimension	HxWxD	mm	650 x 870	x 330
Weight	Net	kg	44.7	
Exterior	Color of chassis / RAL code	-	Warm gray / R	AL 7044
	Voltage, phase, frequency	V, Ø, Hz	220 - 240,	1, 50
Power supply	Standby power consumption	W	20	
	Recommended circuit breaker	А	16	20
Indoor Units		Unit	HN0613T	NK0
	Heating (Min. ~ Max.)	°C	15 ~ 5.	5
Operation range leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27	7
	DHW (Min. ~ Max.)	°C	15 ~ 8	0
	Volume	l	200	
Domestic hot water tank	Tank material	-	Duplex stainle	ess steel
	Standby losses	-	60	
Expansion vessel (heating circuit)	Volume	l	8	
	Capacity combination	kW	3.0	
	Heating steps	Steps	1	
Electric heater	Power supply	V, Ø, Hz	220 - 240,	1, 50
	Rated running current	А	13.0	
	Inlet / outlet diameter for space heating	inch		
Piping connections (water)	Inlet / outlet diameter for DHW	inch	Female G1" according to ISO22	8-1 (parallel pipe threads)
	Recirculation	inch		
Piping connections (ref.)	Gas / Liquid	mm(inch)	Ø 12.7 (1/2) / Ø	6.35 (1/4)
Dimension	HxWxD	mm	1,750 x 600	x 660
Weight	Net	kg	118.0	
Exterior	Color / RAL code	-	White / RAI	9016

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.

 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
 7. DHW 50 ~ 80°C Operating is available only when the booster heater is operating.



THERMA V R32 SPLIT COMBI UNIT (4/6kW)

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU041MR U20 + HN0613T NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C		
[°C DB]			Capaci	Capacity (kW)				
-20	4.00	4.00	4.00	4.00	-	-		
-15	4.00	4.00	4.00	4.00	4.00	-		
-7	4.00	4.00	4.00	4.00	4.00	4.00		
-4	4.00	4.00	4.00	4.00	4.00	4.00		
-2	4.00	4.00	4.00	4.00	4.00	4.00		
2	4.00	4.00	4.00	4.00	4.00	4.00		
7	4.00	4.00	4.00	4.00	4.00	4.00		
10	4.00	4.00	4.00	4.00	4.00	4.00		
15	4.00	4.00	4.00	4.00	4.00	4.00		
18	4.00	4.00	4.00	4.00	4.00	4.00		
20	4.00	4.00	4.00	4.00	4.00	4.00		
35	4.00	4.00	4.00	4.00	4.00	4.00		

HU061MR U20 + HN0613T NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C
[°C DB]			Capaci	ty (kW)		
-20	4.92	4.78	4.64	4.50	-	-
-15	5.56	5.52	5.48	5.44	5.40	-
-7	6.00	6.00	6.00	6.00	6.00	6.00
-4	6.00	6.00	6.00	6.00	6.00	6.00
-2	6.00	6.00	6.00	6.00	6.00	6.00
2	6.00	6.00	6.00	6.00	6.00	6.00
7	6.00	6.00	6.00	6.00	6.00	6.00
10	6.00	6.00	6.00	6.00	6.00	6.00
15	6.00	6.00	6.00	6.00	6.00	6.00
18	6.00	6.00	6.00	6.00	6.00	6.00
20	6.00	6.00	6.00	6.00	6.00	6.00
35	6.00	6.00	6.00	6.00	6.00	6.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (2/min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate. 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

THERMA V. (822) Split

Performance Table for Cooling Operation

Maximum cooling capacity

HU041MR U20 + HN0613T NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	4.00	4.00	4.00	4.00	4.00	4.00	4.00
20	4.00	4.00	4.00	4.00	4.00	4.00	4.00
30	4.00	4.00	4.00	4.00	4.00	4.00	4.00
35	4.00	4.00	4.00	4.00	4.00	4.00	4.00
40	4.00	4.00	4.00	4.00	4.00	4.00	4.00
45	4.00	4.00	4.00	4.00	4.00	4.00	4.00

HU061MR U20 + HN0613T NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	6.00	6.00	6.00	6.00	6.00	6.00	6.00
20	6.00	6.00	6.00	6.00	6.00	6.00	6.00
30	6.00	6.00	6.00	6.00	6.00	6.00	6.00
35	6.00	6.00	6.00	6.00	6.00	6.00	6.00
40	5.74	5.81	5.87	5.91	6.00	6.00	6.00
45	5.48	5.61	5.73	5.81	5.94	6.00	6.00

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C),
- LPM: Liters Per Minute (ℓ /min), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- * Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.


[Unit: mm]

THERMA V R32 SPLIT COMBI UNIT (4/6 kW)


THERMA V_m Split

Drawings [Unit: mm]


HU041MR U20 / HU061MR U20




Top view



3D view






Bottom view

160

No.	Part Name	Description
1	Air Outlet	-
2	Control Cover & SVC Valve Cover	-
3	Power and Communication Cable Connection	-
4	Gas Pipe Connection	Flare Joint
5	Liquid Pipe Connection	Flare Joint
6	Handle	-
7	Intake Air Temperature Sensor Cover	-

External
HN0613T NK0



Bottom view


14

No.	Part Name	Description
1	Refrigerant Gas Pipe	SAE 1/2" 1)
2	Refrigerant Liquid Pipe	SAE 1/4" ¹⁾
3	Heating Circuit Outlet Pipe	
4	Heating Circuit Inlet Pipe	
5	Domestic Cold Water Inlet Pipe	Female G1" according to ISO228-1 (Parallel pipe threads)
6	Domestic Cold Water Outlet Pipe	
7	DHW Re-circulation Pipe	
8	Control Panel	Built-in Remote Controller

Side view

1) When connecting the refrigerant pipe, the adaptors provided with the outdoor unit must be installed on the connection of the indoor units.

Front view



1	Bottom view	Left side view		Front view	Right side view
No.	Part Name	Description	No.	Part Name	Description
1	DHW tank	Domestic Hot Water Tank (200L)	10	Water Pump	Main Circulation Pump
2	Heater	Electric Heater (3 kW)	11	Control Box	PCB'A and Terminal Blocks
3	Flow sensor	Flow Metering Sensor	12	Air Vent	For Air Purging
4	3 Way Valve	For DHW / Heating	13	Drain Cock 1	Valve for DHW Tank Drain
5	Pressure Sensor	Pressure Sensor	14	Drain Cock 2	Valve for Water Circuit Drain
6	Expansion Vessel	8 ℓ for Heating Circuit	15	Strainer	For Water Circuit
7	DHW Tank Sensor	Temperature Sensor	16	Safety Valve	For DHW (10 Bar)
8	Heat Exchanger 1	Coil Heat Exchange (Water / DHW)	17	Safety Valve	For Water Circuit (3 Bar)
9	Heat Exchanger 2	Plate Heat Exchange (Ref. / Water)			

5 Liquid Pipe Connection Flare Joint 7 DHW Tank Sensor Temperature Sensor 16 Safety Valve For DHW (10 Bar)
6 Handle - Coil Heat Exchanger 1 Coil Heat Exchange (Water / DHW) 17 Safety Valve For Water Circuit (3 Bar)
7 Intake Air Temperature Sensor Cover 9 Heat Exchanger 2 Plate Heat Exchange (Ref. / Water)

THERMA V R32 SPLIT COMBI UNIT (5/7/9kW)

Outdoor unit

HU051MR U44

HU071MR U44

HU091MR U44

Indoor unit

HN0913T NK0
























Key Components

Combi Unit



Components

- 1 Plate heat exchanger (ref. / water)
- 2 Strainer
- 3 Expansion tank for heating (8 l)
- 4 Reserved space for DHW expansion tank
- **5** DHW storage tank (stainless steel, 200 ℓ) with internal coil type heat exchanger
- 6 Standard III remote controller 1) (air temp. sensor integrated)
- 7 Air vent valve
- 8 3 Way diverting valve (DC)
- ② Electric back-up heater (3 kW)
- Water flow sensor
- 11 Main water pump with air vent and safety valve (water circuit, 3 bar)
- 12 Water pressure sensor
- 13 Drain valve for water circuit
- 14 Safety valve (DHW tank, 10 bar)
- 15 Drain valve for DHW tank

1) Temperature control class (ERP class): V

Connections

- A DHW recirculation pipe (female G1" *)
- B Domestic hot water outlet pipe (female G1" *)
- O Domestic cold water inlet pipe (female G1" *) D Heating circuit inlet pipe (female G1" *)
- Heating circuit outlet pipe (female G1" *)
- F Refrigerant liquid pipe (SAE 3/8")
- G Refrigerant gas pipe (SAE 5/8")



Product Specification

Efficiency Data		Unit	5 kW (1 Ø)	7 kW (1 Ø)	9 kW (1 Ø)
Seasonal space heating eff. class (35°C / 55	5°C)	-	A+++ / A++	A+++ / A++	A+++ / A++
Seasonal space heating efficiency (η_s) (35°C	: / 55°C)	%	183 / 126	183 / 126	183 / 126
SCOP (35°C / 55°C)		-	4.65 / 3.23	4.65 / 3.23	4.65 / 3.23
Declared load profile, average climate		-	L	L	XL
Water heating efficiency (η_{WH}), average clim	ate	%	133	133	140
COP _{DHW} , average climate		-	3.15	3.15	3.40
Water heating eff. class, average climate		-	A+	A+	A+
Annual energy consumption, DHW (average	climate)	kWh	770	770	1,196
Heating up time acc. to EN 16147 (average	climate)	h/mm	1h 44	1h 44	1h 44
Max. usable water volume acc. to EN 16147	(average climate)	l	250	250	250
Declared load profile, warmer climate		-	L	L	XL
Water heating efficiency (η _{WH}), warmer clima	ate	%	160	160	170
COP _{DHW} , warmer climate		-	3.69	3.69	4.10
Water heating eff. class, warmer climate		-	A++	A++	A++
Declared load profile, colder climate		-	L	L	XL
Water heating efficiency (η _{WH}), colder climat	ce c	%	110	110	115
COP _{DHW} , colder climate		-	2.54	2.54	2.65
Water heating eff. class, colder climate		-	A	А	А
Sound power level (outdoor unit)	Rated / low noise mode	dB(A)		60 / 58	
Sound pressure level at 5m (outdoor unit)	Rated / low noise mode	dB(A)		38 / 36	
Sound power level (indoor unit)	Rated	dB(A)		42	
Sound pressure level at 1m (indoor unit)	Rated	dB(A)		34	
Nominal Capacity and COP/EER					
Air +7°C / water +35°C	Heating capacity / COP	kW / -	5.50 / 4.90	7.00 / 4.90	9.00 / 4.65
Air +2°C / water +35°C	Heating capacity / COP	kW / -	3.30 / 3.52	4.20 / 3.51	5.40 / 3.50
Air +7°C / water +55°C	Heating capacity / COP	kW / -	5.50 / 2.70	5.50 / 2.70	5.50 / 2.70
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	5.50 / 4.60	7.00 / 4.50	9.00 / 4.20
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	5.50 / 2.80	7.00 / 2.70	9.00 / 2.60

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes, Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation. Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- $6. \ All \ installation \ sites \ must \ be \ equipped \ with \ an \ earth \ leakage \ circuit \ breaker \ (ELCB).$
- 7. DHW 55 ~ 80 $^{\circ}\text{C}$ Operating is available only when the booster heater is operating.

^{*} According to ISO 228-1 (parallel pipe threads)

THERMA V_m (R22) Split

THERMA V R32 SPLIT COMBI UNIT (5/7/9kW)

Product Specification

Outdoor Units		Unit	HU051MR U44	HU071MR U44	HU091MR U44	
Operation range	Heating & DHW (Min. ~ Max.)	°C		-25 ~ 35		
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C		5 ~ 48		
	Туре	-		R32		
Refrigerant	GWP	-		675		
	Precharged amount	g		1,500		
	Gas / Liquid	mm(inch)	Ø	15.88 (5/8) / Ø 9.52 (3/8)	
	Length standard / Max.			5 / 50		
Piping connections (water)	Level difference Max.			30		
	Max. length without additional charge			10		
	Mass of additional ref. charge			40		
Dimension	HxWxD	mm		834 x 950 x 330		
Weight	Net	kg		60.0		
Exterior	Color of chassis / RAL code	-		Warm gray / RAL 7044		
	Voltage, phase, frequency	V, Ø, Hz		220 - 240, 1, 50		
Power supply	Standby power consumption	W	20			
	Recommended circuit breaker	А	20	25	30	
Indoor Units		Unit		HN0913T NK0		
	Heating (Min. ~ Max.)	°C		15 ~ 65		
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27			
	DHW (Min. ~ Max.)	°C		15 ~ 80		
	Volume	l		200		
Domestic hot water tank	Tank material	-		Duplex stainless steel		
	Standby losses	-		60		
Expansion vessel (heating circuit)	Volume	l		8		
	Capacity combination	kW		3.0		
Electric heater	Heating steps	Steps		1		
Electric fleater	Power supply	V, Ø, Hz		220 - 240, 1, 50		
	Rated running current	А		13.0		
	Inlet / outlet diameter for space heating	inch				
Piping connections (water)	Inlet / outlet diameter for DHW	inch	Female G1" acco	ording to ISO228-1 (paralle	l pipe threads)	
	Recirculation	inch				
Piping connections (ref.)	Gas / Liquid	mm(inch)	Ø	15.88 (5/8) / Ø 9.52 (3/8)	
Dimension	HxWxD	mm		1,750 x 600 x 660		
Weight	Net	kg		118.0		
Exterior	Color / RAL code	-		White / RAL 9016		

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes, Especially the power cable and circuit breaker should be selected in accordance with that.

 3. Sound power level is measured on the rated condition in accordance with ISO 9614 standard. Sound pressure level is converted from sound power level based on a tonality
- penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation.

 Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB).
 7. DHW 55 ~ 80°C Operating is available only when the booster heater is operating.



THERMA V_m (R22) Split

THERMA V R32 SPLIT COMBI UNIT (5/7/9kW)

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HU051MR U44 + HN0913T NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]		Capacity (kW)						
-25	4.02	3.90	3.78	3.66	-	-	-	-
-20	4.64	4.51	4.38	4.26	4.13	-	-	-
-15	5.26	5.12	4.99	4.85	4.72	4.58	-	-
-7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-4	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
-2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	-
2	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
7	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
10	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
15	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
18	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
20	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50
35	5.50	5.50	5.50	5.50	5.50	5.50	5.50	5.50

HU071MR U44 + HN0913T NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]		Capacity (kW)						
-25	5.00	4.85	4.71	4.56	-	-	-	-
-20	5.58	5.43	5.27	5.11	4.95	-	-	-
-15	6.17	6.00	5.83	5.66	5.49	5.32	-	-
-7	7.00	7.00	7.00	7.00	7.00	7.00	6.49	-
-4	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
-2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	-
2	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
7	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
15	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
18	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00	7.00

HU091MR U44 + HN0913T NK0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C	LWT 65 °C
[°C DB]								
-25	6.40	6.20	6.00	5.80	-	-	-	-
-20	7.23	7.00	6.77	6.54	6.31	-	-	-
-15	8.06	7.80	7.54	7.28	7.02	7.10	-	-
-7	9.00	9.00	9.00	9.00	9.00	9.00	8.60	-
-4	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
-2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	-
2	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
7	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
15	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
18	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00	7.95

Note

166

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM : Liters Per Minute (ℓ/\min), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.

 Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HU051MR U44 + HN0913T NK0

LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
			Capacity (kW)			
5.50	5.50	5.50	5.50	5.50	5.50	5.50
5.50	5.50	5.50	5.50	5.50	5.50	5.50
5.50	5.50	5.50	5.50	5.50	5.50	5.50
5.50	5.50	5.50	5.50	5.50	5.50	5.50
5.32	5.34	5.35	5.37	5.38	5.40	5.41
5.13	5.17	5.21	5.23	5.27	5.29	5.32
	5.50 5.50 5.50 5.50 5.32	5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.32 5.34	5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.32 5.34 5.35 5.35	Capacity (kW) 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.32 5.34 5.35 5.37	Capacity (kW) 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.32 5.34 5.35 5.37 5.38	Capacity (kW) 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.50 5.32 5.34 5.35 5.37 5.38 5.40

HU071MR U44 + HN0913T NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	7.00	7.00	7.00	7.00	7.00	7.00	7.00
20	7.00	7.00	7.00	7.00	7.00	7.00	7.00
30	7.00	7.00	7.00	7.00	7.00	7.00	7.00
35	7.00	7.00	7.00	7.00	7.00	7.00	7.00
40	6.50	6.63	6.81	7.00	7.00	7.00	7.00
45	6.43	6.48	6.63	6.66	6.70	6.74	6.77

HU091MR U44 + HN0913T NK0

Outdoor Temp.	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C
[°C DB]				Capacity (kW)			
10	9.00	9.00	9.00	9.00	9.00	9.00	9.00
20	9.00	9.00	9.00	9.00	9.00	9.00	9.00
30	9.00	9.00	9.00	9.00	9.00	9.00	9.00
35	9.00	9.00	9.00	9.00	9.00	9.00	9.00
40	8.10	8.10	8.70	9.00	9.00	9.00	9.00
45	7.50	7.70	7.80	7.90	8.00	8.10	8.20

Note


- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C),
- LPM: Liters Per Minute (\$\ell/\text{min}\), TC: Total Capacity (kW)

 2. Direct interpolation is permissible. Do not extrapolate.
- Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.


THERMA V R32 SPLIT COMBI UNIT (5/7/9kW)


Drawings [Unit: mm]


HU051MR U44 / HU071MR U44 / HU091MR U44













Internal front view

No.	Part Name	Description
1	Air Outlet	-
2	Power and Communication Cable Hole	-
3	Gas Pipe Connection	Flare Joint
4	Liquid Pipe Connection	Flare Joint
5	Handle	-
6	Pipe Routing Hole (Front)	-
7	Pipe Routing Hole (Side)	-
8	Pipe Routing Hole (Back)	-

Internal top view



No.	Part Name	Description
1	Refrigerant Gas Pipe	SAE 5/8"
2	Refrigerant Liquid Pipe	SAE 5/8"
3	Heating Circuit Outlet Pipe	
4	Heating Circuit Inlet Pipe	
5	Domestic Cold Water Inlet Pipe	Female G1" according to ISO228-1 (Parallel pipe threads)
6	Domestic Cold Water Outlet Pipe	
7	DHW Re-circulation Pipe	
8	Control Panel	Built-in Remote Controller



					9
No.	Part Name	Description	No.	Part Name	Description
1	DHW tank	Domestic Hot Water Tank (200L)	10	Water Pump	Main Circulation Pump
2	Heater	Electric Heater (3 kW)	11	Control Box	PCB'A and Terminal Blocks
3	Flow sensor	Flow Metering Sensor	12	Air Vent	For Air Purging
4	3 Way Valve	For DHW / Heating	13	Drain Cock 1	Valve for DHW Tank Drain
5	Pressure Sensor	Pressure Sensor	14	Drain Cock 2	Valve for Water Circuit Drain
6	Expansion Vessel	8 l for Heating Circuit	15	Strainer	For Water Circuit
7	DHW Tank Sensor	Temperature Sensor	16	Safety Valve	For DHW (10 Bar)
8	Heat Exchanger 1	Coil Heat Exchange (Water / DHW)	17	Safety Valve	For Water Circuit (3 Bar)
9	Heat Exchanger 2	Plate Heat Exchange (Ref. / Water)			



What is Heat Pump Water Heater

A Heat Pump Water Heater (HPWH) is an advanced, energyefficient water heating solution that utilizes heat pump technology to heat water more sustainably than traditional water heaters. A heat pump water heater extracts ambient heat from the air and transfers it to the water, significantly reducing energy consumption and lower utility bills while providing reliable hot water for home.

Ideal for residential applications, these systems offer an ecoconscious alternative to traditional water heating methods, making them a smart choice for sustainable living.

Key Features

- Wide capacity range from 100 to 270 ℓ to suit various household members
- LG's unique design provides harmony in various installation places
- Energy class A+ applies to all models
- Simple installation due to no refrigerant piping work
- · Connect and control anytime, anywhere with LG ThinQ
- Max. water temperature up to 75°C (R290 models only, with heating element)
- Includes SG Ready function (SG Ready models only)







ThinQ

Product Range

	Description		Model Name	Remark
Power 1 Ø, 230 V, 50 Hz	Туре	Volume	Model Name	Remark
		100 l	WH10ESF0 HA	
	Round Type	150 l	WH15ESF0 HA	
		200 l	WH20ESF0 CA	SG Ready model
	Square Type	200 l	WH20STR2 FA	
		270 l	WH27STR2 FA	
		200 l	WH20S F5 "	-
		270 l	WH27S F5	

Browse now Q

Stylish Design

New White Essence Design



HIGHLIGHT OF


HEAT PUMP WATER HEATER

Differentiated Design



High Efficiency Operation






- 2) 100 / 150 ℓ models COP at air temperature 7°C and water temperature 10°C to 54°C with duct.
- 3) 200 / 2701 models COP at air temperature 15°C and water temperature 10°C to 54°C with duct.



Intelligent Energy Management

Smart Living Starts with SG Ready

The Heat Pump Water Heater is operated automatically according to the power supply status signals received from power supplying companies. It is minimizing energy costs and taking a step closer to achieving the ultimate smart home.



* The SG Ready function is only available for models that support SG Ready. (Except the WH**S.F5)



1) COP test conditions are base on EN16147 and EN 12102

5) Profile L: WH15ESF0,HA / WH20ESF0,CA / WH20S,F5 / WH27S,F5 / WH20STR2.FA / WH27STR2.FA

4) Profile M: WH10ESF0.HA

Comfortable Environment


Experience Warmth in Perfect Silence



Since the noise level is below 45 dB(A) 1, it provides a comfortable environment even in indoor installation scenes.

Sound levels	F	ound typ	Square type		
Soulid levels	100 l	150 l	200 l	200 l	270 l
Sound power level [dB(A)] ²⁾	45	45	53	55	55
Sound pressure level [dB(A)] 2) 3)	38	38	38	38	38

Users will hardly recognize the water heater operating, as it runs quietly and creates a calm, peaceful environment.



1) Based on 100 / 1500 model (WH**ESE0 HA)

172

2) Rated sound power / pressure level was measured on the rated condition in accordance with EN 12102-02 and ISO 3741

3) Sound pressure level measured at 2 m away from the unit

Convenience

Smart Control by LG ThinQ

Users can control their THERMA V via smart internet devices such as Android or iOS smartphones. With the LG ThinQ app, users can easily control and monitor the heat pump water heater, checking for current water temperatures, setting operating schedules and more.







Easy to Use

Choose Simple and Quick Comfort Mode

Users can select from four operating modes, allowing for easy customization of the product to effectively meet their individual needs.





Auto mode

Heat pump mode





Turbo mode

Vacation mode





THERMA V_m R290%

HEAT PUMP WATER HEATER (100 / 150 / 200 l)




Fits Perfectly with All Your Needs

The new refrigerant technology allows the unit to efficiently reach outlet temperatures of up to 75°C. Available in sizes ranging from 100 to 200 liters, the unit is developed to meet the capacity needs of each household. Designed with modern living in mind, the R290 Heat Pump Water Heater blends seamlessly into any indoor space.

Key Features

- Capacity range from 100, 150 and 200 l
- New round type design with essence white color
- Natural refrigerant R290 with low GWP (3)
- Connect and control anytime, anywhere with LG ThinQ
- Max. water temperature up to 75 °C with heating element
- Includes SG Ready function



Application



Certifications



Energy Label








THERMA V R290 HEAT PUMP WATER HEATER (100 / 150 £)

WH10ESF0 HA WH15ESF0 HA



Key Components

Heat Pump Water Heater (Wall Mount)



Components

- 1 Duct connector
- 2 Evaporator
- 3 Control box
- 4 Compressor5 Water tank
- 6 ICCP¹⁾ (Ti)
- 7 Anode road (Mg)
- 8 Display
- Electric heater

Connections

- A Water inlet (G 1/2")
- B Water outlet (G 1/2")
- © Pressure relief valve (accessory)
- D Condensate drain (G 3/4")

Product Specification

Indoor Units		Unit	WH10ESF0.HA	WH15ESF0.HA
Capacity	Volume (nominal)	l	100	150
	Туре	-	R2	90
Refrigerant	GWP	-	:	3
	Pre-charged amount	g	14	48
	COP (7°C)	-	2.70	2.95
Efficiency	Energy class (7°C)	-	A+	A+
	Annual energy consumption (7°C)	kWh	438	812
	Operation range	°C	-7 -	- 48
	Max. water temperature with heat pump	°C	6	0
	Max. water temperature with heating element	°C	7	5
	Heating element	kW	1.2	1.2
Performance	Sound power level	dB(A)	45	45
	Sound pressure level at 2 m (Auto mode)	dB(A)	38	38
	V40	l	110	173
	Load profile	-	М	L
	Operation mode	-	Turbo / Auto / Heat pump	/ Vacation / Anti legionella
Compressor	Туре	-	Constant s	peed rotary
Piping connections	Water inlet / outlet	inch	G 1	/2"
Dimension	HxWxD	mm	1,280 x 540 x 565	1,620 x 540 x 565
Weight	Net	kg	64	75
Exterior	Color of chassis / RAL code	-	Essence whit	e / RAL 9003
Safety valve	Туре	-	Pressure i	relief valve
IP Class		-	IP	X4
Anode type		-	Mg +	ICCP ¹⁾
Tank material		-	Enamel	ed steel
	Voltage, phase, frequency	V, Ø, Hz	230, 1, 50	
Power supply	Recommended circuit breaker	А	1	6
A 1 150 - 16 - 11	Wi-Fi (ThinQ)	-	(0
Additional function	SG Ready	-	()

¹⁾ Impressed current cathodic protection


THERMA V R290 HEAT PUMP WATER HEATER (200 £)

WH20ESF0 CA



Key Components

Heat Pump Water Heater (Floor Standing)



Components

- 1 Duct connector
- 2 Evaporator
- 3 Display
- 4 Control box 6 Compressor
- 6 Water tank
- 7 ICCP 1) (Ti)
- 8 Electric heater

Connections

- A Water inlet (G 3/4")
- B Water outlet (G 3/4")
- © T&P relief valve (accessory) O Condensate drain (G 3/4")
- Drain valve (accessory)

Product Specification


Indoor Units		Unit	WH20ESF0.CA
Capacity	Volume (nominal)	l	200
	Туре	-	R290
Refrigerant	GWP	-	3
	Pre-charged amount	g	150
	COP (15°C)	-	3.20
Efficiency	Energy class (15°C)	-	A+
	Annual energy consumption (15°C)	kWh	770
	Operation range	°C	-7 ~ 48
	Max. water temperature with heat pump	°C	60
	Max. water temperature with heating element	°C	75
	Heating element	kW	2.0
Performance	Sound power level	dB(A)	53
	Sound pressure level at 2 m (Auto mode)	dB(A)	38
	V40	l	260
	Load profile	-	L
	Operation mode	-	Turbo / Auto / Heat pump / Vacation / Anti legionella
Compressor	Туре	-	Constant speed rotary
Piping connections	Water inlet / outlet	inch	G 3/4"
Dimension	HxWxD	mm	1,708 x 600 x 608
Weight	Net	kg	92
Exterior	Color of chassis / RAL code	-	Essence white / RAL 9003
Safety valve	Туре	-	T&P relief valve
IP Class		-	IPX1
Anode type		-	ICCP ¹⁾
Tank material		-	Enameled steel
D	Voltage, phase, frequency	V, Ø, Hz	230, 1, 50
Power supply	Recommended circuit breaker	А	16
Additional E	Wi-Fi (ThinQ)	-	0
Additional function	SG Ready	-	0


¹⁾ Impressed current cathodic protection

THERMA V R290 HEAT PUMP WATER HEATER (100 / 150 / 200 l)


Drawings [Unit: mm]

WH10ESF0 HA WH15ESF0 HA WH20ESF0 CA









No.	Part Name	Description		Part Name	Description	
1	Water Tank	200 ℓ	11	Power Cable	1.5 x 3	
2	Front Panel	-	12	Connecting Box Cover	For SG Signal	
3	Heater Cover	-	13	C/Box Case	-	
4	Top Cover	over -		Compressor	WHP01750PSV	
5	T/P Valve (Accessories)	alve (Accessories) 1.0 M Pa, 80°C Open		Motor	30 W	
6	Drain Valve (Accessories)	G 3/4		Fan Propeller	Centrifugal Fan	
7	Dielectric Union (Accessories)	2 EA, Water In & Out	17	ECO	Emergency Cut Off (90°C)	
8	Outlet Pipe	Outlet Pipe Water Out, G 3/4		Heating Element	1 EA, 2,000 W, 230 V	
9	Inlet Pipe	Inlet Pipe Water In, G 3/4		ICCP	Ti	
10	Condensate Drain	Condensate Drain 19 mm		Duct Connector	160 Ø Duct Available	







HEAT PUMP WATER HEATER (200 / 270 l)










Perfect Fit Maximum Efficiency

Featuring a unique and elegant design, the R134a Heat Pump Water Heater is available in two capacity ranges of 200 and 270 l. It features outstanding efficiency and low noise thanks to the dual inverter compressor, and has excellent connectivity and controllability such as SG ready and LG ThinQ.

Key Features

- Capacity range from 200, 270 l
- LG's unique square design with luxury silver color
- High efficiency with dual inverter compressor
- Connect and control anytime, anywhere with LG ThinQ
- Fast hot water production using two heating elements in
- Includes SG Ready function (SG Ready models only)
- Red Dot and iF Design Award Winner in 2020



Application



Certifications





1) WH20S.F5 / WH27S.F5 2) WH20STR2.FA / WH27STR2.FA

Energy Label





THERMA V R134a HEAT PUMP WATER HEATER (200 / 270 £)


WH20STR2 FA¹⁾
WH27STR2 FA¹⁾
WH20S F5
WH27S F5



1) Available SG ready function

Key Components

Heat Pump Water Heater



Components

- 1 Display screen
- 2 Inverter drive
- 3 Water tank
- 4 Electric heaters, 2 x 2 kW
- 5 Fan
- 6 Evaporator
- 7 Dual inverter compressor
- 8 Anode (ICCP 1)
- 9 Ref. piping coil

Connections

- A Water outlet (NPT 3/4")
- B Opening for T&P relief valve
- Water inlet (NPT 3/4")
- Opening for drain valve

Technical Specification

Indoor Units		Unit	WH20STR2 FA WH20S F5 WH27STR2 FA WH27S F5 200 270 R134a 1,430 650 750 3.30 / 3.50 3.45 / 3.85 A+ / A+ A+ / A+ 756 / 709 712 / 646 -5 ~ 48 50		
Capacity	Volume (nominal)	l	200	270	
	Туре	-	R13	34a	
Refrigerant	GWP	-	1,4	30	
	Pre-charged amount	g	650	750	
	COP (7°C / 15°C)	-	3.30 / 3.50	3.45 / 3.85	
Efficiency	Energy class (7°C / 15°C)	-	A+ / A+	A+ / A+	
	Annual energy consumption (7°C / 15°C)	kWh	756 / 709	712 / 646	
	Operation range	°C -5 ~ 48 pump °C 50 ng element °C 60 kW 2.0 + 2.0 3	· 48		
Performance	Max. water temperature with heat pump	°C	5	0	
	Max. water temperature with heating element	°C	6	0	
	Heating element	kW	2.0 + 2.0	2.0 + 2.0	
Performance	Sound power level	dB(A)	55	55	
	Sound pressure level at 2 m (Auto mode)	dB(A)	38	38	
	V40	l	260	360	
	Load profile	-	L	L	
	Operation mode	-	Turbo / Auto / Heat pump / Vacation / Anti legionella		
Compressor	Туре	-	Inverter t	win rotary	
Piping connections	Water inlet / outlet	inch	G 3	/4"	
Dimension	HxWxD	mm	1,625 x 580 x 582	2,008 x 580 x 582	
Weight	Net	kg	102	119	
Exterior	Color of chassis / RAL code	-	Luxury silver	· / RAL 9006	
Safety valve	Туре	-	T&P reli	ef valve	
IP Class		-	IP.	X1	
Anode type		-	ICC	P ¹⁾	
Tank material		-	Enamel	ed steel	
Davis and	Voltage, phase, frequency	V, Ø, Hz	230,	1, 50	
Power supply	Recommended circuit breaker	А	1	5	
	Wi-Fi (ThinQ)	-	()	
Additional function	SG Ready	-	Not supported for WH**S.F5 Supported in WH**STR2.FA		

THERMA V_m (R134a) Heat Pump Water Heater


¹⁾ Impressed current cathodic protection

Accessory Name	Model Name	Figure	Applicable Product	Feature
Duct accessory	PHDCLA0.ELGTEEU		R134a Heat pump water heater	Duct accessories are necessary for duct installation.


THERMA V R134a HEAT PUMP WATER HEATER (200 / 270 l)

Drawings [Unit: mm]


WH20STR2FA WH20SF5




Top view



WH27STR2FA
WH27S F5





NO.	Part Name	Description		Part Name	Description
1	Water Tank	200 ℓ		Wooden Pallet	-
2	Front Panel	-	10	Junction Cover	Power Input
3	Rear Panel	-	11	C/B Case	-
4	Top Cover	-		Compressor	EST092MBA
5	T/P Valve	210 °F / 99 °C 3/4 NPT	13	Motor	43 W
6	Drain Valve	3/4 NPT	14	Fan Propeller	290 Ø
7	Outlet Pipe	Water Out, 3/4 NPT	15	ECO	Emergency Cut Off (77°C)
8	Inlet Pipe	Water In, 3/4 NPT 16		Heating Element	2 EA, 2,000 W+2,000 W, 220 ~ 240 V

No.	Part Name	Description		Part Name	Description	
1	Water Tank	270 ℓ	0ℓ 9 Wooden Pallet		-	
2	Front Panel	-	10	Junction Cover	Power Input	
3	Rear Panel	-	11	C/B Case	-	
4	Top Cover	-	12	Compressor	EST092MBA	
5	T/P Valve	210 °F / 99 °C 3/4 NPT	13	Motor	43 W	
6	Drain Valve	3/4 NPT	14	Fan Propeller	290 Ø	
7	Outlet Pipe	Water Out, 3/4 NPT	15	ECO	Emergency Cut Off (77°C)	
8	Inlet Pipe	Water In, 3/4 NPT	16	Heating Element	2 EA, 2,000 W+2,000 W, 220 ~ 240 V	

SOLUTIONS

COLLECTIVE SOLUTIONS

MONOBLOC

190 R32 Monobloc 51 kW

CASCADE SOLUTION

200 Cascade Control Unit






Compact Yet Powerful

The innovative Collective Solution R32 Monobloc 51 kW delivers efficient performance for large residential spaces with easy installation and inherently safe operation. Compact and lightweight, yet with high capacity and high efficiency, it is ideal for multi-family homes and light commercials.

What is R32 Monobloc 51 kW

The LG R32 Monobloc 51 kW is a large capacity heat pump that provides a collective central heating solution for multi-family houses or light commercial buildings. Ideal for locations that require reliable heating and cooling year-round, this air to water heat pump offers a versatile solution.

Operating efficiently as a single system, it is well-suited for various commercial spaces including multi family house, office buildings, schools and universities.



Key Features

- Fits to Multi-family homes (MFH) or light commercial buildings
- ErP Energy Labeling A++ / A++ for space heating (Average Climate 35°C / 55°C LWT)
- 100% Heating capacity at -10°C outdoor temperature
- Maximum flow temperature up to 60°C
- Operation range down to -25°C
- Compact size and light weight
- Easy installation with no refrigerant piping work
- · Convenient wiring with Control Unit installed indoor
- Enhanced control connectivity aligned with THERMA V lineup













Product Range

Description		Indoor Unit	Outdown Heir
		Control Unit	Outdoor Unit
3 Ø	51 kW	PHCSL0 ENCXLEU	HM513MR UXC0

HIGHLIGHT OF R32 MONOBLOC 51 kW





— Browse now ℚ

Large Capacity THERMA V

Just Simply Install a Large Capacity Heat Pump Instead of Multiple Small Heat Pumps

Installing a high-capacity heat pump system provides efficient and powerful heating while handling high thermal loads. The R32 Monobloc 51 kW ensures centralized heat production, simplify installation, and optimize space utilization. Perfect suitable solution for buildings with high & variable thermal loads (commercial, multi-residential, industrial).

- Well-suited large capacity heat pump for multi family house and various commercial spaces including office buildings, schools and universities
- Centralized solution for both new built and renovation projects
- No refrigerant work require (Plug and play concept)










Excellent Performance

High Energy Efficiency

- High heating efficiency SCOP 4.26 / 3.21 (Low / Mid temp.)
- High cooling efficiency SEER 5.0 (A35 / W7)
- 100% Heating capacity at -10°C outdoor temperature

Achieving the highest ErP energy grade A++ / A++ for space heating





Space Optimization

SCOP

Handy Installation with Small Size and Weight

- Light weight and small size, easy to install
- Ideal for buildings with limited space or where compact installation is required.



Simplified and Centralized Solution

- Easy to design and manage the entire system, with fewer points of failure and simpler hydraulic and electrical connections.
- Easy and cost effective to monitor and maintain with only one unit



THERMA V R32 **MONOBLOC 51 kW**

Outdoor unit

HM513MR UXC0

Indoor unit

PHCSL0 ENCXLEU
























Key Components

Outdoor Unit



Components

- 1 Black Fin heat exchanger (air / ref.)
- 2 Compressor
- 3 Accumulator
- 4 Receiver 6 Biomimetic fan
- 6 Air vent
- 7 Plate heat exchanger
- 8 Flow Switch
- Inlet / Outlet Temp. sensor

Connections

- A Leaving water pipe (male PT 1-1/2")
- B Entering water pipe (male PT 1-1/2")

Indoor Unit (Control Unit)

194



Components

1 Standard III remote controller 1)

1) Temperature control class (ERP class): V

Product Specification

Efficiency Data		Unit	51 kW (3 Ø)
Seasonal space heating eff. class (35°C / 55°C)			A++ / A++
Seasonal space heating efficiency (η _s) (35°C / 55°C)		%	167 / 125
SCOP (35°C / 55°C)		-	4,26 / 3,21
Sound power level	Rated / low noise mode (heating)	dB(A)	82 / 75
Sound pressure level at 10m	Rated / low noise mode (heating)	dB(A)	54 / 47
Nominal Capacity and COP/EER			
Air +7°C / water +35°C	Heating capacity / COP	kW / -	51.0 / 4.30
Air +2°C / water +35°C	Heating capacity / COP	kW / -	51.0 / 3.40
Air -7°C / water +35°C	Heating capacity / COP	kW / -	5.10 / 2.50
Air +7°C / water +55°C	Heating capacity / COP	kW / -	51.0 / 2.80
Air -7°C / water +55°C	Heating capacity / COP	kW / -	40.0 / 1.67
Air +35°C / water +18°C	Cooling capacity / EER	kW / -	51.0 / 4.50
Air +35°C / water +7°C	Cooling capacity / EER	kW / -	51.0 / 3.10
Outdoor Units		Unit	HM513MR UXC0
Operation range	Heating & DHW (Min. ~ Max.)	°C	-25 ~ 35
(outdoor air temperature)	Cooling (Min. ~ Max.)	°C	10 ~ 48
Refrigerant	Туре	-	R32
	GWP	-	675
	Precharged amount	kg	10
Piping connections (water)	Inlet / outlet diameter	inch	Male PT 1-1/2" according to ISO 7-1 (tapered pipe threads)
	Rated water flow rate	LPM	146
Plate heat exchanger	Minimum flow rate (flow switch trigger point)	LPM	100
Dimension	HxWxD	mm	1,690 x 1,640 x 825
Weight	Net	kg	335
Exterior	Color of chassis / RAL code	-	Morning gray & dawn gray / RAL 7038 & RAL 7037
	Voltage, phase, frequency	V, Ø, Hz	380 ~ 415, 3, 50
Power supply	Standby power consumption	W	20
	Recommended circuit breaker	А	50
Indoor Units		Unit	PHCSL0 ENCXLEU
	Heating (Min. ~ Max.)	°C	25 ~ 60 (65) ⁷⁾
Operation range (leaving water temperature)	Cooling (Min. ~ Max.)	°C	5 ~ 27
(couring mater temperature)	DHW (Min. ~ Max.)	°C	25 ~ 80
Dimension	HxWxD	mm	490 x 420 x 141
Weight	Net	kg	6.8
Exterior	Color / RAL code	-	Essence white / RAL 9003
	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50
Power supply	Recommended circuit breaker	А	10

THERMA V_m (R32) Monobloc 51 kW

- 1. Due to our policy of innovation, some specifications may be changed without notification.
- 2. Wiring cable size must comply with the applicable local and national codes, Especially the power cable and circuit breaker should be selected in accordance with that,
- 3. Sound power level is measured on the rated condition in accordance with EN 12102-1 and ISO 9614. Sound pressure level is not a value declared on Eurovent Program and is converted from sound power level based on a tonality penalty of 0 dB and installation in free-field. The directivity index (Q) is assumed as 2. Therefore, these values can be increased owing to ambient conditions during operation, Rated sound power level is in accordance with EN12102-1 under condition of EN14825.
- 4. Performances are in accordance with EN14511 and reflect ErP testing conditions. Above gives the declared values at rated conditions according to ErP regulation.
- 5. This product contains fluorinated greenhouse gases.
- ${\it 6. All installation sites must be equipped with an earth leakage circuit breaker (ELCB)}.$
- 7. The leaving water temperature of 65°C is possible only when a backup heater is installed.

8. DHW 55~80°C Operating is available only when the booster heater is operating.

THERMA V. (R32) Monobloc 51 kW

THERMA V R32 **MONOBLOC 51 kW**

Performance Table for Heating Operation

Maximum heating capacity (including defrost effect)

HM513MR UXC0

Outdoor Temp.	LWT 30 °C	LWT 35 °C	LWT 40 °C	LWT 45 °C	LWT 50 °C	LWT 55 °C	LWT 60 °C
[°C DB]				Capacity (kW)			
-25	30.3	29.3	25.3	19.2	-	-	-
-22	34.0	32.0	27.0	23.0	-	-	-
-20	37.1	36.8	35.3	32.8	29.6	-	-
-17	43.2	42.5	41.8	40.6	39.0	-	-
-15	47.3	46.4	46.1	45.8	45.3	40.0	-
-12	49.5	49.2	47.9	47.8	46.3	41.9	-
-10	51.0	51.0	49.2	49.1	47.0	43.1	36.0
-7	51.0	51.0	51.0	51.0	48.0	45.0	42.0
-2	51.0	51.0	51.0	51.0	51.0	51.0	47.5
2	51.0	51.0	51.0	51.0	51.0	51.0	51.0
7	51.0	51.0	51.0	51.0	51.0	51.0	51.0
10	51.0	51.0	51.0	51.0	51.0	51.0	51,0
15	51.0	51.0	51.0	51.0	51.0	51.0	51.0
20	51.0	51.0	51.0	51.0	51.0	51.0	51,0
25	51.0	51.0	51.0	51.0	51.0	51.0	51,0
30	-	51.0	51.0	51.0	51.0	51.0	51.0
35	-	-	51.0	51.0	51.0	51.0	51.0

196

- 1. DB : Dry Bulb Temperature (°C), LWT : Leaving Water Temperature (°C), LPM : Liters Per Minute (\$\rho(m)\), TC : Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- · Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- 4. The shaded areas are not guaranteed continuous operation.

Performance Table for Cooling Operation

Maximum cooling capacity

HM513MR UXC0


Outdoor Temp.	LWT 5 °C	LWT 7 °C	LWT 10 °C	LWT 13 °C	LWT 15 °C	LWT 18 °C	LWT 20 °C	LWT 22 °C	LWT 27 °C
[°C DB]					Capacity (kW)				
10	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
20	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
30	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
35	48.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0	51.0
40	46.5	48.8	51.0	51.0	51.0	51.0	51.0	51.0	51.0
45	44.0	48.5	50.5	51.0	51.0	51.0	51.0	51.0	51.0
48	42.5	43.8	45.8	48.3	51.0	51.0	51.0	51.0	51.0

- 1. DB: Dry Bulb Temperature (°C), LWT: Leaving Water Temperature (°C), LPM: Liters Per Minute (\$\rho(m)\), TC: Total Capacity (kW)
- 2. Direct interpolation is permissible. Do not extrapolate.
- 3. Measuring procedure follows EN-14511.
- Rated values are based on standard conditions and it can be found on specifications.
- Above table values may not be matched according to installation condition. Except for rated value, the performance is not guaranteed.
- In accordance with the test standard (or nations), the rating will vary slightly.
- ${\it 4.} \ {\it The shaded areas are not guaranteed continuous operation}.$


THERMA V R32 MONOBLOC 51 kW


Drawings [Unit: mm] [Unit: mm]

HM513MR UXC0










Back view


Bottom view


No.	Part Name	Description
1	Entering Water Pipe	Male PT 1-1/2" according to ISO 7-1 (Tapered pipe threads)
2	Leaving Water Pipe	Male PT 1-1/2" according to ISO 7-1 (Tapered pipe threads)
3	Access to Electrical Terminals	Power, Communication cables

1


PHCSL0 ENCXLEU








THERMA V_{III} 822 Monobloc 51 kW




No.	Part Name	Description
1	Remote Controller Assembly	Built-in Remote Controller
2	Panel Assembly.Front	SGMCD1 M08 ESSENCE WHITE PCM
3	Panel Assembly.Indoor	PCB and Terminal Blocks
4	Cover	MOLD ABS



What is Cascade Control Unit

The LG Cascade Control Unit is an advanced heating solution designed to manage up to 8 units of the THERMA V system with a single controller. This centralized control enhances system efficiency and simplifies operation, making it an ideal choice for optimizing heat pump performance in multi-unit applications.



Key Features

- Up to 8 outdoor units 1) can be operated as one system
- Heating demands up to 128 kW can be covered through flexible combination in same capacity models ¹⁾
- Easy to configure as no separate indoor unit or control devices are required except for the cascade control unit
- Extremely quiet and high efficient operation combining with R290 Monobloc over wide heating capacity ranges
- Intuitive interface through a 4.3 inch full-touch / full-color display and motion graphics
- Optimized Runtime Control for stable operation and maintenance
- Alternating defrost operation that Individual units enter into the defrost operation sequentially
- Emergency operation for various emergency situations

Compatible Line-up

•R290 Monobloc 2)

	R290 Monobloc Outdoor Unit					
Description	10	30				
7 kW	HM071HF UB40	HM073HF UB40				
9 kW	HM091HF UB40	HM093HF UB40				
12 kW	HM121HF UB60	HM123HF UB60				
14 kW	HM141HF UB60	HM143HF UB60				
16 kW	HM161HF UB60	HM163HF UB60				

1) All units connected to Cascade Control Unit must be configured with models of the same capacity.
2) Only R290 Monobloc outdoor units manufactured after June of 2025 are compatible

 Only R290 Monobloc outdoor units manufactured after June of 2025 are compatible with Cascade Control Unit.

THERMA V **CASCADE CONTROL UNIT**

Cascade Solution for THERMA V

No Need to Install Separate Indoor Units; Just Connect the Outdoor Units

The cascade system allows more than one heat pump unit to work together to meet a property's heating, cooling and hot water needs. It is the perfect solution for buildings with variable thermal loads. (Residential Collective Housing, light commercial) Installing a Cascade Heat Pump system offers several significant advantages in terms of Performance, Flexibility, and Energy efficiency.

- · Modularity and scalability
- Optimal operation
- Installation flexibility
- Built-in redundancy and maintenance










High Efficient Operation

Exceptional Efficiency Exceeding SCOP 5 1)



1) Based on Average Climate and Low Temperature (35°C) condition

High efficient operation over wide heating capacity ranges



As it uses the highly efficient R290 Monobloc outdoor units, LG Cascade system also provides excellent efficiency across a wide range of capacities.

Easy Installation

Simplified Configuration and Wiring

Customer can save significant costs by reducing the cost for of purchasing and installing multiple indoor units (Control Units).



Extremely Quiet Operation

Extremely Quiet Operation Using the R290 Monobloc



Extremely low noise level unit available today

The sound power level of 49 dB(A) @ 12kW is outstanding in the market.

Sound nower level	R290 Monobloc					
Sound power level	7 kW	9 kW	12 kW	14 kW	16 kW	
Heating / Rated	49	50	49	51	52	

¹⁾ The certification (Quite Mark) for R290 Monobloc is valid for UK & EU territories only until Dec. 31st of 2025.

LG Cascade system with R290 Monobloc outdoor units provides a significantly now noise level.







THERMA V CASCADE CONTROL UNIT

Indoor unit

PHCM0 ENCXLEU



Product Specification

Indoor Unit			PHCMO ENCXLEU
Operation range	Heating (Min. ~ Max.)	°C	15 ~ 70
(leaving water temperature when combined to R290 Monobloc)	Cooling (Min. ~ Max.)	°C	5 ~ 27
	DHW (Min. ~ Max.)	°C	15 ~ 80
Dimension	H x W x D	mm	490 x 420 x 141
Weight	Net	kg	6.9
Exterior	Color of chassis / RAL code	-	Essence white / RAL 9003
Davis and the	Voltage, phase, frequency	V, Ø, Hz	220 ~ 240, 1, 50
Power supply	Recommended circuit breaker	А	10


- 1. Due to our policy of innovation, some specifications may be changed without notification.


 2. Wiring cable size must comply with the applicable local and national codes. Especially the power cable and circuit breaker should be selected in accordance with that.


 3. DHW 65 ~ 80°C Operating is available only when the booster heater is operating.


Drawings [Unit: mm]

PHCM0 ENCXLEU










Front view



ACCESSORIES

208 Accessories Provided by LG

212 Electric Backup Heater

214 LG Wi-Fi Modem

215 Domestic Hot Water Tank



THERMA V ACCESSORIES

Accessories Provided by LG

Category	Model name	Model number	Figure	Applicable product	Relevant function	Purpose	Feature
	Room temperature sensor	PQRSTA0	9	All except for R32 Monobloc 51 kW and Cascade Control Unit	Room temperature based control	To detect room air temperature for room temperature based control	• Max. wire length: 15 m
	Thermistor for 2 nd circuit or e/heater	PRSTAT5K10	0	All THERMA V products	2 nd circuit (mixing circuit)	To detect 2 nd circuit temperature when using 2 nd circuit function	• 5 kΩ thermistor, 10 m
	Outdoor air temperature sensor	PHATS0		R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW	Weather-dependent operation	To detect outdoor air temperature more accurately for weather-dependent operation especially when the outdoor unit is exposed to sunlight	Max. wire length: 12 m optional accessory - i.e pre-installed air sensor (mounted at grille of outdoor unit) will be used for weather- dependent operation if the outdoor air temperature sensor is not installed
				All except for Combi Units	Domestic hot water heating	To detect DHW tank temperature	Included in DHW tank kit Max. wire length: 12 m A harness that can be
1	Water tank sensor	PHRSTA0	•	R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW	Buffer tank temperature based control	To detect the temperature at the top of the buffer tank or at its outlet pipe if a big buffer tank is connected in parallel to the heat pump	connected to PCB- connector TB_SENSOR/BUFFER is included in this accessory produced after 1st of March 2024.
	3 way valve	OSHA-3 V		All except for Combi Units	Domestic hot water heating	To divert water flow between space heating and DHW heating	Size: DN 20 G 1" connection, male threaded
Valves	Thermostatic	OSHA-MV	Regardless of	Domestic	To blend hot water with cold water for ensuring	Size: 3/4" DN20 male threaded	
	mixing valve	OSHA-MV1		the model	hot water supply	constant, safe shower and bath outlet temp.	Size: 1" DN25 male threaded
	Domestic	OSHW-200 F				To generate and store domestic hot water	• Storage volume: 200 l, 300 l, 500 l
DHW	hot water tank (single coil)	OSHW-300 F		All except for	Domestic		Type: internal single coil Material: stainless steel Capacity of booster heater: 2.4 kW
Tanks	Domestic hot water tank (double coil)	OSHW-300 FD		All except for Combi Units	hot water heating		• Storage volume: 300 ℓ • Type: internal double coil • Material: stainless steel • Capacity of booster heater: 2.4 kW
		PHLTA		Hydro Unit for Split & Hydrosplit	Domestic	To control an external	Parts included: DHW tank sensor (thermistor), circuit breaker, relay
Installation kits		PHLTB	THERMAN.	hot water heating R32 Monobloc S, R32 Monobloc S I	DHW booster heater	Parts included: DHW tank sensor (thermistor), circuit breaker, relay, multi harness	
kits .	Solar thermal kit	PHLLA		All except for Combi Units	Solar thermal heat utilization	To operate with solar thermal system	• Length of thermistor: 12 m • Size of tube connector (W x H x D): 110 x 55 x 22

Category	Model name	Model number	Figure	Applicable product	Relevant function	Purpose	Feature
		HA031M E2 ●us					Heater capacity: 3 kW Number of heating coil: 1ea (3.0 kW) Size (W x H x D): 210 x 607 x 217 Power: 220 ~ 240 V, 1 Ø
		HA061M E2		R32 Monobloc S, R32 Monobloc S II 8	Capacity back up & emergency operation	To supplement insufficient capacity	Heater capacity: 6 kW Number of heating coil: 2 ea (3.0 + 3.0 kW) Size (W × H × D): 210 × 607 × 217 Power: 220 ~ 240 V, 1 Ø
Installation kits	Electric back-up heater	HA063M E2					Heater capacity: 6 kW Number of heating coil: 3 ea (2.0 + 2.0 + 2.0 kW) Size (W x H x D): 210 x 607 x 217 Power: 380 ~ 415 V, 3 Ø
		HA061C E1		R32 Hydrosplit Hydro Unit	Capacity back Up &	To supplement insufficient	Heater capacity: 6 kW Number of heating coil: 2 ea (3.0 + 3.0 kW) Power: 220-240 V, 1 Ø
		HA063C E1		(HN1600MC NK1)	emergency operation	capacity	Heater capacity: 6 kW Number of heating coil: 3 ea (2.0 + 2.0 + 2.0 kW) Power: 380-415 V, 3 Ø
	Buffer tank for space heating	OSHB-40KT		R32 Hydrosplit Combi Unit	-	To provide the buffer volume of water to the heating circuit	• Volume: 40 <i>l</i> • Size (W x H x D): 518 x 560 x 175
Vessel	Buffer tank for space heating	OSHE-12KT	R32 Hydrosplit - variations in th Combi Unit - tank due to ch		To absorb the pressure variations in the DHW tank due to changing temperatures	• Volume: 8 \(\epsilon \) • Connection: 3/4" • Max. pressure: 10 bar • Size (W x H x D): 416 x 238 x 502	
	Extension wire for a wired remote controller	PZCWRC1		All THERMA V products	-	To extend the wire between the wired remote controller and the indoor unit	• Length: 10 m
	Extension cable for Wi-Fi modem	PWYREW000		All THERMA V products	Wi-Fi control via LG ThinQ	To extend a wire between the WI-Fi modem and the indoor unit	• Length: 10 m
	2-remote control wire	PZCWRC2		All except for R32 Monobloc 51kW and Cascade Control Unit	2 remote control	To connect an additional remote controller (Slave)	• Length: 0.25 m
		PHDPB	-	R32 Split Hydro Unit (NK4 suffix), R410A Split Hydro Unit (NK3 suffix)		To collect condensed	
ETC	Drain pan	PHDPC		R290 Monobloc, R32 Hydrosplit , R32 Split Hydro Unit (NK5 suffix), R410A Split Hydro Unit (NK5 suffix)	Cooling operation	water in the indoor unit during the cooling operation	-
	Cover plate	PDC-HK10		All except for Monobloc unit and Cascade Control Unit	-	To fill the blank space of the indoor unit front panel when the remote controller is relocated indoors.	-
	Downward	PHDW36B0	ما <u>و و</u>	R290 Monobloc	-	To change the piping direction from backside	_
	piping kit	PHDW60B0	700	K290 Monobloc	-	direction from backside to downward	

THERMA V

THERMA V ACCESSORIES

Accessories Provided by LG

Category	Model name	Model number	Figure	Applicable product	Relevant function	Purpose	Feature												
Remote Controller	Wired remote controller	PREMTW101		All except for R32 Monobloc 51 kW and Cascade Control Unit	2 remote control	To control the AWHP using two remote controllers (an additional remote controller)	New modern design 4.3 inch color LCD display Information displayed with simple graphic, icon & text Built-in temperature sensor Size (W x H x D): 120 x 120 x 16 Extension cable (PZCWRC1, 9.6 m) and 2 remote cable (PZCWRC2, 0.25 m) are included												
	AC Ez Touch ¹⁾	PACEZA000	The state of the s				• 5 inch color display • User-friendly control with iconographic interface (touch screen) • Max. 32 unit control • Total 200 schedule events (weekly / monthly / yearly / exception day) • Operation history • Remote controller lock (all, temp, mode) • PC access supported (IPv6 supported) • DI 1 ea (emergency stop only) • Size (W x H x D): 137 x 121 x 25												
Central Controller	AC Smart 5 ¹⁾	PACS5A000		All THERMA V products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and Cascade Control Unit	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	products except for R290 Monobloc, R32 Monobloc S II, R32 Monobloc 51 kW and	Centralized control	To control the AWHP using LG central controller	• 10.2 inch color display • User-friendly control with iconographic interface (touch screen) • Max. IDU 64 • Total 100 schedule events (weekly / monthly / yearly / exception day) • History / operation trend • Interlock with 3 rd party equipment (ACS IO, ACU IO module is needed) • Error alarm by e-mail • Remote controller lock (all, temp, mode) • Map view (visual navigation) • Web access supported with HTML5 (PC, smartphone, tablet) • DI 2 ea, DO 2 ea • BACnet IP/ modbus TCP protocol support • Size (W x H x D): 253.2 x 167.7 x 28.9
	ACP 5 ⁻¹⁾	PACP5A000	### The state of				Web access controller Max. 128 unit control Total 100 schedule events (weekly / monthly / yearly / exception day) History / operation trend Interlock with 3rd party equipment (ACS IO, ACU IO module is needed) Error alarm by e-mail Remote controller lock (all, temp, mode) Map view (visual navigation) DI 10 ea, DO 4 ea BACnet IP/ modbus TCP protocol support Lonworks protocol support* (max. 64 unit control) Size (W x H x D): 270 x 155 x 65												

^{*} For using Lonworks protocol, only ACP 5 provides interface for BMS integration, and, need to U60FT module between ACP 5 and BMS system interface between Lonworks FT-10 BMS and LG HVAC unit. U60FT should be purchased separately from 3rd party supplier. Please contact regional LG office for more detailed information.

Category	Model name	Model number	Figure	Applicable product	Relevant function	Purpose	Feature
Gateway	Modbus RTU gateway	PMBUSB00A	© re JMH: H4	All except for R32 Monobloc 51 kW	Centralized control	To communicate and control through the central controller (providing modbus RTU connection between the AWHP and BMS)	Modbus RTU slave (RS485) / 9,600 bps Size (W x H x D): 53.6 x 89.7 x 60.7 Max. 16 IDUs with single module / Max. 64 IDUs with 4 modules Power: DC 12 V
	PI485 gateway for THERMA V ¹⁾	PP485A00T		All except for R290 Monobloc, R32 Monobloc S II and R32 Monobloc 51 kW		To communicate and control through the central controller (converting LG protocol to RS485 protocol)	• 1 for each outdoor unit • Power: supplied by outdoor unit
	Simple dry contact	PDRYCB000					• 1 Set per 1 unit • 1 Input contact for turning on/off • Input power: 220 ~ 240 V • 2 output contacts • Operation status - Error status
Dry contact	Dry	PDRYCB320		All THERMA V products	-	To connect between the AWHP and external devices to control various functions	1 Set per 1 unit Non voltage or 12 ~ 24 V 8 digital input contacts for thermostat On/off, operation mode, DHW heating Emergency mode, silent mode 2 Output contacts Operation status - Error status
	LG Wi-Fi modem	PWFMDD200	• LG	All THERMA V products	Wi-Fi control via LG ThinQ	To control the AWHP via a smartphone	Basic control function On/off, operation mode, set temp DHW heating and set temp Weekly on/off schedule Error status check Frequency: 2.4 GHz IEEE 802.11b/g/n supported
ETC	Cloud gateway ¹⁾	PWFMDB200	enter Out	R290 Monobloc, R32 Monobloc S II, R32 Split Combi Unit, New Hydro Unit for Split & Hydrosplit	LG BECON cloud service	For remote control, monitoring and diagnosis	Max 16 indoor units RS485: 1 channel (LGAP) Wired/wireless LAN Power: 12 V DC Size (W x H x D): 120 x 120 x 29
	Meter interface	PENKTH000	STEERING TO THE STREET OF THE	All THERMA V products	Energy monitoring	To measure production / consumption power	Energy meter interface to monitor Electricity and Heat energy Max. 3 watt

¹⁾ PI485 Gateway (PP485A00T) should be installed on outdoor unit to use the central controller and cloud gateway.

In the case of R290 Monobloc and R32 Monobloc S II, PI485 G/W is built-in, so there is no need to purchase it separately.

THERMA V ACCESSORIES **ELECTRIC BACKUP HEATER**

Electric Backup Heater

HA031M E2 HA061M E2 HA063ME2




Backup Heater Specification

Electrical Specification		Unit	HA031M E2	HA061M E2	HA063M E2
	Туре	-		Sheath	
	Number of heating coil	EA	1	2	3
	Capacity combination	kW	3.0	3.0 + 3.0	2.0 + 2.0 + 2.0
D 1 1 .	Heating steps	Step	1	2	1
Backup heater	Power supply	V, Ø, Hz	220 ~ 240, 1, 50		380 ~ 415, 3, 50
	Rated running current	А	12.5	25.0	8.7
	Dimensions (H x W x D)	mm		607 x 210 x 217	
	Net weight (unit)	kg	12.8	13.4	13.1
Wiring connections	Power supply cable (included earth, H07RN-F)	mm² x cores	1.5 x 3 C	4.0 x 3 C	2.5 x 4 C
Wiring connections	Communication cable (H07RN-F)	mm² x cores	0.75	x 4 C	0.75 x 2 C


212

Drawings [Unit: mm]





Right side panel detail







Right side view








Internal front





3D view

Internal front

Internal right side



Front view

No.	Part Name	Description
1	Leaving Water Pipe	Male PT 1" according to ISO 7-1 (Tapered pipe threads)
2	Entering Water Pipe Male PT 1" according to ISO 7-1 (Tapered pipe threads)	
3	Control Box	Circuit Breaker, Magnetic Switch, Terminal blocks
4	Thermal Switch	Cut-off Power Input to E/heater at 90°C
5	Air Vent	Air Purging when Charging Water
6	Electric Heater	Support the Space Heating at Very Cold Temperature and in Case of Emergency
7	Backup Heater Outlet Sensor	Connect to Unit (Heat pump)
8	Access Hole for Air Vent Valve	Access Hole for Operating the Air Vent Valve During Water Charging

^{*} Compatible with R32 Monobloc S and R32 Monobloc S II series

 $^{{\}it 1.}\ {\it Due\ to\ our\ policy\ of\ innovation\ some\ specifications\ may\ be\ changed\ without\ notification.}$

 $^{2. \} Wiring \ cable \ size \ must \ comply \ with \ the \ applicable \ local \ and \ national \ codes.$

Especially the power cable and circuit breaker should be selected in accordance with that.

THERMA V **ACCESSORIES**

LG Wi-Fi Modem

PWFMDD200 ENCXLEU

Access LG THERMA V anytime and from anywhere with a Wi-Fi equipped device. LG's exclusive home appliances control app (LG ThinQ) offers simple operation and various functions.

- On / Off
- Operation mode selection
- Current temperature
- Set temperature
- On / Off reservation scheduling
- Energy monitoring
- ESS monitoring
- Silent mode reservation
- Holiday mode
- Quick DHW heating



Model Name	PWFMDD200 ENCXLEU
Size (mm)	46 x 68 x 14
Interfaceable products	All THERMA V line-ups
Connection type	Indoor unit 1:1
Communication frequency	2.4 GHz
Wireless standards	IEEE 802.11b/g/n
Mobile application	LG ThinQ (Android v7.0 (Nougat) or higher, iPhone iOS 11.0 or higher)
Optional extension cable	PWYREW000 (10 m extension)

214

- 1. Functionality may be different according to each Indoor model.
- 2. User interface of application shall be revised for its design and contents improvement.
- 3. Application is optimized for smartphone use, so it may not be well functioning with tablet devices. - For the compatibility with indoor unit, please contact regional office.

Domestic Hot Water Tank

OSHW-200F AEU OSHW-300F AEU OSHW-500F AEU OSHW-300FD AEU



Technical Specification		Unit	OSHW-200F	OSHW-300F	OSHW-500F	OSHW-300FD
General characteristics	Water volume	l.	200	300	500	300
	Diameter	mm	640	640	810	640
	Height	mm	1,350	1,850	1,900	1,850
	Net weight	kg	61	100	146	106
	Tank materials	-	STS: F18	STS: F18	STS: F18	STS: F18
	Color	-	Gray (RAL 7035)	Gray (RAL 7035)	Gray (RAL 7035)	Gray (RAL 7035)
Specification of electric back up	Additional electric heater	W	2,400	2,400	2,400	2,400
	Power supply	V, Ø, Hz	230, 1, 50 (60)	230, 1, 50 (60)	230, 1, 50 (60)	230, 1, 50 (60)
	Adjustable thermostat	°C	0 ~ 90	0 ~ 90	0 ~ 90	0 ~ 90
Specification of heat exchanger	Exchanger type	-	Internal single coil	Internal single coil	Internal single coil	Internal double coil
	Material exchanger	-	STS: F18	STS: F18	STS: F18	STS: F18
	Maximum water temp.	°C	90	90	90	90
	Coil surface	m²	2.3	3.1	4.8	3.1 + 1
Water connections	Heat pump inlet	inch	1 BSP female	1 BSP female	1 ¼ BSP female	1 BSP female (upper coil)
	Heat pump outlet	inch	1 BSP female	1 BSP female	1 ¼ BSP female	1 BSP female (upper coil)
	Solar inlet	inch	-	-	-	% BSP Female (lower coil)
	Solar outlet	inch	-	-	-	% BSP Female (lower coil)
	City water inlet	inch	¾ BSP male	¾ BSP male	1 BSP male	¾ BSP male
	Hot water outlet	inch	¾ BSP female	1 BSP female	1 BSP female	1 BSP female
Energy efficiency class (A+ to F scale)		-	В	В	В	В
Standing heat loss		W	61	70	83	70
Technical Specification						
Domestic hot water tank installation kit			PHLTA (R290 Monobloc, Hydro Unit for Split & Hydrosplit), PHLTB (Monobloc)			

OSHA-MV

OSHA-MV1

OSHA-3V

215

Technical Specification

3 way valve

Thermostatic mixing valve (3/4" DN20)

Thermostatic mixing valve (1" DN25)